DESCRIPTION: DSUB IP67 FLANGE // FEMALE // STANDARD // SOLDER CUP

DIMENSIONS(mm)			
SIZE	A	B	C
9	39.50	25.00	16.30
15	48.00	33.30	24.60
25	61.50	47.05	38.40
37	77.80	63.50	54.80

NOTE:

MATERIAL


HOUSING	PBT UL94V-0, BLACK
FLANGE	PBT UL94V-0, BLACK
CONTACT	BRASS, PLATING P/N KEY BELOW
SHELL	STEEL, NICKEL
O-RING	SILICONE
SEALING COMPOUND	EPOXY
HARDWARE	BRASS; NICKEL PLATED

ELECTRICAL

RATED CURRENT	5A
VOLTAGE	1000 VAC 1 MIN
INSULATOR RESISTANCE	5 GOhms MIN.
CONTACT RESISTANCE	10 mOhms MAX.
WATER PROOF	IP67

ENVIRONMENT

OPERATION TEMPERATURE	-25°C TO +85°C



SDF-SYY-203LYYY

SERIES
- SDF = STANDARD DSUB FLANGE

CONTACT TYPE
- S = SOLDER CUP

POSITIONS
- 09
- 15
- 25
- 37

GENDER
- 2 = FEMALE

HARDWARE OPTIONS
- 01 = 4-40 THREADED INSERTS/4-40 JACKSCREWS

CONTACT PLATING OPTIONS
- 1 = GOLD FLASH
- 2 = 30u" GOLD PLATING

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL

DATE: 03/02/2020

TOLERANCES
X. ±0.40
.X ±0.30
.XX ±0.20
.XXX ±0.10

NorComp

SCALE: NTS

SHEET 1 OF 1

REV 1

DWG NO. SDF-SYY-203LYYY