

Features:

- Precision metal film
- Superior electrical, TCR performances
- Flame-retardant coatings are standard
- Panasert available selected sizes (contact Stackpole)
- RNMF (mini) an ideal choice where size constraints apply
- RNF 5% replaces MP series
- Lower or higher resistance values may be possible (contact Stackpole)
- RoHS compliant, REACH compliant, lead free, and halogen free




Electrical Specifications												
Type/Code	Mil Ref	Power Rating (W) @ 70°C	Maximum Working Voltage (Vrms) ⁽¹⁾	Maximum Overload Voltage (Vrms)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance						
						0.05%	0.1%	0.25%	0.5%	1%	2%	5%
RNF18	RN 50	0.125	200	400	± 25 ± 50 ± 100	100 - 100K	100 - 100K	100 - 100K	30.1 - 499K	49.9 - 499K	-	
							51.1 - 100K		10 - 1M	1 - 1M ^(*) 1 - 10M ^(*)		
												1 - 22M ^(*)
RNMF14	-	0.25	200	400	± 25 ± 50 ± 100	-	100 - 100K		30.1 - 499K	30.1 - 499K	-	
									10 - 1M	1 - 1M ^(*) 1 - 2.15M ^(*)		
											1 - 2.2M ^(*)	
RNF14	RN 55	0.25	250	500	± 10 ± 25 ± 50 ± 100	100 - 100K	100 - 100K	-		-	-	
							1 - 2.2M ^(*)		10 - 1M			
									1 - 5.11M ^(*) 1 - 10M ^(*)			1.1M - 10M ^(*)
										5.6 - 10M ^(*)	1 - 10M ^(*)	
RNMF12	RL 07	0.5	350	600	± 25 ± 50 ± 100	-	30.1 - 294K		49.9 - 1M		-	
							30.1 - 1M	10 - 1M	1 - 1M ^(*) 1 - 10M ^(*)			
											1 - 10M ^(*)	
RNF12	RN 60	0.5	350	700	± 25 ± 50 ± 100	100 - 100K			49.9 - 499K		-	
									10 - 1M	1 - 4.99M ^(*) 1 - 10M ^(*)		
												1 - 10M ^(*)
RNF1	RN 65	1	350	700	± 25 ± 50 ± 100	-			-		-	-
									10 - 1M	10 - 470K 1 - 1M ^(*)		
RNF2	-	2	350	800	± 25 ± 50 ± 100	-			-	-	-	
									10 - 1M		10 - 1M	

(1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage

(*) Contact Stackpole for resistance values below 10 ohms and above 1M.

Mechanical Specifications




Type/Code	A Body Length	B Body Diameter	C Lead Length (Bulk)	D Lead Diameter	Unit
RNF18	0.130 ± 0.012 3.30 ± 0.30	0.071 ± 0.012 1.80 ± 0.30	1.102 ± 0.118 28.00 ± 3.00	0.018 ± 0.003 0.45 ± 0.07	inches mm
RNMF14	0.130 ± 0.012 3.30 ± 0.30	0.070 ± 0.003 1.78 ± 0.08	1.102 ± 0.118 28.00 ± 3.00	0.017 ± 0.002 0.44 ± 0.05	inches mm
RNF14	0.250 ± 0.026 6.35 ± 0.65	0.093 ± 0.010 2.35 ± 0.25	1.102 ± 0.118 28.00 ± 3.00	0.022 ± 0.003 0.56 ± 0.08	inches mm
RNMF12	0.250 ± 0.026 6.35 ± 0.65	0.093 ± 0.010 2.35 ± 0.25	1.102 ± 0.118 28.00 ± 3.00	0.022 ± 0.003 0.56 ± 0.08	inches mm
RNF12	0.344 ± 0.030 8.75 ± 0.75	0.108 ± 0.039 2.75 ± 1.00	1.102 ± 0.197 28.00 ± 5.00	0.026 ± 0.004 0.65 ± 0.10	inches mm
RNF1 (< 10Ω)	0.453 ± 0.039 11.50 ± 1.00	0.177 ± 0.020 4.50 ± 0.50	1.378 ± 0.079 35.00 ± 2.00	0.031 ± 0.001 0.78 ± 0.03	inches mm
RNF1 (≥ 10Ω)	0.433 ± 0.039 11.00 ± 1.00	0.177 ± 0.020 4.50 ± 0.50	1.181 ± 0.118 30.00 ± 3.00	0.030 ± 0.002 0.75 ± 0.05	inches mm
RNF2	0.591 ± 0.039 15.00 ± 1.00	0.197 ± 0.020 5.00 ± 0.50	1.339 ± 0.157 34.00 ± 4.00	0.028 ± 0.004 0.70 ± 0.10	inches mm


Performance Characteristics

Test	Test Method	Typical Results	Test Limits
Insulation Resistance	JIS C5201-1, IEC60115-1, 4.6	≥ 1000M Ω	≥ 1000M Ω
Voltage Proof / DWV		RNF16 / RNMF14: 300 RNF14 / RNMF12: 500 RNF12 / RNF1: 700	≤ ± (0.5% + 0.05Ω) No mechanical damage
Short Time Overload	JIS C5201-1, IEC60115-1, 4.13	< ± 0.1%	≤ ± (0.25% + 0.05Ω)
Resistance to Solder Heat	JIS C5201-1, IEC60115-1, 4.18	< ± 0.1%	≤ ± (0.3% + 0.05Ω)
Rapid Change of Temperature	JIS C5201-1, IEC60115-1, 4.19	< ± 0.05%	≤ ± (0.35% + 0.05Ω)
Endurance at 70°C	JIS C5201-1, IEC60115-1, 4.25.1	< ± 0.15%	≤ ± (1.0% + 0.05Ω)
Robustness of Terminations	JIS C5201-1, IEC60115-1, 4.16	< ± 0.10%	≤ ± (0.2% + 0.05Ω)
Damp Heat (Steady state)	JIS C5201-1, IEC60115-1, 4.24	< ± 0.10%	≤ ± (1.5% + 0.05Ω)

Operating temperature range is -55°C to +155°C

Power Derating Curve:





Repetitive Pulse Information:


If repetitive pulses are applied to resistors, pulse wave form must be less than “pulse limiting voltage”, “pulse limiting current” or “pulse limiting wattage” calculated by the formula below.

$$V_p = K\sqrt{P \times R \times T/t}$$

$$I_p = K\sqrt{P/R \times T/t}$$

$$P_p = K^2 \times P \times T/t$$


Where: V_p : Pulse limiting voltage (V)
 I_p : Pulse limiting current (A)
 P_p : Pulse limiting wattage (W)
 P : Power rating (W)
 R : Nominal resistance (ohm)
 T : Repetitive period (sec)
 t : Pulse duration (sec)
 K : RNF / RNMF Coefficient: 0.7
 $[V_r$: Rated Voltage (V), I_r : Rated Current (A)]




- Note 1: If $T > 10 \rightarrow T = 10$ (sec), $T/t > 1000 \rightarrow T/t = 1000$
 Note 2: If $T > 10$ and $T/t > 1000$, “Pulse Limiting power (Single pulse) is applied
 Note 3: If $V_p < V_r$ ($I_p < I_r$ or $P_p < P$), V_r (I_r , P) is V_p (I_p , P_p)
 Note 4: Pulse limiting voltage (current, wattage) is applied at less than rated ambient temperature.
 If ambient temperature is more than the rated temperature (70 °C), decrease power rating according to “Power Derating Curve”
 Note 5: Assure sufficient margin for use period and conditions for “pulse limiting voltage”
 Note 6: If the pulse waveform is not square wave, judge after transform the waveform into square wave according to the “Waveform Transformation to Square Wave”.

Waveform Transformation to Square Wave


1. Discharge curve wave with time constant "t" → Square wave




2. Damping oscillation wave with time constant of envelope "t" → Square wave




3. Half-wave rectification wave → Square wave



4. Triangular wave → Square wave



5. Special wave → Square wave




Recommended Soldering Condition

Flow Soldering:


- Pre-heating: 110°C MAX
- Peak temperature/duration: 260°C within 10 seconds (1st, 2nd wave total)
- Temperature profile (see chart on the right)

Iron Soldering:

- 380°C, 5 seconds, once/terminal



Reel Specifications




Series	A max ⁽¹⁾	B max	C	D ⁽²⁾	Tape	Unit
RNF18	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNMF14	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNF14	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNMF12	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNF12	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNF1	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm
RNF2	2.756 ± 0.118 70.00 ± 3.00	11.811 ± 0.197 300.00 ± 5.00	0.197 ± 0.020 5.00 ± 0.50	2.047 ± 0.020 52.00 ± 0.50	0.250 6.35	inches mm

Dimension "E": This is a non-critical dimension that does not have a tolerance in the standard.

Range of diameters is from 0.547 inches (13.90 mm) to 1.500 inches (38.10 mm).

- (1) Reference value only. The "A" dimension shall be governed by the overall length of the taped component. The distance between flanges shall be 0.059 inches (1.50 mm) to 0.315 (8.00 mm) greater than the overall component.
- (2) The given dimension "D" expresses the standard width spacing.

Ammo Packaging Specifications



Type/Code	Size	A	B	C	Unit
RNF	16	2.953 ± 0.079 75.00 ± 2.00	2.756 ± 0.118 70.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
RNF	14	2.953 ± 0.079 75.00 ± 2.00	3.937 ± 0.118 100.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
RNF	12	2.953 ± 0.079 75.00 ± 2.00	2.756 ± 0.118 70.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
RNF	1	2.953 ± 0.079 75.00 ± 2.00	2.953 ± 0.118 75.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
RNMF	14	2.953 ± 0.079 75.00 ± 2.00	2.756 ± 0.118 70.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
RNMF	12	2.953 ± 0.079 75.00 ± 2.00	3.937 ± 0.118 100.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm

Rev Date: 3/30/2023 7 www.seielect.com
 This specification may be changed at any time without prior notice. marketing@seielect.com
 Please confirm technical specifications before use.

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 2). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament.

RoHS Compliance Status						
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
RNF	General Purpose Metal Film Leaded Resistor	Axial	YES	99.3/0.7 Sn/Cu 100% Matte Sn	Apr-05 (Japan) Jan-04 (Taiwan, China)	05/14 04/01
RNMF	General Purpose Mini Metal Film Leaded Resistor	Axial	YES	99.3/0.7 Sn/Cu 100% Matte Sn	Apr-05 (Japan) Jan-04 (Taiwan, China)	05/14 04/01

"Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the Eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

How to Order

R		N		F		1		4		F		T		D		4		K		7		5	
Product Series		Power Rating		Tolerance			Packaging				TCR		Resistance Value										
Code	Description	Code	W	Code	Tol	Value	Code	Description	Size	Quantity	Code	ppm	Four characters with the multiplier used as the decimal holder. 10 ohm = 10R0 10.2 K ohm = 10K2 1 M ohm = 1M00										
RNF	Standard	18	0.125	A	0.05%	E96 E24	T	Tape and Reel	RNF18, RNF14 RNMF14, RNMF12	5000	T	10											
RNMF	Mini	14	0.25	B	0.1%				RNF12, RNF1	2500	E	25											
PRNF	Panaset RoHS	12	0.5	C	0.25%				RNF2	1000	C	50											
		1	1	D	0.5%		A	Ammo	RNF18, RNF14 RNMF14, RNMF12	5000 (*)	D	100											
		2	2	F	1%	E24			RNF12	2000													
				G	2%				RNF1, RNF2	1000													
				J	5%		B	Bulk	RNF18, RNF14, RNF12, RNF1, RNF2, RNMF12, RNMF14	1000													

(*) Precision metal film resistors with tolerances <1% may be available in smaller quantities. Contact Stackpole for more details.