

Search

Amphenol Pcd #

Find

Cross Reference #

Find

Locate inventory

Find

SJS620100

Series:	Push & Snap
Type:	Plug, inline
Length (in/cm):	1.079/2.74
Diameter (in/cm):	0.7/1.78
Weight (oz/g):	0.15/4.3
Key:	A
Mated Length (in/cm):	1.68/4.27
Mating Half:	SJS620200
Shell Size:	Size 8
Color:	Red
Contact Qty:	3
Contact Qty Range:	1 -- 3
Contact Size:	20
Mil-Spec:	M39029/56-351, socket
Contact Type:	Socket
Crimp Tool, Basic:	M22520/1-01
Crimp Tool, Positioner:	M22520/1-04
Installation Tool:	M81969/14-02
Removal Tool:	M81969/14-02
QPL:	BACC63DE0320SA
With or Without:	Without
Cradle:	N/A
Body:	Polyamide 6/6 (Nylon)
Grommet:	Silicone Rubber
Contact Retainers:	Stainless Steel
Temperature Range:	- 65C to 155C
Insulation Resistance:	> 5000 Megaohms Min.
Dielectric Withstanding:	1500Vrms @ Sea Level
Voltage:	600Vrms @ 45,000 Ft. Alt.
Current Ratings:	7.5
Engineering Drawing:	 SJS620100_C.pdf
Datasheet:	 Luminus-data-sheet-2012.pdf