

Part Number:	DRAWN	
SM400204-1	CJ	2/7/2018
	CHECKED J.S.	2/8/2018
Description: Dynamic Speaker	APPROVED C.E.	2/8/2018

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions
Sound Pressure Level	99	dB (@ 10cm), Avg.
Resonant Frequency	220	Hz
Frequency Range	220 ~ 20,000	Hz
Nominal Power	3	W
Max. Power	4	W
Impedance	4	Ω
Cone Material	PU + Aluminum	
Mount Type	Flush Mount	
Storage Temperature	-20 ~ +55	°C
Operating Temperature	-20 ~ +55	°C
Weight	18.5	g

REVISION HISTORY

REV	DESCRIPTION	DATE	APPROVED
	Released from Engineering	2/8/2018	C.E.
1	Removed lead wires	2/19/2018	C.E.
2	Updated tolerances	4/19/2018	C.E.

NOTES

1) All dimensions are in mm unless otherwise noted
2) All tolerances are ± 0.5 mm unless otherwise noted
3) All parts meet RoHS
4) Subject to change or redrawn without notice