

NOTES:

1. ALLOWABLE FLEXIBLE LIGHT PIPE CUT LENGTH AVAILABLE IN INCREMENTS OF 0.1".
2. MINIMUM BEND RADIUS OF FLEXIBLE LIGHT PIPE: 1.22" [31mm].
3. COMPONENTS SHIPPED NON-ASSEMBLED.








TABLE 1 - LENGTH	
LENGTH (L)*	TOLERANCE
1.00" - 16.00"	±0.05"
16.1" - 40.00"	±0.15"
40.1" - 80.00"	±0.30"
80.1" - 3,940.00"	±0.5%

*AVAILABLE IN 0.1" INCREMENTS



CUSTOMER USE DRAWING

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		BIVAR® 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
DECIMALS	ANGULAR	TITLE: FLP ASSEMBLY WITH SMFLP ADAPTER, LC2	
.X ± .1	X° ± 1°		
.XX ± .02			
.XXX ± .010			
		TITLE: FLP ASSEMBLY WITH SMFLP ADAPTER, LC2	
DESIGNED: B. OLIVER	DATE: 9/14/2009	DRAWING NO: SMFLP2-X.X REVISION: D	
REVISED: K. BARON	DATE: 4/24/2024	SHEET SIZE	A CAGE CODE: 32559
CHECKED: A. VALDEZ	DATE: 4/24/2024	SCALE: 2:1	SHEET # 1 OF 1
CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING			