NextGen Components,Inc.

PART CODE: SOT23BC846AS1A

SPECIFICATION SHEET

SPECIFICATION SHEET NO.	P0610- SOT23BC846AS1A
DATE	June 10, 2022
REVISION	A0
DESCRIPITION	SMD Plastic-Encapsulate Transistors, SOT-23 series, 3 pads BC846A Type, NPN, Collector-Emitter Voltage 65V. Collector Current 100mA Max. Operating Temp. Range -65°C ~+150°C, Package in Tape/Reel, 3000pcs/Reel RoHS/RoHS III compliant
CUSTOMER	
CUSTOMER PART NUMBER	
CROSS REF. PART NUMBER	
ORIGINAL PART NUMBER	MDD BC846A
PART CODE	SOT23BC846AS1A

VENDOR APPROVE
Issued/Checked/Approved   
DATE: June 10, 2022

CUSTOMER APPROVE
DATE:

NextGen Components,Inc.

PART CODE: SOT23BC846AS1A

SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES

MAIN FEATURE

- Ideally suited for automatic insertion

APPLICATION

- For Switching and AF Amplifier Applications

RFQ
Request For Quotation

PART CODE GUIDE

SOT23	BC846A	S	1A
1	2	3	4

1) **SOT23:** SMD Plastic-Encapsulate Transistors, 3 pads SOT-23 series Code

2) **BC846A**: Type code for BC846A Type

3) **S**: Package code, Package in Tape/Reel, 3000pcs/Reel

4) **1A:** Marking code for "1A" on the case surface, Different Marking for different specification

MORE ITEMS LIST


SOT23BC846AS1A	SOT23BC846BS1B	
SOT23BC847AS1E	SOT23BC847BS1F	SOT23BC847CS1G
SOT23BC848AS1J	SOT23BC848BS1K	SOT23BC848CS1L

PART CODE: SOT23BC846AS1A

SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES


DIMENSION (Unit: Inch/mm)


Image for reference



Marking: 1A


SOT-23






Symbol	Value (mm)		
	Min.	Typ.	Max.
A	1.00		1.40
A1			0.10
b	0.35		0.50
c	0.10		0.20
D	2.70	2.90	3.10
E	1.40		1.60
E1	2.40		2.80
e		1.90	
L	0.10		0.30
L1	0.40		
θ	0°		10°

Recommend Pad Layout





1.Base
2.Emitter
3.Collector

SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES

MECHANICAL DATA

Case	Terminals	Polarity	Mounting Position	Weight per piece
JEDEC SOT-23 molded plastic body	Solder plated, Solderable per MIL-STD-750, Method 2026	Polarity symbol marking on case	Any	0.00019 Ounce, 0.00591 grams

MAX. RATINGS AT Ta=25 °C

Parameter	SYMBOLS	VALUE	UNITS
		LIMIT	
Collector-base Voltage	V_{CBO}	80	Volts
Collector-emitter Voltage	V_{CEO}	65	Volts
Emitter-base Voltage	V_{EBO}	6	Volts
Collector Current - Continuous	I_C	0.10	A
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_J	+150	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C


ELECTRICAL CHARACTERISTICS AT Ta= 25 °C

Parameter	SYMBOLS	VALUE			UNIT	Condition
		Min.	Typ.	Max.		
Collector-base Breakdown Voltage	V_{CBO}	80			V	I_C= 10 µA, I_E=0
Collector-emitter Breakdown Voltage	V_{CEO}	65			V	I_C= 10mA, I_B=0
Emitter-base Breakdown Voltage	V_{EBO}	6			V	I_E= 10 µA, I_C=0
Collector Cut-off Current	I_{CBO}			0.1	µA	V_{CB}=70V, I_E=0
Collector Cut-off Current	I_{CEO}			0.1	µA	V_{CB}=60V, I_B=0
Emitter Cut-off Current	I_{EBO}			0.1	µA	V_{EB}= 5V, I_C=0
DC Current Gain	h_{FE}	110		220		V_{CE}=5V, I_C=2 mA
Collector-emitter Saturation Voltage	$V_{CE(sat)}$			0.5	V	I_C=100mA, I_B=5 mA
Base-emitter Saturation Voltage	$V_{BE(sat)}$			1.1	V	I_C=100mA, I_B=5 mA
Transition Frequency	f_T		100		MHz	V_{CE}=5 V, I_C=10mA f= 100 MHz
Collector output capacitance	C_{ob}			4.5	pF	V_{CB}=10 V, f=1 MHz

RELIABILITY

Number	Experiment Items	Experiment Method And Conditions	Reference Documents
1	Solder Resistance Test	Test 260°C± 5°C for 10 ± 2 sec. Immerse body into solder 1/16" ± 1/32"	MIL-STD-750D METHOD-2031.2
2	Solderability Test	230°C ±5°C for 5 sec.	MIL-STD-750D METHOD-2026.1 0
3	Pull Test	1 kg in axial lead direction for 10 sec.	MIL-STD-750D METHOD-2036.4
4	Bend Test	0.5Kg Weight Applied To Each Lead, Bending Arcs 90 °C ± 5 °C For 3 Times	MIL-STD-750D METHOD-2036.4
5	High Temperature Reverse Bias Test	T_A=100°C for 1000 Hours at V_R=80% Rated V_R	MIL-STD-750D METHOD-1038.4
6	Forward Operation Life Test	TA=25°C Rated Average Rectified Current	MIL-STD-750D METHOD-1027.3
7	Intermittent Operation Life Test	On state: 5 min with rated IRMS Power Off state: 5 min with Cool Forced Air. On and off for 1000 cycles.	MIL-STD-750D METHOD-1036.3
8	Pressure Cooker Test	15 PSIG, T_A=121°C, 4 hours	MIL-S-19500 APPENOIXC
9	Temperature Cycling Test	-55°C~+125°C; 30 Minutes For Dwelled Time 5 minutes for transferred time. Total: 10 cycles.	MIL-STD-750D METHOD-1051.7
10	Thermal Shock Test	0°C for 5 minutes., 100°C for 5minutes, Total: 10 cycles	MIL-STD-750D METHOD-1056.7
11	Forward Surge Test	8.3ms Single Sale Sine-wave One Surge.	MIL-STD-750D METHOD-4066.4
12	Humidity Test	T_A=65°C, RH=98% for 1000 hours.	MIL-STD-750D METHOD-1021.3
13	High Temperature Storage life Test	150°C for 1000 Hours	MIL-STD-750D METHOD-1031.5


SUGGESTED REFLOW PROFILE (For Reference Only)





- Recommended peak temperature is over 245℃, If peak temperature is below 245 ℃, you may adjust the following parameters; time length of peak temperature (longer), time length of soldering (longer), thickness of solder paste (thicker)
- Welding shall not exceed 2 times
- Remark: lead free solder paste (96.5 sn/3.0 Ag/0.5Cu)


SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES

RATINGS AND CHARACTERISTIC CURVES (For Reference Only)













SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES

RATINGS AND CHARACTERISTIC CURVES (For Reference Only)













TAPE/REEL (Unit: mm)

All Devices are packed in accordance with EIA standard RS-481-A and specifications.









Item	Symbol	Tolerance	SOT-23
Carrier width	A	0.1	3.15
Carrier Length	B	0.1	2.77
Carrier Depth	C	0.1	1.22
Sprocket hole	d	0.05	1.55
7”Reel outside diameter	D	2.0	178.00
7”Reel inner diameter	D1	Min.	54.4
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.1	0.25
Tape width	W	0.3	8.00
Reel width	W1	1.0	19.50

SMD PLASTIC-ENCCAPULATE TRANSISTORS SOT23 SERIES

PACKAGE

Case Code	SOT-23
Reel Size	7”
Reel Size	178 mm
MPQ/Reel	3000 pcs
Qty. /Box	6000 pcs
G.W/Box	1 LBS

DISCLAIMER

NextGen Component, Inc. reserves the right to make changes to the product(s) and or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information