

SS2020FL~SS20100FL

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER


VOLTAGE 20 to 100 Volt **CURRENT** 2 Ampere

FEATURES



- Fast switching speed
- Surface mount package ideally suited for automatic insertion
- Low power loss, high efficiency
- Ultra thin profile package for space constrained utilization
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

MECHANICAL DATA

- Case : SOD-123FL, Plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0006 ounces, 0.017 grams.
- Polarity : Color band denotes cathode end



SOD-123FL Unit : inch(mm)



ABSOLUTE RATINGS

PARAMETER	SYMBOL	SS2020FL	SS2030FL	SS2040FL	SS2060FL	SS20100FL	UNITS
Marking Code		GM	GN	GP	GQ	GR	
Reverse Voltage	V_R	20	30	40	60	100	V
Peak Reversr Voltage	V_{RRM}	20	30	40	60	100	V
Average Rectified Current at $T_A=75^{\circ}\text{C}$	$I_{F(AV)}$	2					A
Non-repetitive Peak Forward Surge Current at $t=8.3\text{ms}$	I_{FSM}	50					A

ELECTRICAL AND THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	SS2020FL	SS2030FL	SS2040FL	SS2060FL	SS20100FL	UNITS
Minimum Reverse Breakdown Voltage at I _R =500μA	V _R	20	30	40	60	100	V
Maximum Forward Voltage at I _F =2A	V _F	0.5			0.7	0.85	V
Reverse Leakage Current at V _{RRM}	I _R	100			40		μA
Typical Thermal Resistance, Junction to Ambient	R _{θJA}	60					°C/W
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-50 to +150					°C

Note:1 Mounted with minimum recommended pad size, PC Board FR4.

2. $T_A=25^{\circ}\text{C}$ unless otherwise specified.

SS2020FL~SS20100FL

Rating and Characteristic Curves




FIG. 1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTIC




FIG. 3 TYPICAL JUNCTION CHARACTERISTIC




FIG. 4 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





Fig.5 Operating Temperature Derating Curve

SS2020FL~SS20100FL

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

SS2020FL~SS20100FL

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.