STH180N10F3-6

N-channel 100 V, 3.9 mΩ typ.,180 A, STripFET™ F3 Power MOSFET in H²PAK-6 package

Datasheet - production data





Figure 1: Internal schematic diagram



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STH180N10F3-6	100 V	4.5 mΩ	180 A

- Low on-resistence $R_{DS(on)}$
- 100% avalanche tested

Applications

- Switching applications

Description

This device is an N-channel Power MOSFET developed using STripFET™ F3 technology. It is designed to minimize on-resistance and gate charge to provide superior switching performance.

Table 1: Device summary

Order code	Marking	Package	Packing
STH180N10F3-6	180N10F3	H²PAK-6	Tape and reel

Obsolete Product(s) - Obsolete Product(s)

This is information on a product in full production. www.st.com

Contents

1 Electrical ratings 3
2 Electrical characteristics 4
2.1 Electrical characteristics (curves) 6
3 Test circuits 8
4 Package information 9
4.1 H²PAK-6 package information 9
4.2 Packing information 12
5 Revision history 14

Obsolete Product(s) - Obsolete Product(s)

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	100	V
V_{GS}	Gate-source voltage	± 20	V
I_D (1)	Drain current (continuous) at T_C = 25 °C	180	A
I_D (1)	Drain current (continuous) at T_C = 100 °C	120	A
I_{DM} (2)	Drain current (pulsed)	720	A
P_{TOT}	Total dissipation at T_C = 25 °C	315	W
	Derating factor	2.1	W/ºC
dv/dt	Peak diode recovery voltage slope	20	V/ns
E_{AS} (3)	Single pulse avalanche energy	350	mJ
T_J	Operating junction temperature	-55 to 175	°C
T_{stg}	Storage temperature		°C

Notes:

(1)Current limited by package

(2)Pulse width limited by safe operating area

(3)Starting T_J = 25 °C, I_D = 80, V_{DD} = 50 V

Table 3: Thermal resistance

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case	0.48	°C/W
$R_{thj\text{-}pcb}$ (1)	Thermal resistance junction-pcb	35	°C/W

Notes:

(1)When mounted on FR-4 board of 1 inch², 2 oz Cu

Obsolete Product(s) - Obsolete Product(s)

2 Electrical characteristics

(T_{CASE} = 25 °C unless otherwise specified)

Table 4: On/off-state

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage (V_{GS}= 0)	I_D = 250 µA	100			V
I_{DSS}	Zero gate voltage drain current (V_{GS} = 0)	V_{DS} = 100 V			10	µA
		V_{DS} = 100 V; T_C = 125 °C			100	µA
I_{GSS}	Gate body leakage current (V_{DS} = 0)	V_{GS} = ±20 V			±200	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	2		4	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 60 A		3.9	4.5	mΩ

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 25 V, f = 1 MHz, V_{GS} = 0	-	6665	-	pF
C_{oss}	Output capacitance			786		pF
C_{rss}	Reverse transfer capacitance			49		pF
Q_g	Total gate charge	V_{DD} = 50 V, I_D = 120 A V_{GS} = 10 V See *Figure 14: "Gate charge test circuit"*		114.6		nC
Q_{gs}	Gate-source charge			38.8		nC
Q_{gd}	Gate-drain charge			31.9		nC

Table 6: Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 50 V, I_D = 60 A, R_G = 4.7 Ω, V_{GS}= 10 V See *Figure 13: "Switching times test circuit for resistive load"*	-	25.6	-	ns
t_r	Rise time			97.1		ns
$t_{d(off)}$	Turn-off delay time			99.9		ns
t_f	Fall time			6.9		ns

Obsolete Product(s) - Obsolete Product(s)

Table 7: Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		180	A
I_{SDM} (1)	Source-drain current (pulsed)				720	A
V_{SD} (2)	Forward on voltage	I_{SD} = 120 A, V_{GS} = 0			1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 120 A, di/dt = 100 A/µs, V_{DD} = 80 V, T_j = 150 °C		83.4		ns
Q_{rr}	Reverse recovery charge			295.7		nC
I_{RRM}	Reverse recovery current			7.1		A

Notes:

(1)Pulse width limited by safe operating area

(2)Pulsed: pulse duration = 300 µs, duty cycle 1.5%

Obsolete Product(s) - Obsolete Product(s)

2.1 Electrical characteristics (curves)

Figure 2: Safe operating area




Figure 3: Thermal impedance




Figure 4: Output characteristics




Figure 5: Transfer characteristics




Figure 6: Normalized $V_{(BR)DSS}$ vs temperature





Figure 7: Static drain-source on-resistance



Obsolete Product(s) - Obsolete Product(s)

Figure 8: Gate charge vs gate-source voltage




Figure 9: Capacitance variations




Figure 10: Normalized gate threshold voltage vs temperature




Figure 11: Normalized on-resistance vs temperature





Figure 12: Source-drain diode forward characteristics



Obsolete Product(s) - Obsolete Product(s)

3 Test circuits

Figure 13: Switching times test circuit for resistive load




Figure 14: Gate charge test circuit




Figure 15: Test circuit for inductive load switching and diode recovery times




Figure 16: Unclamped inductive load test circuit




Figure 17: Unclamped inductive waveform





Figure 18: Switching time waveform




Obsolete Product(s) - Obsolete Product(s)

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: ***www.st.com***. ECOPACK® is an ST trademark.

4.1 H²PAK-6 package information

Figure 19: H²PAK-6 outline




Obsolete Product(s) - Obsolete Product(s)

Table 8: H²PAK-6 mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.30	-	4.80
A1	0.03		0.20
C	1.17		1.37
e	2.34		2.74
e1	4.88		5.28
e2	7.42		7.82
E	0.45		0.60
F	0.50		0.70
H	10.00		10.40
H1	7.40		7.80
L	14.75		15.25
L1	1.27		1.40
L2	4.35		4.95
L3	6.85		7.25
L4	1.5		1.75
M	1.90		2.50
R	0.20		0.60
V	0°		8°

Obsolete Product(s) - Obsolete Product(s)

Figure 20: H²PAK-6 recommended footprint



Obsolete Product(s) - Obsolete Product(s)

Dimensions are in mm.

4.2 Packing information

Figure 21: Tape outline





Figure 22: Reel outline



Obsolete Product(s) - Obsolete Product(s)

Table 9: Tape and reel mechanical data

Tape			Reel		
Dim.	mm		Dim.	mm	
	Min.	Max.		Min.	Max.
A0	10.5	10.7	A		330
B0	15.7	15.9	B	1.5	
D	1.5	1.6	C	12.8	13.2
D1	1.59	1.61	D	20.2	
E	1.65	1.85	G	24.4	26.4
F	11.4	11.6	N	100	
K0	4.8	5.0	T		30.4
P0	3.9	4.1			
P1	11.9	12.1	Base quantity		1000
P2	1.9	2.1	Bulk quantity		1000
R	50				
T	0.25	0.35			
W	23.7	24.3			

Obsolete Product(s) - Obsolete Product(s)

5 Revision history

Table 10: Document revision history

Date	Revision	Changes
10-Oct-2011	1	First version
04-Nov-2011	2	• Updated features in cover page
14-Nov-2014	3	• Updated: H^2PAK-6 package mechanical data. • Updated: title, features and description. • Minor text changes.
26-Nov-2014	4	Updated *Table 4: "On/off-state"*.

Obsolete Product(s) - Obsolete Product(s)

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2014 STMicroelectronics – All rights reserved

Obsolete Product(s) - Obsolete Product(s)