
# STL100N6LF6


## N-channel 60 V, 3.3 mΩ typ., 25 A STripFET™ VI DeepGATE™ Power MOSFET in a PowerFLAT™ 5x6 package

**Datasheet – production data**




**PowerFLAT™ 5x6**

**Figure 1. Internal schematic diagram**




## Features

| Order code | $V_{DS}$ | $R_{DS(on)}$ max | $I_D$ |
|---|---|---|---|
| STL100N6LF6 | 60 V | 4.4 mΩ | 25 A |

- Low gate charge
- Very low on-resistance
- High avalanche ruggedness

## Applications

- Switching applications

## Description

This device is an N-channel Power MOSFET developed using the 6th generation of STripFET™ DeepGATE™ technology, with a new gate structure. The resulting Power MOSFET exhibits the lowest $R_{DS(on)}$ in all packages.

**Table 1. Device summary**

| Order code | Marking | Package | Packaging |
|---|---|---|---|
| STL100N6LF6 | 100N6LF6 | PowerFLAT™ 5x6 | Tape and reel |



This is information on a product in full production. www.st.com

# Contents

1 Electrical ratings . . . . . 3

2 Electrical characteristics . . . . . 4

2.1 Electrical characteristics (curves) . . . . . 6

3 Test circuits . . . . . 8

4 Package mechanical data . . . . . 9

5 Packaging mechanical data . . . . . 12

6 Revision history . . . . . 14

# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $V_{DS}$ | Drain-source voltage | 60 | V |
| $V_{GS}$ | Gate-source voltage | ± 20 | V |
| $I_D$ (1) | Drain current (continuous) at $T_C$ = 25 °C | 130 | A |
| $I_D$ (2) | Drain current (continuous) at $T_{pcb}$ = 25 °C | 25 | A |
| $I_D$ (2) | Drain current (continuous) at $T_{pcb}$=100 °C | 18 | A |
| $I_{DM}$ (3) | Drain current (pulsed) | 100 | A |
| $P_{TOT}$ (2) | Total dissipation at $T_{pcb}$ = 25 °C | 4.8 | W |
| $T_{stg}$ | Storage temperature | - 55 to 175 | °C |
| $T_j$ | Operating junction temperature | | |

1. The value is rated according to $R_{thj\text{-}c}$
2. The value is rated according to $R_{thj\text{-}pcb}$
3. Pulse width limited by safe operating area

**Table 3. Thermal data**

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $R_{thj\text{-}pcb}$ (1) | Thermal resistance junction-pcb max | 31.3 | °C/W |
| $R_{thj\text{-}case}$ | Thermal resistance junction-case max | 1.13 | °C/W |

1. When mounted on FR-4 board of 1 inch², 2 oz Cu, t < 10 sec

**Table 4. Avalanche characteristics**

| Symbol | Parameter | Max value | Unit |
|---|---|---|---|
| $I_{AS}$ | Avalanche current, repetitive or not-repetitive (pulse width limited by $T_j$ max) | 10 | A |
| $E_{AS}$ | Single pulse avalanche energy (starting $T_j$ = 25 °C, $I_D$ = $I_{AS}$, $V_{DD}$ = 52 V) | 1370 | mJ |

# 2 Electrical characteristics

($T_J$ = 25 °C unless otherwise specified)

**Table 5. On/off states**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage | $I_D$ = 1 mA, $V_{GS}$= 0 | 60 | | | V |
| $I_{DSS}$ | Zero gate voltage drain current ($V_{GS}$ = 0) | $V_{DS}$ = 60 V | | | 1 | µA |
| | | $V_{DS}$ = 60 V, $T_C$ =125 °C | | | 10 | µA |
| $I_{GSS}$ | Gate body leakage current ($V_{DS}$ = 0) | $V_{GS}$ = ±20 V | | | ±100 | nA |
| $V_{GS(th)}$ | Gate threshold voltage | $V_{DS}$= $V_{GS}$, $I_D$ = 250 µA | 1 | | 2.5 | V |
| $R_{DS(on)}$ | Static drain-source on-resistance | $V_{GS}$= 10 V, $I_D$= 11 A | | 3.3 | 4.4 | mΩ |
| | | $V_{GS}$= 4.5 V, $I_D$= 11 A | | 4.3 | 5.5 | mΩ |

**Table 6. Dynamic**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $C_{iss}$ | Input capacitance | $V_{DS}$ =25 V, f = 1 MHz, $V_{GS}$ = 0 | - | 6600 | - | pF |
| $C_{oss}$ | Output capacitance | | - | 670 | - | pF |
| $C_{rss}$ | Reverse transfer capacitance | | - | 315 | - | pF |
| $Q_g$ | Total gate charge | $V_{DD}$ = 30 V, $I_D$ = 20 A $V_{GS}$ =10 V (see *Figure 14*) | - | 121 | - | nC |
| $Q_{gs}$ | Gate-source charge | | - | 17 | - | nC |
| $Q_{gd}$ | Gate-drain charge | | - | 22 | - | nC |
| $R_g$ | Gate input resistance | f=1 MHz Gate DC Bias=0 test signal level=20 mV $I_D$=0 | - | 1.2 | - | Ω |

**Table 7. Switching times**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $t_{d(on)}$ | Turn-on delay time | $V_{DD}$= 30 V, $I_D$= 20A, $R_G$=4.7 Ω, $V_{GS}$=10 V (see *Figure 13*) | - | 20 | - | ns |
| $t_r$ | Rise time | | - | 13 | - | ns |
| $t_{d(off)}$ | Turn-off delay time | | - | 108 | - | ns |
| $t_f$ | Fall time | | - | 22 | - | ns |

**Table 8. Source drain diode**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max | Unit |
|---|---|---|---|---|---|---|
| $I_{SD}$ | Source-drain current | | - | | 22 | A |
| $I_{SDM}$(1) | Source-drain current (pulsed) | | - | | 84 | A |
| $V_{SD}$(2) | Forward on voltage | $I_{SD}$ = 22 A, $V_{GS}$ = 0 | - | | 1.3 | V |
| $t_{rr}$ | Reverse recovery time | $I_{SD}$ = 20 A, di/dt = 100 A/µs, $V_{DD}$= 48V, $T_J$ = 150 °C (see *Figure 15*) | - | 34 | | ns |
| $Q_{rr}$ | Reverse recovery charge | | - | 44 | | nC |
| $I_{RRM}$ | Reverse recovery current | | - | 2.6 | | A |

1. Pulse width limited by safe operating area
2. Pulsed: pulse duration=300µs, duty cycle 1.5%

## 2.1 Electrical characteristics (curves)

**Figure 2. Safe operating area**





**Figure 3. Thermal impedance**





**Figure 4. Output characteristics**





**Figure 5. Transfer characteristics**





**Figure 6. Gate charge vs gate-source voltage**





**Figure 7. Static drain-source on-resistance**




**Figure 8. Capacitance variations**





**Figure 9. Source-drain diode forward characteristics**





**Figure 10. Normalized gate threshold voltage vs temperature**





**Figure 11. Normalized on-resistance vs temperature**






**Figure 12. Normalized $V_{DS}$ vs temperature**



# 3 Test circuits

**Figure 13. Switching times test circuit for resistive load**





**Figure 14. Gate charge test circuit**





**Figure 15. Test circuit for inductive load switching and diode recovery times**





**Figure 16. Unclamped inductive load test circuit**





**Figure 17. Unclamped inductive waveform**






**Figure 18. Switching time waveform**



# 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: *www.st.com*.
ECOPACK® is an ST trademark.

**Figure 19. PowerFLAT™ 5x6 type S-C mechanical data**





Table 9. PowerFLAT™ 5x6 type S-C mechanical data

| Dim. | mm | | |
|---|---|---|---|
| | Min. | Typ. | Max. |
| A | 0.80 | | 1.00 |
| A1 | 0.02 | | 0.05 |
| A2 | | 0.25 | |
| b | 0.30 | | 0.50 |
| D | | 5.20 | |
| E | | 6.15 | |
| D2 | 4.11 | | 4.31 |
| E2 | 3.50 | | 3.70 |
| e | | 1.27 | |
| e1 | | 0.65 | |
| L | 0.715 | | 1.015 |
| K | 1.05 | | 1.35 |

Figure 20. PowerFLAT™ 5x6 recommended footprint (dimensions in mm)




Footprint

# 5 Packaging mechanical data

**Figure 21. PowerFLAT™ 5x6 tape[(a)]**







**Figure 22. PowerFLAT™ 5x6 package orientation in carrier tape.**




a. All dimensions are in millimeters.

**Figure 23. PowerFLAT™ 5x6 reel**



# 6 Revision history

**Table 10. Document revision history**

| Date | Revision | Changes |
|---|---|---|
| 24-Feb-2011 | 1 | First release |
| 10-Nov-2011 | 2 | *Section 4: Package mechanical data* has been updated.<br>Minor text changes. |
| 10-Mar-2014 | 3 | – Updated: title on the cover page.<br>– Modified: $R_{DS(on)}$ and $I_D$ values on cover page<br>– Modified: drain current (continuous) at $T_C$ = 25 °C, drain current (continuous) at $T_{pcb}$ = 25 °C, drain current (continuous) at $T_{pcb}$=100 °C, $I_{DM}$, total dissipation at $T_{pcb}$ = 25 °C, $T_{stg}$ and $T_j$ values on table 2, $R_{thj\text{-}case}$ value on *Table 3*, max values on *Table 4*, $R_{DS(on)}$ typ and max. values, typical values on *Table 6*, *7* and *8*<br>– Inserted: *Section 2.1: Electrical characteristics (curves)*<br>– Updated: *Section 4: Package mechanical data*<br>– Added: *Section 5: Packaging mechanical data*<br>– Minor text changes |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**ST PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER’S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR “AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL” INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.
Information in this document supersedes and replaces all information previously supplied.
The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2014 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

**www.st.com**