STL9N3LLH5

N-channel 30 V, 0.015 Ω typ., 9 A STripFET™ V Power MOSFET in a PowerFLAT™ (3.3x3.3) package


Datasheet — production data

Features

Order code	V_{DSS}	$R_{DS(on)}$ max	I_D
STL9N3LLH5	30 V	< 0.019 Ω	9 A (1)

1. The value is rated according Rthj-pcb

- $R_{DS(on)}$ * Q_g industry benchmark
- Extremely low on-resistance $R_{DS(on)}$
- Very low switching gate charge
- High avalanche ruggedness
- Low gate drive power losses



PowerFLAT™(3.3x3.3)

Applications

- Switching applications

Description

This device is an N-channel Power MOSFET developed using STMicroelectronics' STripFET™ V technology. The device has been optimized to achieve very low on-state resistance, contributing to a FOM that is among the best in its class.

Figure 1. Internal schematic diagram




Table 1. Device summary

Order code	Marking	Package	Packaging
STL9N3LLH5	9N3L	PowerFLAT™ (3.3x3.3)	Tape and reel

Obsolete Product(s) - Obsolete Product(s)

This is information on a product in full production. www.st.com

Contents

1 Electrical ratings 3

2 Electrical characteristics 4

2.1 Electrical characteristics (curves) 6

3 Test circuits 8

4 Package mechanical data 9

5 Revision history 12

Obsolete Product(s) - Obsolete Product(s)

1 Electrical ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage (V_{GS} = 0)	30	V
V_{GS}	Gate-source voltage	± 22	V
I_D (1)	Drain current (continuous) at T_C = 25 °C	9	A
I_D (1)	Drain current (continuous) at T_C=100 °C	6	A
I_{DM} (2)	Drain current (pulsed)	36	A
P_{TOT} (3)	Total dissipation at T_C = 25 °C	50	W
P_{TOT} (1)	Total dissipation at T_C = 25 °C	2	W
	Derating factor	0.4	W/°C
T_J T_{stg}	Operating junction temperature storage temperature	-55 to 150	°C

1. The value is rated according Rthj-pcb
2. Pulse width limited by safe operating area.
3. The vaule is rated according Rthj-c

Table 3. Thermal resistance

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case (drain)	2.5	°C/W
$R_{thj\text{-}pcb}$ (1)	Thermal resistance junction-pcb	42.8	°C/W
$R_{thj\text{-}pcb}$ (2)	Thermal resistance junction-pcb	63.5	°C/W

1. When mounted on FR-4 board of 1inch², 2oz Cu, t < 10sec
2. Steady state

Table 4. Avalanche data

Symbol	Parameter	Value	Unit
I_{AV} (1)	Not-repetitive avalanche current	7.5	A
E_{AS} (2)	Thermal resistance junction-pcb	150	mJ

1. Pulse width limited by $T_{Jmax.}$
2. Starting T_J = 25 °C, I_D=I_{AV}, V_{DD} = 21 V

Obsolete Product(s) - Obsolete Product(s)

2 Electrical characteristics

(T_{CASE}=25 °C unless otherwise specified)

Table 5. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	I_D = 250 µA, V_{GS}= 0	30			V
I_{DSS}	Zero gate voltage drain current (V_{GS} = 0)	V_{DS} = Max rating, V_{DS} = Max rating @125 °C			1 10	µA µA
I_{GSS}	Gate body leakage current (V_{DS} = 0)	V_{GS} = ± 22 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS}= V_{GS}, I_D = 250 µA	1		2.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS}= 10 V, I_D= 4.5 A V_{GS}= 4.5 V, I_D= 4.5 A		15 19	19 22	mΩ mΩ

Table 6. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss} C_{oss} C_{rss}	Input capacitance Output capacitance Reverse transfer capacitance	V_{DS} =25 V, f=1 MHz, V_{GS}=0	-	724 132 20	900 (1) 165 (1) 25 (1)	pF pF pF
Q_g Q_{gs} Q_{gd}	Total gate charge Gate-source charge Gate-drain charge	V_{DD}=15 V, I_D = 9 A V_{GS} =4.5 V *(see Figure 14)*	-	5 2 2	6 (1) 2.5 (1) 2.5 (1)	nC nC nC
R_G	Gate input resistance	f=1 MHz Gate DC Bias = 0 Test signal level = 20 mV Open drain	-		3.3	Ω

1. Max values not tested

Table 7. Switching times (1)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$ t_r $t_{d(off)}$ t_f	Turn-on delay time Rise time Turn-off delay time Fall time	V_{DD}=15 V, I_D= 4.5 A, R_G=4.7 Ω, V_{GS}= 10 V *(see Figure 13)*	-	4 4.2 21 3.5	5 5.2 26 4.25	ns ns ns ns

1. Max values not tested

Obsolete Product(s) - Obsolete Product(s)

Table 8. Source drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		9	A
I_{SDM}(1)	Source-drain current (pulsed)		-		36	A
V_{SD}(2)	Forward on voltage	I_{SD}= 9 A, V_{GS}=0	-		1.1	V
t_{rr} Q_{rr} I_{RRM}	Reverse recovery time Reverse recovery charge Reverse recovery current	I_{SD}= 9 A, di/dt = 100 A/µs, V_{DD}=20 V, Tj=150 °C *(see Figure 18)*	-	21 10 1		ns nC A

1. Pulse width limited by safe operating area
2. Pulsed: pulse duration = 300 µs, duty cycle 1.5 %

Obsolete Product(s) - Obsolete Product(s)

2.1 Electrical characteristics (curves)

Figure 2. Safe operating area




Figure 3. Thermal impedance




Figure 4. Output characteristics




Figure 5. Transfer characteristics




Figure 6. Normalized B_{VDSS} vs temperature





Figure 7. Static drain-source on-resistance



Obsolete Product(s) - Obsolete Product(s)

Figure 8. Gate charge vs gate-source voltage




Figure 9. Capacitance variations




Figure 10. Normalized gate threshold voltage vs temperature




Figure 11. Normalized on-resistance vs temperature





Figure 12. Source-drain diode forward characteristics



Obsolete Product(s) - Obsolete Product(s)

3 Test circuits

Figure 13. Switching times test circuit for resistive load




Figure 14. Gate charge test circuit




Figure 15. Test circuit for inductive load switching and diode recovery times




Figure 16. Unclamped inductive load test circuit




Figure 17. Unclamped inductive waveform





Figure 18. Switching time waveform



Obsolete Product(s) - Obsolete Product(s)

4 Package mechanical data


In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: *www.st.com*. ECOPACK® is an ST trademark.

Table 9. PowerFLAT™ 3.3 x 3.3 mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	0.80	0.90	1.00
A1	0		0.05
A3		0.20	
b	0.23		0.38
D	3.20	3.30	3.40
D2	2.50		2.75
E	3.20	3.30	3.40
E2	1.25		1.50
e		0.65	
L	0.30		0.50


Obsolete Product(s) - Obsolete Product(s)

Figure 19. PowerFLAT™ 3.3 x 3.3 drawing



Obsolete Product(s) - Obsolete Product(s)

Figure 20. PowerFLAT™ 3.3 x 3.3 recommended footprint



Obsolete Product(s) - Obsolete Product(s)

5 Revision history

Table 10. Document revision history

Date	Revision	Changes
09-Jul-2009	1	First release
01-Oct-2012	2	Updated *Section 4: Package mechanical data*. Updated *Figure 1*, title and description on the cover page.

Obsolete Product(s) - Obsolete Product(s)

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

Obsolete Product(s) - Obsolete Product(s)