SUNTSU

Ceramic SMD 4 Pad Crystal

SXT214 Series

2.0mm x 1.6mm

Features

- ±10ppm/±10ppm (Tolerance/Stability) Available
- Ultra-Miniature Package
- AT-Cut Fundamental
- Tape and Reel

Applications

- Office Automation
- Audio/Visual Bluetooth
- Small Communication Devices
- SSD
- USB



Part Numbering Guide

SXT 21 4 18 A A 48 - 25.000M

- **SUNTSU CRYSTAL**
- **2.0mm x 1.6mm**
- **4 PAD**
- **LOAD CAPACITANCE**
  - S : Series
  - 8-32 : 8pF - 32pF
- **FREQUENCY TOLERANCE**
  - A : ±50ppm
  - B : ±30ppm
  - C : ±25ppm
  - D : ±20ppm
  - E : ±15ppm
  - F : ±10ppm
- **FREQUENCY STABILITY**
  - A : ±50ppm
  - B : ±30ppm
  - C : ±25ppm
  - D : ±20ppm
  - E : ±15ppm
  - F : ±10ppm*
- **OPERATING TEMPERATURE RANGE****
  - 07 : 0°C - +70°C
  - 16 : -10°C - +60°C
  - 17 : -10°C - +70°C
  - 27 : -20°C - +70°C
  - 38 : -30°C - +85°C
  - 48 : -40°C - +85°C
- **FREQUENCY**
  - MHz

RoHS COMPLIANT

Cage Code: 4GUT4


To customize your parameters contact a Suntsu representative.

* For frequency stability option F contact a Suntsu representative. ** For operating temperatures of -55-125°C a Suntsu representative.

Electrical Parameters	Units	Minimum	Typical	Maximum	Remarks
Frequency Range	MHz	16		96	AT-Cut Fundamental.
Frequency Tolerance at +25°C	ppm	-10		10	See part numbering guide for options.
Frequency Stability vs. Op Temp	ppm	-10		10	See part numbering guide for options.
Frequency Stability vs. Aging	ppm	-2		2	First year @ +25°C.
Operating Temperature	°C	-40		85	See part numbering guide for options.
Storage Temperature	°C	-40		125	
Load Capacitance	pF	8		16	See part numbering guide for options.
Shunt Capacitance	pF			5	
Drive Level	µW		50	100	
Insulation Resistance	MΩ	500			@ 100VDC ± 15V.
16.000MHz ~ 20.999MHz	Ω			200	AT-Cut Fundamental
21.000MHz ~ 25.999MHz	Ω			120	AT-Cut Fundamental
ESR - 26.000MHz ~ 40.999MHz	Ω			100	AT-Cut Fundamental
41.000MHz ~ 60.999MHz	Ω			60	AT-Cut Fundamental
61.000MHz ~ 96.000MHz	Ω			40	AT-Cut Fundamental

Outline Drawing & Recommended Landed Pattern

All dimensions are in millimeters (mm) unless otherwise noted. Drawings are not to scale.



www.suntsu.com

Specifications are subject to change without notice.

Suntsu Electronics, Inc.
142 TECHNOLOGY DR., SUITE 150
IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301

SUNTSU


Ceramic SMD 4 Pad Crystal


SXT214 Series

2.0mm x 1.6mm

Environmental Specifications		Mechanical Specifications	
Temperature Cycling	MIL-STD-883, Method 1010, Condition B	Mechanical Shock	MIL-STD-202, Method 213, Condition B
Fine Leak Test	MIL-STD-883, Method 1014, Condition A	Vibration	MIL-STD-883, Method 2007, Condition A
Gross Leak Test	MIL-STD-883, Method 1014, Condition C	Resistance to Soldering Heat	MIL-STD-202, Method 210, Condition K
Moisture Resistance	MIL-STD-883, Method 1004	Resistance to Solvents	MIL-STD-202, Method 215
Moisture Sensitivity	J-STD-020, MSL 1	Solderability	MIL-STD-883, Method 2003

Reflow Profile & Part Marking






Tape And Reel Dimensions

All dimensions are in millimeters (mm) unless otherwise noted. Drawings are not to scale.

3,000pcs / Reel



Suntsu Electronics, Inc.
142 TECHNOLOGY DR., SUITE 150
IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301