



Heyco® Snap Bushings

Mounting Hole Diameter Range: .250″ (6,4 mm) to .875″ (22,2 mm)

- **Convert raw-edged holes to smooth, neat, insulated holes.**
- Insulate and mechanically protect electrical and telecommunications cables, tubing, hose, rope, and utility lines.
- Locking fingers snap into holes with fingertip pressure.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Withstand a push back force of 35 pounds.
- Available in multiple sizes for use in .250″ (6,4 mm) to 6.00″ (152,4 mm) diameter holes.
- We offer the following brass-colored parts for lamp and lighting applications:
  Part No. 2012, SB 312-3 Brass
  Part No. 2033, SB 375-4 Brass
  Part No. 2041, SB 437-4 Brass



SINGLE PANEL DESIGN



MULTIPLE PANEL DESIGN

MOUNTING HOLE DIAMETER		PART NO.		DESCRIPTION	PART DIMENSIONS					
					A Inside Diameter		B Head Diameter		C Overall Height	
		Black	White							
in.	mm.				in.	mm.	in.	mm.	in.	mm.
Single Locking Step for Panel Thickness up to .040″ (1,0 mm)										
.250	6,4	**2003**	**2004**	SB 250-040	.13	3,2	.31	7,9	.31	7,9
Single Locking Step for Panel Thickness up to .062″ (1,6 mm)										
.250	6,4	**2000**	**2001**	SB 250-2	.14	3,6	.31	7,9	.31	7,9
.312	7,9	**2010**	**2011**	SB 312-3	.19	4,8	.38	9,5		
Multiple Locking Steps for Panel Thickness up to .125″ (3,2 mm)										
.375	9,5	**2020**	**2021**	SB 375-3	.19	4,8	.47	11,9	.41	10,3
		2030	**2031**	SB 375-4	.25	6,4				
.437	11,1	**2042**	**2037**	SB 437-243	.24	6,2	.53	13,5		
		2038	**2039**	SB 437-4	.27	6,8				
		2043	**2044**	SB 437-5	.31	7,9				
.500	12,7	**2058**	**2059**	SB 500-4	.25	6,4	.57	14,5		
		2049	**2050**	SB 500-5	.31	7,9				
		2053	**2054**	SB 500-6	.39	9,9				
.562	14,3	**2060**	**2061**	SB 562-5	.31	7,9	.66	16,7		
		2063	**2064**	SB 562-6	.39	9,9				
		2066	**2067**	SB 562-7	.44	11,1				
.625	15,9	**2075**	**2078**	SB 625-4	.25	6,4	.72	18,2		
		2070	**2071**	SB 625-7	.44	11,1				
		2073	**2074**	SB 625-8	.50	12,7				
.687	17,4	**2083**	**2084**	SB 687-8	.50	12,7	.78	19,8		
		2086	**2087**	SB 687-9	.56	14,3				
.750	19,1	**2090**	**2091**	SB 750-6	.39	9,9	.85	21,6		
		2092	**2099**	SB 750-8	.50	12,7				
		2093	**2094**	SB 750-9	.56	14,3				
		2096	**2097**	SB 750-10	.61	15,5				
.812	20,6	**2100**	**2101**	SB 812-9	.56	14,3	.89	22,6		
		2103	**2104**	SB 812-10	.63	15,9				
.875	22,2	**2110**	**2111**	SB 875-6	.38	9,5	.95	24,2	.45	11,5
		2113	**2114**	SB 875-7	.44	11,1				
		2116	**2117**	SB 875-8	.50	12,7				
		2120	**2121**	SB 875-9	.56	14,3				
		2123	**2124**	SB 875-10	.63	15,9				
		2126	**2127**	SB 875-11	.69	17,5				

Standard colors black and white. Consult Heyco for other colors.

Quick Specs

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File E15331
	Certified by Canadian Standards Association, File 8919
Flammability Rating	94V-2
Temperature Range	-.4°F (-18°C) to 221°F (105°C)

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com