

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of the utility model or design



* for 12 and 14 pol dimension is 6,45











Panel cutout M1:1



Number of contacts	Standard	3	4	5	5	6	7	7	8	12	14
Contact arrangement	IEC 61076-2-106	03-a	04-a	05-a	05-b	06-a	07-a	07-b	08-a	12-a	14-a
Contact arrangement	IEC 60130-9[1)]	yes		no	yes		no	yes		no	
Rated voltage[2)]	IEC 60664-1	300 V (100 V)		300 V (63 V)	100 V (32 V)	300 V (63 V)		100 V (32 V)		150 V (32 V)	
Rated voltage	UL 1977	250V								60V	
Rated impulse withstand voltage[2)]	IEC 60664-1	1500 V (1500 V)			1200 V (800 V)	1500 V (1500 V)		1200 V (800 V)			
Pollution degree[2)]	IEC 60664-1	1 (2)									
Installation category	IEC 60664-1	I									
Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600									
Current rating	IEC 60512-5-2 UL 1977	10A/+40°C		7A/+40°C						3A/+40°C	
Insulation resistance	IEC 60512-3-1	>10[10] Ohm[3)]									
Contact resistance	IEC 60512-2-1	<5mOhm									
Climatic category	IEC 60668-1	40 / 100 / 56									
Temperatur range	IEC 60668-1	-40°C...+100°C / -40°F...+212°F									
IP degree	IEC 60529	IP 40									
Insertion and withdrawal force	IEC 60512-13-2	25N	30N	35N	35N	50N	55N	55N	60N	50N	50N
mechanical operation	IEC 60512-9-1	Silver ≥500 mating cycles / Gold ≥1000 mating cycles									
housing material		brass and / or zinc die cast, nickel plated or thermoplast									
dielectric material		thermoplastic									
contacts		silver or gold plated, please order contacts separately acc. to drawing M-N 01 015 00XX X (3-8pol) or M-N 01 010 0158 X (12-14pol)									
termination technique		crimp									
wire gauge		0,09-1,0mm²			0,09-0,75 mm²	0,09-1,0 mm²		0,09-0,75mm²		0,09-0,25mm²	
flamability		UL 94 V0									
locking system		metal screw coupling; tightening torque 0,7 - 1,5 Nm									

[1)] Edition 2000-05
[2)] values in brackets are according to DIN EN 61076-2-106
[3)] under operating conditions >10[8] Ohm

Do not connect or disconnect under load. Metal housing parts shall be securely incoporated to protected ground.
All technical data have been measured in a laboratory environment and can be different during pratical usage of the product. Any product information is for descriptive usage only and not legally binding; particulary the information does not constitute or provide any legal guaranties ("Beschaffenheitsgarantie" or " Haltbarkeitsgarantie").

	Contact arrangement View on mating side	Number of contacts (Contact arrangement acc. DIN EN 61076-2-106)	Part number
	14 (14-a)		T 3652 150 U
	12 (12-a)		T 3637 150 U
	8 (08-a)		T 3506 150 U
	7 (07-b)		T 3486 150 U
	7 (07-a)		T 3477 150 U
	6 (6-a)		T 3402 150 U
	5 (05-b)		T 3358 150 U
	5 (05-a)		T 3362 150 U
	4 (04-a)		T 3302 150 U
	3 (03-a)		T 3262 150 U
	2 (Pin 1+3)		T 3202 150 U

Index	Änderung / Description	Datum / Date	Name
01	202100006	15.06.2021	MCARL

Gewicht (errechnet) / *Calc WT* : 15,793 g
Prüfmaß / *Testdimension*
Teileindex / *Partindexnumber:*
Bagatelle change:

Zul. Abw. / *Tolerances* : ISO 2768-c
DIN / ISO 13715

Maßstab / *Scale* : 2:1;1:1 | A3

Gez. 14.06.2021
Drawn MCARLE
Status Released
Gepr. 16.06.2021
Checked MBERTSCH

Amphenol Tuchel Industrial GmbH

CUSTOMER DRAWING

Male receptacle
rear mounting

M CA T 3XXX 150 U

Blatt / *Sheet* 1 | 1 Bl.

Ers. f. / *Replacement for* :

FA2021-002707 | NXM-V03

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten