PNP Epitaxial Silicon Darlington Transistors

Features

- High DC Current Gain
- Low Collector-Emitter Saturation Voltage
- Complementary to TIP110/111/112
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix Designates RoHS Compliant. See Ordering Information)


Maximum Ratings @ 25°C Unless Otherwise Specified

- Operating Junction Temperature Range: -55℃ to +150℃
- Storage Temperature Range: -55℃ to +150℃
- Thermal Resistance: 2.5℃/W Junction to Case

Parameter		Symbol	Rating	Unit
Collector-Base Voltage	TIP115	V_{CBO}	-60	V
	TIP116		-80	
	TIP117		-100	
Collector-Emitter Voltage	TIP115	V_{CEO}	-60	V
	TIP116		-80	
	TIP117		-100	
Emitter-Base Voltage		V_{EBO}	-5	V
Continuous Collector Current		I_C	-2	A
Peak Collector Current		I_{CM}	-4	A
Base Current		I_B	-50	mA
Power Dissipation @T_A=25°C		P_D	2	W
Power Dissipation @T_C=25°C		P_D	50	W

Note: 1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

TO-220



1.BASE
2.COLLECTOR
3.EMITTER

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.560	0.625	14.22	15.88	
B	0.380	0.420	9.65	10.67	
C	0.140	0.190	3.56	4.82	
D	0.020	0.045	0.51	1.14	
F	0.139	0.161	3.53	4.09	Φ
G	0.090	0.110	2.29	2.79	
H	-----	0.250	-----	6.35	
J	0.012	0.025	0.30	0.64	
K	0.500	0.580	12.70	14.73	
L	0.045	0.060	1.14	1.52	
N	0.190	0.210	4.83	5.33	
Q	0.100	0.135	2.54	3.43	
R	0.080	0.115	2.04	2.92	
S	0.045	0.055	1.14	1.39	
T	0.230	0.270	5.84	6.86	
U	-----	0.050	-----	1.27	
V	0.045	-----	1.15	-----	

Electrical Characteristics @ T_A=25°C Unless Otherwise Specified

Parameter		Symbol	Min	Typ	Max	Units	Conditions
Collector-Emitter Breakdown Voltage	TIP115	$V_{(BR)CEO}$	-60			V	I_C=-30mA, I_B=0
	TIP116		-80				
	TIP117		-100				
Collector Cutoff Current	TIP115	I_{CBO}			-1	mA	V_{CB}=-60V, I_E=0
	TIP116						V_{CB}=-80V, I_E=0
	TIP117						V_{CB}=-100V, I_E=0
Collector Cutoff Current	TIP115	I_{CEO}			-2	mA	V_{CE}=-30V, I_B=0
	TIP116						V_{CE}=-40V, I_B=0
	TIP117						V_{CE}=-50V, I_B=0
Emitter Cutoff Current		I_{EBO}			-2	mA	V_{EB}=-5V, I_C=0
DC Current Gain		$h_{FE(1)}$	1000				V_{CE}=-4V, I_C=-1A
		$h_{FE(2)}$	500				V_{CE}=-4V, I_C=-2A
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$			-2.5	V	I_C=-2A, I_B=-8mA
Base-Emitter On Voltage		$V_{BE(on)}$			-2.8	V	V_{CE}=-4V, I_C=-2A
Output Capacitance		C_{ob}			200	pF	V_{CB}=-10V, I_E=0, f=0.1MHz

Ordering Information

Device	Packing
Part Number-BP	Bulk:50pcs/Tube,1Kpcs/Box,5Kpcs/Carton

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-BP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . ***Micro Commercial Components Corp*** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold ***Micro Commercial Components Corp*** . and all the companies whose products are represented on our website, harmless against all damages. ***Micro Commercial Components Corp***. products are sold subject to the general terms and conditions of commercial sale, as published at
https://www.mccsemi.com/Home/TermsAndConditions.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.