soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile

Inspection Fixture

Page 4
Frequency Response Curve

Page 5
Dimensions

Page 6
Packing

Specifications

Item	Unit	Specification	Condition
Rated Voltage	VDC	5.0	
Operating Voltage	VDC	3.0 ~ 7.0	
Mean Current	mA	30 Max	At rated voltage
Sound Output	dBA	85	At 10cm at rated voltage
Rated Frequency	Hz	3100 ±400	
Operating Temp	℃	-20 ~ +60	
Storage Temp	℃	-30 ~ +70	
Dimension	mm	φ12.0×H7.5	See attached drawing
Weight	gram	2.0	
Material		PPO (Black)	
Terminal		PIN Type	See attached drawing
Environmental Protection Regulation		RoHS	

Test condition:

Temperature: +25±2 ℃ **Related humidity:** 65±5% **Air pressure:** 86-106KPa

Mechanical Characteristics

Item	Test condition	Evaluation standard
Solderability	Lead terminals are immersed in rosin for 5 seconds and then immersed in the solder bath at +250±5°C for 3±0.5 seconds.	90% min. lead terminals shall be wet with solder.
Soldering Heat Resistance	Lead terminals are immersed in the soldering bath at +250±5°C for 2±0.5 seconds.	No interference in operation.
Terminal Mechanical Strength	Apply the terminal with 1KG tension for 1 minute.	No damage and cutting off.
Vibration	The part shall be subjected to a vibration cycle of 10Hz to 55Hz to 10Hz in a period of 1 minute. Total peak amplitude shall be 1.52mm(9.3G). The vibration test shall consist of 2 hours per axis in each three axes(X,Y,Z). Total 6 hours.	After the test, the part shall meet specifications without any damage in appearance and performance except SPL.
Drop Test	The part is dropped from a height of 75cm onto a 40mm thick wooden board 3 times in 3 axes(X,Y,Z). Total of 9 times.	

soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile



Inspection Fixture

Page 4
Frequency Response Curve

Page 5
Dimensions

Page 6
Packing

Environment Test

Item	Test condition	Evaluation standard
High Temp. Test	The part is placed in a chamber at +70°C for 96 hours.	After the test, the part shall meet specifications without any degradation in appearance and performance except SPL. After 4 hours at +25°C, the SPL should be in ±10dBA compared with initial one.
Low Temp. Test	The part is placed in a chamber at -30°C for 96 hours.	
Thermal Shock	The part shall be subjected to 10 cycles. Each cycle shall consist of: 	
Temp./Humidity Cycle	The part shall be subjected to 10 cycles. One cycle shall be 24 hours and consist of: 	

Reliability Test

Item	Test condition	Evaluation standard
Operating life test	**Ordinary Temperature** The part shall be subjected to 96 hours of continuous operation at +25˚C±10˚C. **High Temperature** The part shall be subjected to 72 hours of continuous operation at +60°C at 5.0V applied. **Low Temperature** The part shall be subjected to 72 hours of continuous operation at -20°C at 5.0V applied. **High and Low Voltage** Applying 3.0 voltage and 7.0 voltage, available time 24 hours each.	After the test, the part shall meet specifications without any degradation in appearance and performance except SPL. After 4 hours at +25°C, the SPL should be in ±10dBA compared with initial one.

Standard test condition:

a) Temperature: +5~+35℃
b) Humidity: 45~85%
c) Pressure: 86~106KPa

soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile


Inspection Fixture

Page 4
Frequency Response Curve

Page 5
Dimensions


Page 6
Packing

Recommended Wave Soldering Temperature Curve



Inspection Fixture

Input Signal: 5.0 VDC, 3100Hz



Mic: RION S.P.L meter UC30 or equivalent
S.G: Hewlett Packard 33120A Function Generator or equivalent

soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile


Inspection Fixture


Page 4
Frequency Response Curve

Page 5
Dimensions

Page 6
Packing

Typical Frequency Response Curve





soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile

Inspection Fixture


Page 4
Frequency Response Curve


Page 5
Dimensions

Page 6
Packing

Dimensions

Tolerance: ±0.5 (unit: mm)





No.	Part Name	Material	Quantity
1	Case	PPO	1
2	Diaphragm	Ferrum	1
3	Magnet Ring	Poly + Ferrite	1
4	Coil	Copper	1
5	Core	Ferrum	1
6	PCB	Epoxy Glass Fiber Cloth + Copper	1
7	Transistor	Epoxy + Copper	2
8	PIN	Copper	2

soberton inc.

WST BUZZER

Acoustic Product Specification

Product Number: WST-1206BX



Release | Revision: C/2018

CONTENTS

This document contains the technical specifications for the electromagnetic buzzer.

Page 1
Specifications

Mechanical Characteristics

Page 2
Environment Test

Reliability Test

Page 3
Recommended Temperature Profile


Inspection Fixture


Page 4
Frequency Response Curve

Page 5
Dimensions

Page 6
Packing

Packing





Packing Box	LxWxH (mm)	Pieces
Tray	190x190x25	100
Inner Carton	210x210x220	1,000
Outer Carton	430x430x250	4,000