


- Molded of **transparent** polycarbonate for internal viewing or light transmission.
- Snap into mounting holes with fingertip pressure–no tools required.
- Multiple sizes for use in .187″ (4,7 mm) to 2.000″ (50,8 mm) diameter holes.
- Lock firmly into panel up to .125″ (3,2 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062″ (1,6 mm). Thickness may vary.
- **Available in a variety of tints –consult Heyco.**



Infrared Window Plug



Blue Transparent Window Plug



- Matte Finish diffuses light from source behind plug.


Heyco® Window "View Port" Plugs

Consult Heyco for Window Tints Other Than Clear


Mounting Hole Diameter Range: .187″ (4,7 mm) to 2.000″ (50,8 mm)

MOUNTING HOLE DIAMETER in.	MOUNTING HOLE DIAMETER mm.	PART NO. Clear*	DESCRIPTION	PART DIMENSIONS A Head Diameter in.	A Head Diameter mm.	B Overall Height in.	B Overall Height mm.
Single Locking Step for Panel Thickness up to .062″ (1,6 mm)							
.187	4,7	**1300**	WP 187	.25	6,4	.23	5,9
.250	6,4	**1301**	WP 250	.31	7,9	.31	7,9
.312	7,9	**1302**	WP 312	.38	9,5		
Multiple Locking Steps for Panel Thickness up to .125″ (3,2 mm)							
.375	9,5	**1303**	WP 375	.47	11,9	.41	10,3
.437	11,1	**1304**	WP 437	.53	13,5		
.500	12,7	**1305**	WP 500	.56	14,3		
.625	15,9	**1307**	WP 625	.73	18,6		
.760	19,3	**1309**	WP 750	.86	21,8		
.875	22,2	**1311**	WP 875	.95	24,2	.45	11,5
1.000	25,4	**1312**	WP 1000	1.13	28,6		
1.093 - 1.125	27,8 - 28,6	**1313**	WP 1093	1.22	30,9		
1.375	34,9	**1314**	WP 1375	1.50	38,1		
1.500	38,1	**1316**	WP 1500	1.62	41,2		
1.750	44,5	**1318**	WP 1750	1.90	48,3		
2.000	50,8	**1319**	WP 2000	2.16	54,8		

*Consult Heyco for Window Plugs in tinted colors.



SINGLE PANEL THICKNESS DESIGN



MULTIPLE PANEL THICKNESS DESIGN

Heyco® Diffuser Plugs

MOUNTING HOLE DIAMETER* in.	MOUNTING HOLE DIAMETER* mm.	PART NO. Matte	DESCRIPTION	PART DIMENSIONS A Head Diameter in.	A Head Diameter mm.	B Overall Height in.	B Overall Height mm.
Multiple Locking Steps for Panel Thickness up to .125″ (3,2 mm)							
.375	9,5	**1303D**	DWP 375	.47	11,9	.41	10,3
.760	19,3	**1309D**	DWP 750	.92	23,4		
1.000	25,4	**1312D**	DWP 1000	1.13	28,6	.45	11,5
2.000	50,8	**1319D**	DWP 2000	2.16	54,8		

*Consult Heyco for other mounting hole diameters.

Material	Polycarbonate
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 239°F (115°C)

Quick Specs

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com