

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/12/20	


APPROVED: _____

DATE: _____ TITLE: _____



RECOMMENDED PCB LAYOUT





SPECIFICATIONS:
Material:
Housing: PBT, rated UL94V−0, Color: Black
Contact: Brass, Tin plated
Electrical:
Contact resistance: 30 Milliohms max
Insulation resistance: 1,000 Megaohms ohms min
Dielectric Voltage: 500 VAC @ sea level
Temperature Rating:
Operating temperature: −25°C to +85°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED

MM		ANGLE	
X	± 0.30	X	± 1°
X.X	± 0.25	X.X	± 0.5°
X.XX	± 0.20		
X.XXX	+ 0.10		

APPROVALS		DATE
DRAWN	LH	3/12/20
CHECKED	MY	3/12/20
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: BATTERY HOLDER, PCB THRU HOLE FOR 2032

SIZE	PART NO.	REV.
X	BH-25F-1	-

REF:	SCALE:	SHEET
S00136C	NTS	1 OF 1