



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. 60A  
3P 600V 3W NON FUSED HD T1 W/GB

|                                                    |                                                 |
|----------------------------------------------------|-------------------------------------------------|
| mechanical service life (switching cycles) typical | 10000                                           |
| fastening method                                   | SURFACE                                         |
| number of poles                                    | 3                                               |
| suitability for operation                          | DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS |
| <b>Electricity</b>                                 |                                                 |
| ampacity                                           | 60 A                                            |
| supply voltage frequency rated value 50/60 Hz      | Yes                                             |
| <b>Model</b>                                       |                                                 |
| product brand name                                 | SIEMENS                                         |
| product type designation                           | HEAVY DUTY SWITCH                               |
| special product feature                            | FACTORY INSTALLED GROUND BAR                    |
| type of electrical connection                      | MECHANICAL LUGS                                 |
| <b>Mechanical Design</b>                           |                                                 |
| design of the housing                              | TYPE 1                                          |
| design of the actuating element                    | SINGLE THROW                                    |
| material                                           | STEEL                                           |
| <b>General product approval</b>                    |                                                 |
| certificate of suitability                         | UL98                                            |

last modified:

9/16/2021 

