

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B3	PART STATUS CHANGE TO DISCONTINUNACE	13JUL2026	NS	PS

NOTES:


1. MATERIALS & FINISH
HOUSING : PA6.6 , UL94 V0, COLOUR -GREEN
SCREW M3 : COPPER ALLOY, NICKEL PLATED
CLAMP : COPPER ALLOY, NICKEL PLATED
CONTACT : COPPER ALLOY, TIN PLATED
2. MECHANICAL
RECOMMENDED TIGHTENING TORQUE : 0.5 Nm
WIRE STRIPPING LENGTH : 6 - 7.5 mm
INSERTION FORCE PER POLE : MAX 3 N
WITHDRAWAL FORCE PER POLE : MIN 1.5 N
3. ELECTRICAL
WIRE RANGE : 12-30 AWG
VOLTAGE RATING : 300 V
CURRENT RATING : 15 A
CONTACT RESISTANCE : <15 m Ohm
INSULATION RESISTANCE : >1000 M Ohm (500V DC)
4. OPERATING TEMPERATURE BETWEEN -40°C TO +105°C

- 5 TOLERANCE NOT CUMULATIVE
- 6 NOTE DELETED

OBSOLETE	13.0	2	2-284042-2
	88.0	12	1-284042-2
	80.5	11	1-284042-1
	73.0	10	1-284042-0
	65.5	9	284042-9
	58.0	8	284042-8
	50.5	7	284042-7
	43.0	6	284042-6
	35.5	5	284042-5
	28.0	4	284042-4
	20.5	3	284042-3
	13.0	2	284042-2
DIM. A		NO OF POS.	PART NUMBER

284042-3 AS SHOWN

2-284042-2 AS SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN E. ZANOLINI 03JAN2002	TE Connectivity NAME TERMINAL BLOCK VERTICAL PLUG STACKING, LEFT HAND 7.5mm PITCH	
DIMENSIONS: mm		CHK E. ZANOLINI 03JAN2002		
		APVD D. BIEVENOUR 03JAN2002		
		PRODUCT SPEC		
MATERIAL SEE NOTES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	APPLICATION SPEC	
		0 PLC ±° 1 PLC ±0.2 2 PLC ±0.15 3 PLC ±° 4 PLC ±° ANGLES ±2°		
FINISH SEE NOTES		WEIGHT	RESTRICTED TO	
		-		
CUSTOMER DRAWING		SCALE 3:1	SHEET 1 OF 1	REV B3