ATGBICS

ATGBICS EX-QSFP-8LC-AOC20M Juniper Compatible Active Optical Breakout Cable 40GBase QSFP+ to 4 Duplex LC (850nm MMF 20m)



Brand : ATGBICS

Product code: EX-QSFP-8LC-AOC20M-C

Product name : EX-QSFP-8LC-AOC20M Juniper Compatible Active Optical Breakout Cable 40GBase QSFP+ to 4 Duplex LC (850nm MMF 20m)

EX-QSFP-8LC-AOC20M Juniper Compatible Active Optical Breakout Cable 40GBase QSFP+ to 4 Duplex LC (850nm MMF 20m)

ATGBICS EX-QSFP-8LC-AOC20M Juniper Compatible Active Optical Breakout Cable 40GBase QSFP+ to 4 Duplex LC (850nm MMF 20m):

ATGBICS Juniper Compatible EX-QSFP-8LC-AOC20M 40GBase QSFP+ to 4 duplex LC Active Optical Cable operates over Active Fibre using a wavelength of 850nm over MMF with a cable length of 20m. This product operates within a commercial temperature range. It is suitable for short reach network. This breakout cable connects to 1 x 40G QSFP+ port on one end and to 4 x LC Duplex ports on the other end. Our product meets the specification of Juniper EX-QSFP-8LC-AOC20M and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Features	
Cable length *	20 m
InfiniBand protocol	✔
Cable shape	Round
Fastening type	Push–pull
Connector 1 *	QSFP+
Connector 2 *	4x LC
Connector 1 gender *	Male
Connector 2 gender *	Male
Cable type *	AOC
Product colour *	Aqua colour, Orange
Wavelengths supported	850 nm
Ethernet interface type	40 Gigabit Ethernet
Data transfer rate	40000 Gbit/s
Data transfer rate	40000 Mbit/s
Jacket material *	Optical fiber non-conductive plenum (OFNP), Low smoke zero halogen (LSZH)
Brand compatibility	Juniper
Plug and Play	✔

Sustainability	
Sustainability compliance	✔
Doesn't contain	Lead
Certificates	
Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Certification	CE, FCC, RoHS, REACH, FDA, TUV
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Weight & dimensions	
Bending radius	3 cm
Packaging content	
Quantity per pack	1 pc(s)
Other features	
Networking standards	IEEE 802.3ba
Logistics data	
Country of origin	China

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 15-SEP-2026. Prints or copies of Information are only valid on the printed Publication date