

6 OBSOLETE PART		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN09MAY2002 A.J.BEKEN CHK09MAY2002 S.CLAPPISON APVD09MAY2002 S.CLAPPISON		TE Connectivity			
7 INTERNAL FLASH INSIDE CAVITY (THIN AND FLEXIBLE THAT DO NOT COME OFF) ACCEPTABLE UP TO 0.15 mm. EXTERNAL FLASH ACCEPTABLE UP TO 0.4 mm		DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: LINEAR ±0.5 Ø PLC ±0.1 1 PLC ±0.1 2 PLC ±0.05 3 PLC ± 4 PLC ± ANGLES ±2°		NAME POSITIVE LOCK RECEPTACLE INSULATOR			
						PRODUCT SPEC 108-3252			
						APPLICATION SPEC 114-2153			
		MATERIAL See Table		FINISH -		WEIGHT 0.5g		SIZE A2	
						Customer Drawing		CAGE CODE 00779	
								DRAWING NO C=154719	
								RESTRICTED TO -	
								SCALE 5:1	
								SHEET 1	
								OF 1	
								REV AV8	