© 2026 TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	C7	PART STATUS CHANGE TO DISCONTINUANCE	07JUL2026	NS	PS











284041-3 AS SHOWN

NOTES
1. MATERIALS AND FINISH:
   HOUSING: PA 6-6, UL 94-V0, COLOR: GREEN.
   CLAMP: COPPER ALLOY, NICKEL PLATED.
   CONTACT SPRING : COPPER ALLOY, FINISH: SEE TABLE
   CLAMPING SCREW: M3, COPPER ALLOY, NICKEL PLATED.

2. MECHANICAL
   MAX. INSERTION FORCE PER HOLE : 3N
   MIN. WITHDRAWAL FORCE PER HOLE: 1.5N
   WIRE STRIPPING LENGTH : 6-7.5 mm
   RECOMMENDED/ HIGHEST TIGHTENING TORQUE : 0.5/0.6 Nm

3. ELECTRICAL
   WIRE RANGE : 30 - 12 AWG
   MAX. VOLTAGE : 300 V
   MAX CURRENT : 15 A
   CONTACT RESISTANCE : <15 m Ohm
   INSULATION RESISTANCE : >1000 M Ohm (500V DC)

4. OPERATING TEMPERATURE RANGE: -40°C TO +110°C

5 TOLERANCE NOT CUMULATIVE.

6 NOTE DELETED

7 SPECIAL MARKING TO BE PERMANENT BLACK LETTERING

8 SPECIAL MARKING TO BE IN PERMANENT BLACK INK

9 SPECIAL MARKING TO BE IN PERMANENT WHITE INK (SEE BACKGROUND COLOUR)

	DIM. A	NO OF POS.	PART NUMBER
DETAIL J	40.64	8	3-284041-4
8 DETAIL H	OBSOLETE	4	3-284041-3
8 DETAIL G	OBSOLETE	6	3-284041-2
8 DETAIL F	OBSOLETE	6	3-284041-1
8 DETAIL E	OBSOLETE	8	3-284041-0
9 DETAIL D	20.32	4	2-284041-9
8 DETAIL C	OBSOLETE	4	2-284041-8
7 DETAIL B	OBSOLETE	4	2-284041-7
DETAIL A	OBSOLETE	4	2-284041-6
	OBSOLETE	25	2-284041-5
	OBSOLETE	24	2-284041-4
	OBSOLETE	23	2-284041-3
	OBSOLETE	22	2-284041-2
	OBSOLETE	21	2-284041-1
	OBSOLETE	20	2-284041-0
	OBSOLETE	19	1-284041-9
	OBSOLETE	18	1-284041-8
	OBSOLETE	17	1-284041-7
	81.28	16	1-284041-6
	OBSOLETE	15	1-284041-5
	71.12	14	1-284041-4
	OBSOLETE	13	1-284041-3
	60.96	12	1-284041-2
	55.88	11	1-284041-1
	50.80	10	1-284041-0
	45.72	9	284041-9
	40.64	8	284041-8
	35.56	7	284041-7
	30.48	6	284041-6
	25.40	5	284041-5
	20.32	4	284041-4
	15.24	3	284041-3
	10.16	2	284041-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±0.3
2 PLC ±0.25
3 PLC ±-
4 PLC ±-
ANGLES ±2°

MATERIAL -
FINISH -

DWN E. ZANOLINI 27MAR2001
CHK D. BIEVENOUR 27MAR2001
APVD D. BIEVENOUR 27MAR2001
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME TERMINAL BLOCK, VERTICAL PLUG STACKING, LEFT HAND 5.08mm PITCH

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-284041	-

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 2 | REV C7

© 2026 TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



DETAIL A



DETAIL B



DETAIL C



DETAIL D



DETAIL E



DETAIL F



DETAIL G



DETAIL H



DETAIL J

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±0.3
2 PLC ±0.25
3 PLC ±
4 PLC ±
ANGLES ±2°

MATERIAL -
FINISH -

DWN E. ZANOLINI 27MAR2001
CHK D. BIEVENOUR 27MAR2001
APVD D. BIEVENOUR 27MAR2001
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME TERMINAL BLOCK, VERTICAL PLUG STACKING, LEFT HAND 5.08mm PITCH

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-284041	-

CUSTOMER DRAWING | SCALE 4:1 | SHEET 2 OF 2 | REV C7