© – TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	G1	REVISED PER ECR-23-179060	05SEP2023	AK	JP

1. MATERIAL: CONNECTOR–NYLON UL94V–2 (BLUE).
   CONTACTS–0.30 [.012] THICK COPPER ALLOY
   0.00038 [.000015] GOLD OR 0.00038 [.000015]
   TOTAL GOLD FLASH OVER PALLADIUM NICKEL,
   PER TE CONNECTIVITY'S DISCRETION, IN CONTACT
   AREA WITH MATTE TIN FOR 647480–2
   THRU 1–647480–3, MATTE WHISKER MITIGATED
   TIN FOR 3–647480–2 THRU 4–647480–3
   OVER NICKEL UNDERPLATE.
2. CONTACTS ACCEPT 26 AWG WIRE WITH 1.52 [.060] MAX INSULATION DIAMETER.
3. CONTACTS MUST ACCEPT 0.64±0.03 [.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
4. IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
5. DIMENSIONS IN BRACKETS ARE IN INCHES.
6. HOUSING FEATURES ARE: FEED THRU WITH LOCKING RAMP AND WITH POLARIZING TAB.
7. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



	LEAD FREE				LEAD FREE		
	DIM A	NO.OF POSN	ASSEMBLY		DIM A	NO.OF POSN	ASSEMBLY
	33.02 [1.300]	13	4–647480–3		33.02 [1.300]	13	⚠7 ~~1–647480–3~~
	30.48 [1.200]	12	4–647480–2		30.48 [1.200]	12	⚠7 ~~1–647480–2~~
	27.94 [1.100]	11	4–647480–1		27.94 [1.100]	11	⚠7 ~~1–647480–1~~
	25.40 [1.000]	10	4–647480–0		25.40 [1.000]	10	⚠7 ~~1–647480–0~~
OBSOLETE	22.86 [.900]	9	~~3–647480–9~~	OBSOLETE	22.86 [.900]	9	~~647480–9~~
	20.32 [.800]	8	3–647480–8		20.32 [.800]	8	647480–8
	17.78 [.700]	7	3–647480–7		17.78 [.700]	7	⚠7 ~~647480–7~~
	15.24 [.600]	6	3–647480–6		15.24 [.600]	6	647480–6
	12.70 [.500]	5	3–647480–5		12.70 [.500]	5	⚠7 ~~647480–5~~
	10.16 [.400]	4	3–647480–4		10.16 [.400]	4	647480–4
	7.62 [.300]	3	3–647480–3		7.62 [.300]	3	⚠7 ~~647480–3~~
	5.08 [.200]	2	3–647480–2		5.08 [.200]	2	⚠7 ~~647480–2~~

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±
2 PLC ± 0.13 [.005]
3 PLC ±
4 PLC ±
ANGLES ±

MATERIAL ⚠1

FINISH ⚠1

DWN	S. HOOVER 20–DEC–2004
CHK	D. BOSSI 20–DEC–2004
APVD	D. BOSSI 20–DEC–2004
PRODUCT SPEC	108–1050
APPLICATION SPEC	114–1019
WEIGHT	

TE Connectivity

NAME: MTA .100 CONNECTOR ASSEMBLY 26 AWG, STANDARD

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-647480	

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 1 | REV G1