








RECOMMENDED P.C. BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN R.K. SEIFRIED 04/09/90 D1K F. KIBLER 8-17-92		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± 0.13 [.005] 4 ANGLES ± —		NAME HDI, 4 ROW, PIN ASSEMBLY, 13.54 [.533] LONG ACTION PINS, ALL GOLD PLATED POSTS	
		PRODUCT SPEC — APPLICATION SPEC —		SIZE A1	
MATERIAL 		WEIGHT 0		CAGE CODE 00779	
FINISH 		DRAWING NO C=533270		RESTRICTED TO —	
CUSTOMER DRAWING				SCALE 4:1 SHEET 1 OF 2 REV M	

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

1

HOUSING MATERIAL: THERMOPLASTIC, COLOR—BLACK.

2

CONTACT MATERIAL: PHOSPHOR BRONZE.

3

FINISH:
MATING AREA: MEETS THE PERFORMANCE REQUIREMENTS OF PRODUCT SPECIFICATION 108—9063; BASED ON TELCORDIA DR—1217—CORE APPLICATIONS IN UNCONTROLLED ENVIRONMENTS.
GOLD FLASH ON REMAINDER OF POST.

4

ACTION PIN POSTS REQUIRE 2.36 [.093] MIN THICK P.C. BOARD. RECOMMENDED P.C. BOARD HOLES ARE 1.151 [.0453] DIA PLATED THRU WITH 0.025—0.076 [.001—.003] COPPER, WITH 0.0076 [.0003] MIN TIN—LEAD PLATING; FINISHED HOLE AFTER PLATING 0.94—1.09 [.037—043] DIA.

5

HOUSINGS WITH CENTER MOUNTING IS RECOMMENDED FOR ASSEMBLIES HAVING 75 CONTACTS PER ROW OR MORE.

6

OBSOLETE.

7

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

5	251.46 [9.900]	—99—	255.27 [10.050]	265.43 [10.450]	273.05 [10.750]	—400—	1—533270—6
5	226.06 [8.900]	—89—	229.87 [9.050]	240.03 [9.450]	247.65 [9.750]	—360—	1—533270—5
5	213.36 [8.400]	—84—	217.17 [8.550]	227.33 [8.950]	234.95 [9.250]	—340—	1—533270—4
5	200.66 [7.900]	—79—	204.47 [8.050]	214.63 [8.450]	222.25 [8.750]	—320—	1—533270—3
7	OBSOLETE	74	187.96 [7.400]	201.93 [7.950]	209.55 [8.250]	300	—1—533270—2—
6	175.26 [6.900]	69	179.07 [7.050]	189.23 [7.450]	196.85 [7.750]	280	1—533270—1
6	162.56 [6.400]	64	166.37 [6.550]	176.53 [6.950]	184.15 [7.250]	260	1—533270—0
6	149.86 [5.900]	59	153.67 [6.050]	163.83 [6.450]	171.45 [6.750]	240	533270—9
	137.16 [5.400]	54	140.97 [5.550]	151.13 [5.950]	158.75 [6.250]	220	533270—8
	124.46 [4.900]	49	128.27 [5.050]	138.43 [5.450]	146.05 [5.750]	200	533270—7
6	111.76 [4.400]	44	115.57 [4.550]	125.73 [4.950]	133.35 [5.250]	180	533270—6
	99.06 [3.900]	39	102.87 [4.050]	113.03 [4.450]	120.65 [4.750]	160	533270—5
6	86.36 [3.400]	34	90.17 [3.550]	100.33 [3.950]	107.95 [4.250]	140	533270—4
6	78.74 [3.100]	31	82.55 [3.250]	92.71 [3.650]	100.33 [3.950]	128	533270—3
6	73.66 [2.900]	29	77.47 [3.050]	87.63 [3.450]	95.25 [3.750]	120	533270—2
7	OBSOLETE	24	60.96 [2.400]	64.77 [2.550]	74.93 [2.950]	100	—533270—1—
	E	D	C	B	A	POSN	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN R.K. SEIFRIED CHK F. KIBLER APVD —		04/09/90 8-17-92	TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		NAME	
		0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± 0.13 [.005] 4 PLC ± — ANGLES ± — FINISH		APPLICATION SPEC		HDI, 4 ROW, PIN ASSEMBLY, 13.54 [.533] LONG ACTION PINS, ALL GOLD PLATED POSTS	
MATERIAL		WEIGHT		SIZE		CAGE CODE	
		0		A1		00779	
CUSTOMER DRAWING		SCALE		DRAWING NO		REV	
		4:1		C=533270		—	
		SHEET		OF		REV	
		2		2		M	