



REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	—	SEE SHEET 1	—	—	—


STANDARD POLARIZATION FOR RECEPTACLES




2P




3P




4P




5P




6P




7P




8P




9P




10P




11P




12P



13P




14P





15P


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Tommy Qian	12APR2021	 TE Connectivity Ltd.		
		CHK Niki Shi	12APR2021			
		APVD Niki Shi	12APR2021	NAME		
		PRODUCT SPEC		1.25mm PITCH WTB Conn.		
		APPLICATION SPEC		SMT V		
		WEIGHT	—	SIZE	CAGE CODE	DRAWING NO
				A3	00779	C-2390138
CUSTOMER DRAWING		SCALE	N/A	SHEET	2 of 3	REV B1

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ± 0.5
	1 PLC ± 0.25
	2 PLC ± 0.15
	3 PLC ± 0.1
	4 PLC ± —
	ANGLES ± 2°
MATERIAL	FINISH
NOTE 1	NOTE 2

HSF




BLACK	15	7-2390138-5	5-2390138-5	44.00±0.30	20.20±0.15	1000	2000	6000
	14	7-2390138-4	5-2390138-4					
	13	7-2390138-3	5-2390138-3					
	12	7-2390138-2	5-2390138-2	32.00±0.30	14.20±0.15	1000	2000	6000
	11	7-2390138-1	5-2390138-1					
	10	7-2390138-0	5-2390138-0					
	09	6-2390138-9	4-2390138-9					
	08	6-2390138-8	4-2390138-8					
	07	6-2390138-7	4-2390138-7					
	06	6-2390138-6	4-2390138-6	24.00±0.30	11.50±0.15	1000	3000	9000
NATURAL	05	6-2390138-5	4-2390138-5					
	04	6-2390138-4	4-2390138-4					
	03	6-2390138-3	4-2390138-3					
	02	6-2390138-2	4-2390138-2	16.00±0.30	7.50±0.15	1000	4000	12000
	15	3-2390138-5	1-2390138-5	44.00±0.30	20.20±0.15	1000	2000	6000
	14	3-2390138-4	1-2390138-4					
	13	3-2390138-3	1-2390138-3					
	12	3-2390138-2	1-2390138-2	32.00±0.30	14.20±0.15	1000	2000	6000
	11	3-2390138-1	1-2390138-1					
	10	3-2390138-0	1-2390138-0					
COLOR	09	2-2390138-9	2390138-9					
	08	2-2390138-8	2390138-8					
	07	2-2390138-7	2390138-7					
	06	2-2390138-6	2390138-6	24.00±0.30	11.50±0.15	1000	3000	9000
	05	2-2390138-5	2390138-5					
	04	2-2390138-4	2390138-4					
	03	2-2390138-3	2390138-3					
	02	2-2390138-2	2390138-2	16.00±0.30	7.50±0.15	1000	4000	12000
		GOLD FLASH	MATT TIN					
		PLATING SPEC						
		PART NUMBER						
				W	F	PCS/Reel	PCS/Inner Box	PCS/Outer Box




包装时产品卷入方向
Direction of product involvement during packaging

客户安装时拉出方向
Customer pull out direction




No.1:
BEFORE PACKAGE, PAY ATTENTION TO LEAVE MORE THAN 160MM(MIN) EMPTY, AFTER PUT THE PRODUCTS INTO THE CARRIER GROOVE, PACKING WITH THE COVER BEND THEN, NOTE: THE TENSION BETWEEN TAPE AND COVER BEND IS 10G~




Outer box: CTN-18KTE

No.4:
SEAL,PACK,LABEL.



No.3:
PUT INNER BOX INTO OUTER BOX, (3PCS INNER BOX/OUTER BOX) PAY ATTENTION TO THE UNIFIED LABEL DIRECTION.



Inner box: CTN-18E

No.2:
PACK THE REEL IN THE PE-33 WATERPROOF BAG PACKING, PUT 1PCS DRYING AGENT, SEAL IT WITH VACUUM MACHINE AND PUT IT INTO THE INNER BOX, SEAL IT WITH SEALING GLUE, WITH LABELS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Tommy Qian 12APR2021	TE Connectivity Ltd.			
		CHK Niki Shi 12APR2021				
DIMENSIONS: mm		APVD Niki Shi 12APR2021	NAME 1.25mm PITCH WTB Conn. SMT V			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL NOTE 1		FINISH NOTE 2	SIZE A3	CAGE CODE 00779	DRAWING NO C-2390138	RESTRICTED TO
CUSTOMER DRAWING			SCALE N/A	SHEET 3 of 3	REV B1	