



BUCHANAN WIREMATE CONNECTOR

SURFACE MOUNT TB SERIES

TE Connectivity (TE)'s BUCHANAN WireMate connectors surface mount series is a two-piece pluggable connector solution designed for customers seeking to switch from wave soldering to surface mount PCB processing. The latest series includes surface mount headers and mating plugs in vertical and right-angle configurations from 2 to 12 poles. The surface mount headers are one of several product offerings from TE enabling customers to make the change to full SMT processed printed circuit boards.

ELECTRICAL

- Current/Voltage Rating:
3.5mm: 2-12 position: 8A @ 300 VAC
5.0mm: 2-9 position: 15A @ 300 VAC
5.0mm: 10-12 position: 10A @ 300 VAC
- Impulse Withstanding Voltage: 2500 VAC

MECHANICAL

- Wire Gauge:
3.5mm: 30-16 AWG
5.0mm: 26-12 AWG
- Screw Torque: 4.5 in-lbf

MATERIALS

- Housing: Thermoplastic, Black (UL 94 V-0)
- Contact: Copper alloy, tin Plated

STANDARDS & SPECIFICATIONS

- UL E60677

BENEFITS

- Surface mount headers allow for simple reflow soldering and faster PCB assembly
- Retention features help ensure secure PCB mounting
- 90°, 180°, 270° wire entry plugs

APPLICATIONS



HVAC Equipment
and Controls



Industrial Controls



Security Systems






Industrial Lighting
Solutions






Elevator/Escalator

BUCHANAN WIREMATE CONNECTOR SURFACE MOUNT TB SERIES

PRODUCT SELECTION INFORMATION

3.5mm Plug			mates with 3.5mm Header		or mates with 3.5mm Header	
Positions	Plug PN's	Description	Header PN's	Description	Header PN's	Description
2	2213936-2	3.5mm Pitch 180° Wire Entry Plug 	2213932-2	3.5mm Pitch SMT Right Angle Standard Header 	2213933-2	3.5mm Pitch SMT Right Angle Header with Retention Pins 
3	2213936-3		2213932-3		2213933-3	
4	2213936-4		2213932-4			
5	2213936-5		2213932-5			
6	2213936-6		2213932-6		2213933-6	
7						
8	2213936-8					
9						
10	1-2213936-0		1-2213932-0		1-2213933-0	
11						
12	1-2213936-2		1-2213932-2		1-2213933-2	

5.0mm Header		mates with 5.0mm Plug		or mates with 5.0mm Plug		or mates with 5.0mm Plug		
Positions	Plug PN's	Description	Plugs PN's	Description	Plugs PN's	Description	Plugs PN's	Description
2	2305908-2	5.0mm Pitch SMT Right Angle Standard Header 	2305909-2	5.0mm Pitch 180° Wire Entry Plug with Retention Clips 	2213934-2	5.0mm Pitch 270° Wire Entry Plug with Retention Clips 	2213935-2	5.0mm Pitch 90° Wire Entry Plug with Retention Clips 
3	2305908-3		2305909-3		2213934-3		2213335-3	
4	2305908-4		2305909-4		2213934-4		2213935-4	
5	2305908-5		2305909-5		2213934-5		2213935-5	
6	2305908-6		2305909-6		2213934-6		2213935-6	
7			2305908-3				2213934-3	
8	2305908-8							
9								
10	1-2305908-0		1-2305909-0		1-2213934-0		1-2213935-0	
11								
12	1-2305908-2		1-2305909-2		1-2213934-2		1-2213935-2	

Connect With Us

We make it easy to connect with our experts and are ready to provide all the support you need.

Visit te.com/support to chat with a Product Information Specialist.

te.com/buchanan-wire-mate-connectors

BUCHANAN, WireMate, TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

© 2025 TE Connectivity. All Rights Reserved.

06-25