




- 1

MOLDED CIRCUIT #1 IDENTIFIER IN LOCATION SHOWN.
- 2

MATERIAL:GLASS FILLED THERMOPLASTIC, UL 94-V0 RATED, COLOR: BLACK
3. NOTE DELETED
- 5


TE LOGO ON EITHER SIDE

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	J	REVISED PER ECR-22-132152	15JUN2022	RK	SD
	J1	REVISED PER ECN-23-211206	24JUN2023	RK	MF
	J2	REVISED PER ECN-24-281985	29AUG2024	RK	MF
	J3	NOTE UPDATION	11APR2025	KS	VP



SECTION X - X

OBSOLETE	91.44[3.600]	35	72	3-102394-4
	88.90[3.500]	34	70	3-102394-3
	86.36[3.400]	33	68	3-102394-2
	83.82[3.300]	32	66	3-102394-1
	81.28[3.200]	31	64	3-102394-0
	78.74[3.100]	30	62	2-102394-9
	76.20[3.000]	29	60	2-102394-8
	73.66[2.900]	28	58	2-102394-7
	71.12[2.800]	27	56	2-102394-6
	68.58[2.700]	26	54	2-102394-5
	66.04[2.600]	25	52	2-102394-4
	63.50[2.500]	24	50	2-102394-3
	60.96[2.400]	23	48	2-102394-2
	58.42[2.300]	22	46	2-102394-1
	55.88[2.200]	21	44	2-102394-0
	53.34[2.100]	20	42	1-102394-9
	50.80[2.000]	19	40	1-102394-8
	48.26[1.900]	18	38	1-102394-7
	45.72[1.800]	17	36	1-102394-6
	43.18[1.700]	16	34	1-102394-5
	40.64[1.600]	15	32	1-102394-4
	38.10[1.500]	14	30	1-102394-3
	35.56[1.400]	13	28	1-102394-2
	33.02[1.300]	12	26	1-102394-1
	30.48[1.200]	11	24	1-102394-0
	27.94[1.100]	10	22	102394-9
	25.40[1.000]	9	20	102394-8
	22.86[.900]	8	18	102394-7
	20.32[.800]	7	16	102394-6
	17.78[.700]	6	14	102394-5
	15.24[.600]	5	12	102394-4
	12.70[.500]	4	10	102394-3
	10.16[.400]	3	8	102394-2
	7.62[.300]	2	6	102394-1
	B	A	NO. OF POSN	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. SHUEY	24JUL91	 TE Connectivity				
DIMENSIONS: mm [Inch]		CHK M. RIDER	24JUL91					
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. RIDER	24JUL91	NAME HOUSING, AMPMODU, MASS TERMINATION DOUBLE ROW, .100X.100 C/L -			
	0 PLC ± 1 PLC ± 2 PLC ±0.13 [.005] 3 PLC ± 4 PLC ± ANGLES ± FINISH ±		PRODUCT SPEC -					
			APPLICATION SPEC -					
MATERIAL 			WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=102394	RESTRICTED TO -	
CUSTOMER DRAWING				SCALE 4:1		SHEET 1	OF 1	REV J3