

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 2020
© COPYRIGHT 2020 BY TE CONNECTIVITY ALL RIGHTS RESERVED.


LOC	DIST

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	REVISED PER PCN E-20-008101	12JUN2020	DM	DM
	G1	REVISED PER PCN-22-157823	12OCT2022	SP	DM
	G2	REVISED PER PCN-25-234736	06FEB2025	GB	DM
	H	REVISED PER PCN-25-253652	14AUG2025	RT	DM







SECTION A-A
WIRE BARREL



SECTION B-B
INSULATION BARREL

	TE INTERNAL PN	DEUTSCH PN	REV	PLATING
	1062-14-0122	1062-14-0122	J	Ni/Cu overall, Sn/Ni/Cu Wire Barrel
1	1062-14-0144	1062-14-0144	K	Selective Au, Ni overall, Sn/Ni Wire Barrel
	1062-14-0177	1062-14-0177	J	Sn/Ni/Cu overall

5 TIN PLATING MAY BE IN THIS REGION.

4 TIN PLATED REGION.

3 MATERIAL:
BODY: .012 [0.30] THICK COPPER ALLOY
SLEEVE: STAINLESS STEEL

2. WIRE RANGE: 18 AWG TO 14 AWG [0.75-2.0 mm²]
INSULATION RANGE: Ø.095-.150 [Ø2.41-3.81]

1 GOLD PLATED REGION.

NOTES: UNLESS OTHERWISE SPECIFIED

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES[mm]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±0.025 [0.64]
4 PLC ±
ANGLES ±

MATERIAL 3

FINISH SEE TABLE

DWN M. BLUM 04NOV1999
CHK VLADIMIR TOMSA 04DEC2000
APVD R. REED 08DEC2000
PRODUCT SPEC 108-151000
APPLICATION SPEC 114-151000
WEIGHT 0.44 g

TE Connectivity

NAME SOCKET, STAMPED CONTACT
SIZE 16
14-18 AWG, .095-.150 INS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	4AFU8	C-1062-14-01XX	-

Customer Drawing | SCALE 6:1 | SHEET 1 OF 1 | REV H

1470-19 (3/11)