The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Plug for copper foil, stranded wire flat type cable

●Material・Finish

Part name	Material	Finish
Plug case	Polycarbonate	Clear
Terminal	Phosphor Bronze	Gold plated

Applicable Cable	
Conductor diameter	Copper foil or AWG #26
Insulator diameter	φ0.9-φ1.0

●Electrical Performance


Item	Condition	Specification
Current rating	Per pin	0.5A
Voltage rating	Per pin	125V AC
Insulation Resistance	100V DC	100MΩMin.
Withstanding Voltage	1minute	500V r.m.s AC


●TM3P-44P


CL No.	PartNo.	RoHS
222-0207-2	TM3P-44P	YES



(Packing unit: 100 Pcs.)







Applicable cable section

[Scheduled to be discontinued]


●TM3P-62P, 64P & 66P


CL No.	PartNo.	RoHS
222-0278-0	TM3P-62P	YES
222-0208-5	TM3P-64P	
222-0209-8	TM3P-66P	






(Packing unit: 100 Pcs.)





Note: Shown TM3P-64P.




Applicable cable section


Aug.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.


The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.


●TM 8P-88P




(Packing unit: 100 Pcs.)







CL No.	Part No.	RoHS
222-1817-9	TM 8P-88P	YES



Applicable cable section

【Scheduled to be discontinued】

Aug.1.2026 Copyright2026 HIROSE ELECTRIC CO., LTD. All rights Reserved.

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Plug for copper foil, stranded wire circular type cable

●Material・Finish

Part name	Material	Finish
Plug case	Polycarbonate	Clear
Terminal	Phosphor Bronze	Gold plated

Applicable Cable	
Conductor diameter	Copper foil or AWG #26
Insulator diameter	φ0.9-φ1.0

●Electrical Performance


Item	Condition	Specification
Current rating	Per pin	0.5A
Voltage rating	Per pin	125V AC
Insulation Resistance	100V DC	100MΩMin.
Withstanding Voltage	1minute	500V r.m.s AC


●TM4P-44P

CL No.	PartNo.	RoHS
222-0279-3	TM4P-44P	YES



(Packing unit: 100 Pcs.)





Applicable cable section


[Scheduled to be discontinued]


●TM4P-64P & 66P

CL No.	PartNo.	RoHS
222-0280-2	TM4P-64P	YES
222-0281-5	TM4P-66P	




(Packing unit: 100 Pcs.)







TM4P-64P



TM4P-66P





Applicable cable section


Note: Shown TM4P-64P.


Aug.1.2026 Copyright2026 HIROSE ELECTRIC CO., LTD. All rights Reserved.


The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.


●TM 10P-88P


CL No.	PartNo.	RoHS
222-1818-1	TM 10P-88P	YES











(Packing unit: 100 Pcs.)

【Scheduled to be discontinued】

Aug.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Plug Connector Cable Assembly Tool

Hand Tool



CL No.	Part No.	Applicable connector
CL902-2205-0	HT601-TM3/4P-44P	TM3P-44P、TM4P-44P
CL902-2206-3	HT601-TM3/4P-64P	TM3P-64P、TM4P-64P TM3P-62P
CL902-2207-6	HT601-TM3/4P-66P	TM3P-66P、TM4P-66P
250-0228-1	TC-2220-8/10P-88-1	TM8P-88P、TM10P-88P TM10P1-88P

【Scheduled to be discontinued】

This tool is made of metal and offers rigidity and durability. The handle is equipped with a ratchet mechanism that allows the press fit height of the plate contact to be set uniformly, and also permits the prevention of insufficient clamping.
* The tool can be used for insulation stripping of flat cables and round cables. Note that model HT601-TM3/4P-66P is for use with flat cables only. Also note that model TC-2220-8/10P-88-1 is not equipped with an insulation stripping mechanism.
* The cable is pulled out by the lever which permits consistent insulation stripping.

Note: Please note that depending on the specifications of the cable, there may be instances in which the insulation cannot be stripped.
When using the tool with products other than Hirose Electric modular plugs, the wiring quality cannot be guaranteed; therefore, please be sure to use Hirose Electric plugs.

Item	Part No.	CL No.	Applicable connector
Press	CM-105	901-0005-4	
Applicator	Applicator 105-TMP-44	901-0195-1	TM3P-44P、TM4P-44P
	Applicator 105-TMP-64	901-0194-9	TM3P-64P、TM4P-64P TM2P-62P
	Applicator 105-TMP-66	901-0193-6	TM3P-66P、TM4P-66P
	AP105-TM10P1-88P	901-2569-0	TM8P-88P、TM10P-88P

Aug.1.2026 Copyright2026 HIROSE ELECTRIC CO., LTD. All rights Reserved.

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Plug for Solid Wire Cable

●Material・Finish

Part name	Material	Finish
Plug case	Polycarbonate	Clear
Terminal	Phosphor Bronze	Gold plated

Applicable Cable	
Conductor diameter	φ0.4~ φ0.65 *
Insulator diameter	φ0.96 max.

* In case of use φ0.65, not to be connected fully for 6 pins and 8 pins depend on size of insulator diameter.


●Electrical Performance

Item	Condition	Specification
Current rating	Per pin	0.5A
Voltage rating	Per pin	30V AC
Insulation Resistance	100V DC	100 MΩ Min.
Withstanding Voltage	1 minute	500V r.m.s AC


●TM 20P-66P

CL No.	PartNo.	RoHS
222-2275-3	TM 20P-66P	YES





Mating Condifiton Figure




(Packing unit: 100 Pcs.)

[Scheduled to be discontinued]


●TM 20P-88P

CL No.	PartNo.	RoHS
222-2217-7	TM 20P-88P	YES





Mating Condifiton Figure



(Packing unit: 100 Pcs.)

Exclusive Hand Tool for Connection



CL No.	PartNo.	Applicable Connector
250-0240-7	TC2-TM 20P-66P	TM 20P-66P
250-0241-0	TC2-TM 20P/30P-88P	TM 20P-88P

Aug.1.2026 Copyright2026 HIROSE ELECTRIC CO., LTD. All rights Reserved.

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
All non-RoHS products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website RoHS search at www.hirose-connectors.com, or contact your Hirose sales representative.

Plug for Thin Wire Cable

●Material・Finish

Part name	Material		Finish
Plug case	Polycarbonate	6 Pins	Clear blue
	*	8 Pins	Clear
Terminal	Phosphor Bronze		Gold plated

*UL94V-0

Applicable Cable	
Conductor diameter	AWG #28(7/0.127)
Insulator diameter	φ0.787 max.


●Electrical Performance

Item	Condition	Specification
Current rating	Per pin	0.5A
Voltage rating	Per pin	125V AC
Insulation Resistance	100V DC	100MΩMin.
Withstanding Voltage	1minute	500V r.m.s AC

●TM30P-66P

CL No.	PartNo.	RoHS
222-2684-2	TM30P-66P	YES






(Scheduled to be discontinued)

●TM30P-88P

CL No.	PartNo.	RoHS
222-2685-5	TM30P-88P	YES





Exclusive Hand Tool for Connection



CL No.	PartNo.	Applicable Connector
250-0145-6	TC1-TM30P-66P	TM30P-66P
250-0241-0	TC2-TM20P/30P-88P	TM30P-88P

Aug.1.2026 Copyright2026 HIROSE ELECTRIC CO., LTD. All rights Reserved.