


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

99.06[3.900]	101.60[4.000]	80		9-146762-0
96.52[3.800]	99.06[3.900]	78		8-146762-9
93.98[3.700]	96.52[3.800]	76		8-146762-8
91.44[3.600]	93.98[3.700]	74		8-146762-7
88.90[3.500]	91.44[3.600]	72		8-146762-6
86.36 3.400]	88.90[3.500]	70		8-146762-5
83.82[3.300]	86.36[3.400]	68		8-146762-4
81.28[3.200]	83.82[3.300]	66		8-146762-3
76.20[3.000]	78.74[3.100]	62		8-146762-2
73.66[2.900]	76.20[3.000]	60		8-146762-1
71.12[2.800]	73.66[2.900]	58		8-146762-0
68.58[2.700]	71.12[2.800]	56		7-146762-9
66.04 2.600]	68.58[2.700]	54		7-146762-8
63.50[2.500]	66.04[2.600]	52		7-146762-7
60.96[2.400]	63.50[2.500]	50		7-146762-6
58.42[2.300]	60.96[2.400]	48		7-146762-5
55.88[2.200]	58.42[2.300]	46		7-146762-4
53.34[2.100]	55.88[2.200]	44		7-146762-3
50.80[2.000]	53.34[2.100]	42		7-146762-2
45.72[1.800]	48.26[1.900]	38		7-146762-1
43.18[1.700]	45.72[1.800]	36		7-146762-0
40.64[1.600]	43.18[1.700]	34		6-146762-9
38.10[1.500]	40.64[1.600]	32		6-146762-8
33.02[1.300]	35.56[1.400]	28		6-146762-7
30.48[1.200]	33.02[1.300]	26		6-146762-6
27.94[1.100]	30.48[1.200]	24		6-146762-5
25.40[1.000]	27.94[1.100]	22		6-146762-4
17.78[.700]	20.32[.800]	16		6-146762-3
15.24[.600]	17.78[.700]	14		6-146762-2
12.70[.500]	15.24[.600]	12		6-146762-1
5.08[.200]	7.62[.300]	6		6-146762-0
2.54[.100]	5.08[.200]	4		5-146762-9
	2.54[.100]	2		 5-146762-8
22.86[.900]	25.40[1.000]	20		5-146762-7
78.74[3.100]	81.28[3.200]	64		5-146762-6
48.26[1.900]	50.80[2.000]	40		5-146762-5
35.56[1.400]	38.10[1.500]	30		5-146762-4
20.32[.800]	22.86[.900]	18		5-146762-3
10.16[.400]	12.70[.500]	10		5-146762-2
7.62[.300]	10.16[.400]	8		5-146762-1

FINISH	B	A	NO OF POSN	PART NUMBER
--------	---	---	------------	-------------

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER 06NOV2002	 TE Connectivity			
		CHK J.OLSON 06NOV02				
		APVD J.OLSON 06NOV02				
		PRODUCT SPEC 108-25022				
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME RCPT. ASSY., MOD II, DBL ROW, .100 X .100 DOUBLE ROW, DUAL ENTRY, .100X.100CL, VERTICAL MOUNT, AMPMODU		
		0 PLC ±- 1 PLC ±- 2 PLC ±0.13[.005] 3 PLC ±- 4 PLC ±- ANGLES ±- FINISH		SIZE 114-25018		
				APPLICATION SPEC		
				WEIGHT -		
MATERIAL 		FINISH  		A200779  146762		RESTRICTED TO -
CUSTOMER DRAWING				SCALE 4:1	SHEET 2 OF 2	REV L