

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	Z1	REVISE PER ECN-22-144098	17MAR2022	MP	MT



AS SUPPLIED



AFTER UNRESTRICTED RECOVERY

TABLE OF DIMENSIONS

PART NUMBER	H				J				P	R	S	T	JO	W
	Min -3,-4,-25 a	Min -12,-100 a	Min -6 a	Max b	Min -3,-4,-25 a	Min -12,-100 a	Min a	Max b	±10% b	±10% b	Ref b	Ref b	Ref b	±20% b
202A111	16.5 [.65]	16.5 [.65]	16.5 [.65]	7.9 [.31]	16.5 [.65]	11.9 [.47]	16.5 [.65]	3.8 [.15]	25.4 [1.00]	14.2 [.56]	12.7 [.50]	N/A	5.8 [.23]	1.27 [.05]
202A121	24.6 [.97]	22.6 [.89]	23.4 [.92]	9.9 [.39]	24.6 [.97]	17.8 [.70]	23.4 [.92]	5.3 [.21]	38.1 [1.50]	21.8 [.86]	15.2 [.60]	N/A	9.1 [.36]	1.52 [.06]
202A132	28.4 [1.12]	26.2 [1.03]	26.7 [1.05]	14.2 [.56]	28.4 [1.12]	20.3 [.80]	26.7 [1.05]	6.6 [.26]	51.3 [2.02]	27.9 [1.10]	19.1 [.75]	16.0 [.63]	13.0 [.51]	1.78 [.07]
202A142	31.0 [1.22]	31.0 [1.22]	31.0 [1.22]	17.8 [.70]	31.0 [1.22]	25.4 [1.00]	31.0 [1.22]	7.4 [.29]	66.8 [2.63]	35.6 [1.40]	19.1 [.75]	22.1 [.87]	17.8 [.70]	1.78 [.07]
202A153	36.0 [1.42]	36.0 [1.42]	36.0 [1.42]	21.9 [.86]	36.0 [1.42]	26.2 [1.03	36.0 [1.42]	8.6 [.34]	73.7 [2.90]	41.4 [1.63]	19.1 [.75]	22.1 [.87]	16.0 [.63]	1.78 [.07]
202A163	42.7 [1.68]	42.7 [1.68]	42.7 [1.68]	27.4 [1.08]	42.7 [1.68]	27.2 [1.07]	42.7 [1.68]	9.4 [.37]	99.1 [3.90]	62.7 [2.47]	19.1 [.75]	25.2 [.99]	18.0 [.71]	2.03 [.08]
202A174	51.8 [2.04]	48.3 [1.90]	51.8 [2.04]	35.3 [1.39]	51.8 [2.04]	48.3 [1.90]	51.8 [2.04]	16.0 [.63]	130.3 [5.13]	64.8 [2.55]	25.4 [1.00]	50.8 [2.00]	41.9 [1.65]	3.30 [.13]
202A185	66.0 [2.60]	66.0 [2.60]	66.0 [2.60]	43.7 [1.72]	66.0 [2.60]	54.1 [2.13]	66.0 [2.60]	19.6 [.77]	161.3 [6.35]	90.2 [3.55]	25.4 [1.00]	54.6 [2.15]	47.8 [1.88]	3.81 [.15]
202A196	86.4 [3.40]	86.4 [3.40]	86.4 [3.40]	57.2 [2.25]	86.4 [3.40]	71.4 [2.81]	86.4 [3.40]	26.9 [1.06]	212.6 [8.37]	113.0 [4.45]	25.4 [1.00]	80.0 [3.15]	62.2 [2.45]	4.06 [.16]

RELEASED FOR PUBLICATION - , - .
ALL RIGHTS RESERVED.
© COPYRIGHT - TE Connectivity Ltd.
THIS DRAWING IS UNPUBLISHED.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± –
1 PLC	± 0.50[.1]
2 PLC	± 0.25[.01]
3 PLC	± 0.13[.005]
4 PLC	± –
ANGLES	± 1°

DWN PRAVEEN N T 31JAN2019
CHK N NAGAR 31JAN2019
APVD M TAYLOR 31JAN2019
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

MATERIAL SEE SHEET 2
FINISH –

TE Connectivity Ltd.

NAME BOOT, STRAIGHT, OVEREXPANDED
–

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A4	06090	C- 202A111-XX-0THRU196-XX-0	—

CUSTOMER DRAWING | SCALE DNS | SHEET 1 OF 2 | REV Z1

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

COMPATABILITY CHART				
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.
–3	Polyolefin, Semi–rigid	RT–301	/42; /86; /180	S1017; S1048; S1030
–4	Polyolefin, Flexible	RT–1304	/42; /86; /180	S1017; S1048; S1030
–12	Fluoroelastomer, Flexible	RT–1312	N/A	N/A
–25	Elastomer, Fluid Resistant	RW–2070	/42; /86; /225	S1017; S1048; S1206
–100	Polyolefin, Simi–flexible ZEROHAL	RW–2082	/86; /180	S1048; S1030

ORDERING INFORMATION

202A1XX –XX –XX /XX –0

BASE PART NUMBER

MATERIAL DASH NUMBER
(SEE COMPATIBILITY CHART)

MODIFICATION NUMBER

ADHESIVE SLASH NUMBER
(IF NECESSARY SEE COMPATIBILITY CHART)

COLOR DESIGNATOR

NOTES:

1. DIMENSIONS APPEARING IN TABLE ARE AS FOLLOWS:
   a – AS SUPPLIED
   b – AFTER UNRESTRICTED RECOVERY
2. COATING (ADHESIVE) IS OPTIONAL. AS SUPPLIED DIMENSIONS APPEARING IN TABLE ARE FOR UNCOATED PARTS. WHEN COATING IS ADDED, ENTRY DIAMETER WILL BE REDUCED BY 1.5mm[.06] MAX.
3. MOLDING PORTS ARE OPTIONAL. WHEN –00 MODIFICATION NUMBER IS SPECIFIED, MOLDING PORTS WILL BE LOCATED AS SHOWN.

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- -. © COPYRIGHT - TE Connectivity Ltd. ALL RIGHTS RESERVED.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± –
1 PLC	± 0.50[.1]
2 PLC	± 0.25[.01]
3 PLC	± 0.13[.005]
4 PLC	± –
ANGLES	± 1°

DWN PRAVEEN N T 31JAN2019
CHK N NAGAR 31JAN2019
APVD M TAYLOR 31JAN2019
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

MATERIAL –
FINISH –

TE Connectivity Ltd.

NAME
BOOT, STRAIGHT, OVEREXPANDED
–

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A4	06090	C– 202A111–XX–0THRU196–XX–0	—

CUSTOMER DRAWING | SCALE DNS | SHEET 2 OF 2 | REV Z1