APTM100DSK35T3G

Dual Buck chopper MOSFET Power Module

V_{DSS} = 1000V
R_{DSon} = 350mΩ typ @ Tj = 25°C
I_D = 22A @ Tc = 25°C





All multiple inputs and outputs must be shorted together
Example: 13/14 ; 29/30 ; 22/23 …

Application

- AC and DC motor control
- Switched Mode Power Supplies

Features

- **Power MOS 7® MOSFETs**
  - Low R_{DSon}
  - Low input and Miller capacitance
  - Low gate charge
  - Avalanche energy rated
  - Very rugged
- Kelvin source for easy drive
- Very low stray inductance
- Internal thermistor for temperature monitoring

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- Each leg can be easily paralleled to achieve a single buck of twice the current capability
- RoHS Compliant

All ratings @ T_j = 25°C unless otherwise specified

Absolute maximum ratings (per MOSFET)

Symbol	*Parameter*		*Max ratings*	*Unit*
V_{DSS}	Drain - Source Voltage		1000	V
I_D	Continuous Drain Current	T_c = 25°C	22	A
		T_c = 80°C	17	
I_{DM}	Pulsed Drain current		88	
V_{GS}	Gate - Source Voltage		±30	V
R_{DSon}	Drain - Source ON Resistance		420	mΩ
P_D	Power Dissipation	T_c = 25°C	390	W
I_{AR}	Avalanche current (repetitive and non repetitive)		25	A
E_{AR}	Repetitive Avalanche Energy		50	mJ
E_{AS}	Single Pulse Avalanche Energy		3000	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

Electrical Characteristics (per MOSFET)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{DSS}	Zero Gate Voltage Drain Current	V_{GS} = 0V,V_{DS} = 1000V			100	µA
$R_{DS(on)}$	Drain – Source on Resistance	V_{GS} = 10V, I_D = 11A		350	420	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 2.5mA	3		5	V
I_{GSS}	Gate – Source Leakage Current	V_{GS} = ±30V, V_{DS} = 0V			±150	nA

Dynamic Characteristics (per MOSFET)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input Capacitance	V_{GS} = 0V V_{DS} = 25V f = 1MHz		5.2		nF
C_{oss}	Output Capacitance			0.88		
C_{rss}	Reverse Transfer Capacitance			0.16		
Q_g	Total gate Charge	V_{GS} = 10V V_{Bus} = 500V I_D = 22A		186		nC
Q_{gs}	Gate – Source Charge			24		
Q_{gd}	Gate – Drain Charge			122		
$T_{d(on)}$	Turn-on Delay Time	**Inductive switching @ 125°C** V_{GS} = 15V V_{Bus} = 670V I_D = 22A R_G = 5Ω		18		ns
T_r	Rise Time			12		
$T_{d(off)}$	Turn-off Delay Time			155		
T_f	Fall Time			40		
E_{on}	Turn-on Switching Energy	**Inductive switching @ 25°C** V_{GS} = 15V, V_{Bus} = 670V I_D = 22A, R_G = 5Ω		900		µJ
E_{off}	Turn-off Switching Energy			623		
E_{on}	Turn-on Switching Energy	**Inductive switching @ 125°C** V_{GS} = 15V, V_{Bus} = 670V I_D = 22A, R_G = 5Ω		1423		µJ
E_{off}	Turn-off Switching Energy			779		
R_{thJC}	Junction to Case Thermal Resistance				0.32	°C/W

Chopper Diode ratings and characteristics (per diode)

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V_{RRM}	Peak Repetitive Reverse Voltage					1000	V
I_{RM}	Reverse Leakage Current	V_R=1000V				250	µA
I_F	DC Forward Current		T_c = 70°C		30		A
V_F	Diode Forward Voltage	I_F = 30A			1.9	2.3	V
		I_F = 60A			2.2		
		I_F = 30A	T_j = 125°C		1.7		
t_{rr}	Reverse Recovery Time	I_F = 30A V_R = 667V di/dt=200A/µs	T_j = 25°C		290		ns
			T_j = 125°C		390		
Q_{rr}	Reverse Recovery Charge		T_j = 25°C		670		nC
			T_j = 125°C		2350		
R_{thJC}	Junction to Case Thermal Resistance					1.2	°C/W

Thermal and package characteristics

Symbol	Characteristic			Min	Max	Unit
V_{ISOL}	RMS Isolation Voltage, any terminal to case t =1 min, 50/60Hz			4000		V
T_J	Operating junction temperature range			-40	150	°C
T_{JOP}	Recommended junction temperature under switching conditions			-40	$T_J$max - 25	
T_{STG}	Storage Temperature Range			-40	125	
T_C	Operating Case Temperature			-40	125	
Torque	Mounting torque	To heatsink	M4	2	3	N.m
Wt	Package Weight				110	g

Temperature sensor NTC (see application note APT0406 on www.microsemi.com for more information).

Symbol	Characteristic		Min	Typ	Max	Unit
R_{25}	Resistance @ 25°C			50		kΩ
$\Delta R_{25}/R_{25}$				5		%
$B_{25/85}$	T_{25} = 298.15 K			3952		K
ΔB/B		T_C=100°C		4		%

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$

T: Thermistor temperature
R_T: Thermistor value at T

Package outline (dimensions in mm)



See application note 1906 - Mounting Instructions for SP3F Power Modules on www.microsemi.com

Typical Performance Curve












Breakdown Voltage vs Temperature
BVDSS, Drain to Source Breakdown Voltage (Normalized)
1.15
1.10
1.05
1.00
0.95
0.90
0.85
-50 -25 0 25 50 75 100 125 150
TJ, Junction Temperature (°C)


ON resistance vs Temperature
VGS=10V
ID=11A
RDS(on), Drain to Source ON resistance (Normalized)
2.5
2.0
1.5
1.0
0.5
0.0
-50 -25 0 25 50 75 100 125 150
TJ, Junction Temperature (°C)


Threshold Voltage vs Temperature
VGS(TH), Threshold Voltage (Normalized)
1.2
1.1
1.0
0.9
0.8
0.7
0.6
-50 -25 0 25 50 75 100 125 150
TC, Case Temperature (°C)


Maximum Safe Operating Area
limited by RDSon
100µs
1ms
10ms
Single pulse
TJ=150°C
TC=25°C
ID, Drain Current (A)
100
10
1
1 10 100 1000
VDS, Drain to Source Voltage (V)


Capacitance vs Drain to Source Voltage
C, Capacitance (pF)
100000
10000
1000
100
Ciss
Coss
Crss
0 10 20 30 40 50
VDS, Drain to Source Voltage (V)


Gate Charge vs Gate to Source Voltage
ID=22A
TJ=25°C
VDS=200V
VDS=500V
VDS=800V
VGS, Gate to Source Voltage (V)
14
12
10
8
6
4
2
0
0 50 100 150 200 250
Gate Charge (nC)


Delay Times vs Current
$t_{d(on)}$ and $t_{d(off)}$ (ns)
I_D, Drain Current (A)
V_{DS}=670V
R_G=5Ω
T_J=125°C
L=100µH
$t_{d(off)}$
$t_{d(on)}$


Rise and Fall times vs Current
t_r and t_f (ns)
I_D, Drain Current (A)
V_{DS}=670V
R_G=5Ω
T_J=125°C
L=100µH
t_f
t_r


Switching Energy vs Current
Switching Energy (mJ)
I_D, Drain Current (A)
V_{DS}=670V
R_G=5Ω
T_J=125°C
L=100µH
E_{on}
E_{off}


Switching Energy vs Gate Resistance
Switching Energy (mJ)
Gate Resistance (Ohms)
V_{DS}=670V
I_D=22A
T_J=125°C
L=100µH
E_{off}
E_{on}
E_{off}


Operating Frequency vs Drain Current
Frequency (kHz)
I_D, Drain Current (A)
V_{DS}=670V
D=50%
R_G=5Ω
T_J=125°C
T_C=75°C
ZVS
ZCS
Hard
switching


Source to Drain Diode Forward Voltage
I_{DR}, Reverse Drain Current (A)
V_{SD}, Source to Drain Voltage (V)
T_J=150°C
T_J=25°C

DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at http://www.microsemi.com/legal/tnc.asp

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or directly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.