









LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
AA	22					
		C2		REVISED PER ECO-11-005033	04MAY11	RK
		D		ECO-15-006810	22JAN2016	LL
		D1		REVISED PER ECO-21-000623	28JUL2020	IT




- △ HOUSING: PBT POLYESTER, BLACK, UL 94V-0.
TERMINALS: 0.30 THICK PHOS BRONZE PLATED WITH 1.27µm MINIMUM THICK HARD GOLD IN LOCALIZED AREA AND 2µm MINIMUM THICK MATTE TIN IN ACTION PIN COMPLIANT PIN TERMINAL AREA OVER 1.27µm MINIMUM THICK NICKEL UNDERPLATE.
SHIELD: 0.25 THICK COPPER ALLOY PLATED WITH 1.27µm MINIMUM NICKEL.
GROUND CLIPS: 0.25 THICK COPPER ALLOY PLATED WITH 2.03µm MINIMUM MATTE TIN OVER 1.27µm MINIMUM NICKEL.
LIGHT EMITTING DIODE (LED): DIFFUSED EPOXY LENS, 12.95 CARBON STEEL WIREFRAME LEADS PLATED WITH 8.89µm TIN/COPPER OVER 2.03µm SILVER OVER 1.02µm COPPER OVER 3.56µm NICKEL OVER 1.02µm COPPER UNDERPLATE.
LED ACTION PIN COMPLIANT PIN CONTACTS: 0.30 THICK BRASS PLATED WITH 2µm MINIMUM MATTE TIN OVER 1.27µm MINIMUM NICKEL UNDERPLATE.
2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS, PART 68 SUBPART F.
3. ALL DIMENSIONS ARE NOMINAL UNLESS OTHERWISE SPECIFIED.
4. TWO LEDS PER PORT, SIZE .079 X .118, SEE TABLE.
- △ 5. DRILLED HOLE DIA = .040±.001.
COPPER THICKNESS = .001-.003.
TIN THICKNESS = .0003 MIN.
- △ 6. DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- △ 7. DATE CODE LOCATED ON REAR OF PART APPROXIMATELY AS SHOWN.
- △ 8. THESE FOUR SIDE PCB ACTION PIN GROUNDS AND CORRESPONDING PCB HOLES ARE REQUIRED ONLY ON 6116317-2, 6116317-3, 6116317-5, 6116317-6, 6116317-7, -9 AND 1--0.
- △ 9. SUGGESTED OPERATING CURRENT FOR LEDS IS 20 mA.




RED/GREEN	RED/GREEN	RED/GREEN	RED/GREEN	1-6116317-0
GREEN/YELLOW	GREEN/YELLOW	RED/GREEN	RED/GREEN	6116317-9
GREEN/YELLOW	GREEN/YELLOW	RED/GREEN	RED/GREEN	6116317-8
GREEN	GREEN	YELLOW	YELLOW	6116317-7
YELLOW	YELLOW	GREEN	GREEN	6116317-6
GREEN/YELLOW	GREEN/YELLOW	GREEN/YELLOW	GREEN/YELLOW	6116317-5
GREEN	GREEN	GREEN	GREEN	6116317-4
GREEN	GREEN	GREEN	GREEN	6116317-3
GREEN	GREEN	GREEN	GREEN	6116317-2
GREEN	GREEN	GREEN	GREEN	6116317-1
LED #4 (LOWER-RIGHT)	LED #3 (UPPER-RIGHT)	LED #2 (UPPER-LEFT)	LED #1 (LOWER-LEFT)	PART NO.





THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. VARELA CHK J. WESTMAN APVD S. FLICKINGER	23JUN2005 DOCKS 23JUN2005 23JUN2005	TE Connectivity	
DIMENSIONS: INCHES[mm]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-1854	APPLICATION SPEC 114-2160	NAME STACKED MODULAR JACK ASSEMBLY, 2X8 WITH LEDS, 8 POSITION, SHIELDED PANEL GROUND, OFFSET, CAT 5	
MATERIAL	FINISH	WEIGHT 1 = 77.2 grams	SIZE A1	CAGE CODE 00779	RESTRICTED TO DRAWING NO 6116317
CUSTOMER DRAWING		SCALE 3:1	SHEET 1	OF 3	REV D1



PC BOARD LAYOUT
(COMPONENT SIDE)



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AA	22	-	-	SEE SHEET 1	-	-	-



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. VARELA 23JUN2005	TE Connectivity	
DIMENSIONS: INCHES[mm]		CHK J. WESTMAN 23JUN2005		
	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD S. FLICKINGER 23JUN2005	NAME STACKED MODULAR JACK ASSEMBLY, 2X8 WITH LEDS, 8 POSITION, SHIELDED PANEL GROUND, OFFSET, CAT 5	
	0 PLC ±"	PRODUCT SPEC		
	1 PLC ±"	108-1854	SIZE A1	
	2 PLC ±"	APPLICATION SPEC		
MATERIAL -	3 PLC ±.005 (0.13)	114-2160	CAGE CODE 00779	
	4 PLC ±.005 (0.13)	WEIGHT 77.2 grams		
FINISH -		CUSTOMER DRAWING	RESTRICTED TO	
		SCALE 3:1	SHEET 3 OF 3	
			REV D1	