

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	R	PRODUCTION ISSUE	31JAN2019	PNT	MT



AS SUPPLIED



AFTER UNRESTRICTED RECOVERY

TABLE OF DIMENSIONS

PART NUMBER	H Min a	H Max b	J,K,L & N Min a	J,K,L & N Max b	P ±10% b	R ±10% b	S ±10% b	T ±10% b	U ±10% b	C° ±5% b	D° ±5% b	HW ±20% b	W ±20% b	Weight Nom lb/[gms] b
562A011	13.2 [.52]	6.9 [.27]	6.6 [.26]	3.5 [.14]	24.1 [.95]	38.4 [1.51]	24.1 [.95]	43.9 [1.73]	20.0 [.79]	45	15	1.52 [.06]	1.02 [.04]	3.63 [.008]
562A022	19.3 [.76]	9.7 [.38]	9.4 [.37]	5.3 [.21]	35.6 [1.40]	36.1 [1.42]	32.0 [1.26]	43.2 [1.70]	23.1 [.91]	45	15	1.78 [.07]	1.02 [.04]	6.80 [.015]
562A032	19.3 [.76]	9.7 [.38]	13.2 [.52]	6.9 [.27]	49.3 [1.94]	36.1 [1.42]	45.0 [1.77]	50.5 [1.99]	25.4 [1.00]	45	15	1.78 [.07]	1.52 [.06]	13.61 [.030]
562A043	26.9 [1.06]	13.0 [.51]	13.2 [.52]	6.9 [.27]	49.3 [1.94]	51.8 [2.04]	45.0 [1.77]	65.8 [2.59]	33.5 [1.32]	45	15	2.54 [.10]	1.52 [.06]	18.60 [.041]
562A054	38.6 [1.52]	18.5 [.73]	19.3 [.76]	9.7 [.38]	71.9 [2.83]	74.9 [2.95]	65.3 [2.57]	95.3 [3.75]	46.5 [1.83]	45	15	3.05 [.12]	1.78 [.07]	54.43 [.120]
562A067	55.6 [2.19]	26.7 [1.05]	26.9 [1.06]	13.0 [.51]	101.6 [4.00]	108.5 [4.27]	92.5 [3.64]	135.1 [5.32]	65.5 [2.58]	45	15	4.57 [.18]	2.54 [.10]	149.69 [.330]

THIS DRAWING IS UNPUBLISHED. © COPYRIGHT - By - ALL RIGHTS RESERVED. RELEASED FOR PUBLICATION - , - .

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

DWN PRAVEEN N T 31JAN2019
CHK N NAGAR 31JAN2019
APVD M TAYLOR 31JAN2019
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

MATERIAL SEE SHEET 2
FINISH –

TE Connectivity Ltd.

NAME TRANSITION, 1 TO 4 CABLES
—

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A4	00779	C- 562A011-XX-0THRU067-XX-0	—

CUSTOMER DRAWING | SCALE DNS | SHEET 1 OF 2 | REV R

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

COMPATABILITY CHART

MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATINGSLASHNO.	COATINGSNO.
-3	Polyolefin, Semi-rigid	RT-301	/42; /86; /180	S1017; S1048; S1030
-4	Polyolefin, Flexible	RT-1304	/42; /86; /180	S1017; S1048; S1030
-12	Fluoroelastomer, flexible	RT-1312	N/A	N/A
-25	Elastomer, Fluid Resistant	RW-2070	/42; /86; /225	S1017; S1048; S1206
-100	Polyolefin, Semi-flexible ZEROHAL	RW-2082	/86,/180	S-1048; S-1030

ORDERING INFORMATION

562A0XX -XX -XX /XX -0

Base part number

Material dash number
(See Compatability Chart)

Modification number

Adhesive slash number
(If necessary, see Compatability Chart)

Color designator

NOTES

1. Dimensions appearing in table are as follows:
   a – As Supplied
   b – After Unrestricted Recovery
2. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by 1.5mm[.06] max.
3. Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
4. Weight appearing in table of dimensions is based on polyolefin part.

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,-. -
© COPYRIGHT - By -
ALL RIGHTS RESERVED.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

DWN PRAVEEN N T 31JAN2019
CHK N NAGAR 31JAN2019
APVD M TAYLOR 31JAN2019
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

MATERIAL –
FINISH –

TE Connectivity Ltd.

NAME
TRANSITION, 1 TO 4 CABLES
–

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A4	00779	C- 562A011-XX-0THRU067-XX-0	—

CUSTOMER DRAWING | SCALE DNS | SHEET 2 OF 2 | REV R