



IHLP® Automotive Inductors, High Temperature (155 °C) Series



LINKS TO ADDITIONAL RESOURCES



APPLICATIONS

- Engine and transmission control units
- Diesel injection drivers
- DC/DC converters for entertainment / navigation systems
- Noise suppression for motors: windshield wipers / power seats / power mirrors / heating and ventilation blower / HID lighting
- LED drivers

FEATURES

- 11.5 mm x 10.3 mm x 5.4 mm size
- High temperature, up to 155 °C
- Shielded construction
- Handles high transient current spikes without saturation
- Polarity marking available for EMI sensitive applications (see "EP" package code below for more information)
- Ultra low buzz noise, due to composite construction
- AEC-Q200 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS
COMPLIANTHALOGEN
FREEGREEN
(5-2008)

STANDARD ELECTRICAL SPECIFICATIONS


PART NUMBER	L_0 INDUCTANCE $\pm 20\%$ AT 100 kHz, 0.25 V, 0 A (μ H)	DCR TYP. 25 °C (m Ω)	DCR MAX. 25 °C (m Ω)	HEAT RATING CURRENT DC TYP. (A) ⁽¹⁾	SATURATION CURRENT DC TYP. (A) ⁽²⁾	SRF TYP. (MHz)
IHLP4040EDE_R33M5A	0.33	1.05	1.12	36.00	20.80	70.00
IHLP4040EDE_R47M5A	0.47	1.30	1.39	35.50	20.30	65.00
IHLP4040EDE_R68M5A	0.68	2.00	2.14	27.00	19.10	48.73
IHLP4040EDE_1R0M5A	1.0	2.35	2.50	26.70	17.61	39.85
IHLP4040EDE_2R2M5A	2.2	4.59	4.91	18.40	17.58	25.01
IHLP4040EDE_3R3M5A	3.3	7.42	7.94	14.80	14.30	20.00
IHLP4040EDE_4R7M5A	4.7	11.00	11.77	11.50	11.90	16.45
IHLP4040EDE_8R2M5A	8.2	20.90	22.36	8.61	11.10	12.55
IHLP4040EDE_100M5A	10	26.00	27.82	7.45	6.37	12.01
IHLP4040EDE_150M5A	15	36.70	39.27	6.50	5.17	8.17
IHLP4040EDE_220M5A	22	46.00	49.22	5.53	4.99	7.23
IHLP4040EDE_330M5A	33	74.00	79.18	4.40	4.40	6.07
IHLP4040EDE_470M5A	47	119.50	127.87	3.60	3.60	4.60
IHLP4040EDE_750M5A	75	204.00	214.20	2.74	3.51	3.53

Notes

- All test data is referenced to 25 °C ambient
 - Operating temperature range -55 °C to +155 °C
 - The part temperature (ambient + temp. rise) should not exceed 155 °C under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application
 - Rated operating voltage (across inductor) = 75 V
- ⁽¹⁾ DC current (A) that will cause an approximate ΔT of 40 °C
⁽²⁾ DC current (A) that will cause L_0 to drop approximately 20 %



DIMENSIONS in inches [millimeters]



DESCRIPTION

IHLP-4040ED-5A	4.7 μ H	± 20 %	EK	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC® LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

I	H	L	P	4	0	4	0	E	D	E	K	4	R	7	M	5	A
PRODUCT FAMILY				SIZE				PACKAGE CODE		IMPEDANCE VALUE		INDUCTANCE TOLERANCE		SERIES			
								EK = tape and reel		4R7 = 4.7 μ H		M = ± 20 %					

PACKAGE CODE OPTIONS


- EK = tape and reel packaging (700 pcs on 13-inch reel)
- ER = tape and reel packaging (500 pcs on 13-inch reel)
- EP = tape and reel packaging (500 pcs on 13-inch reel), includes polarity part marking

Note

- For additional packaging details see ["Packaging Methods"](#)

MAGNETIC FIELD

CONFIGURATION OF THE "B" (FLUX) FIELD FOR THE IHLP WITH POLARITY MARKING



When a positive (+) voltage is placed on the terminal marked with the polarity dot and the opposite terminal is negative (-), the resulting current flow will create a magnetic south pole on the top side of the IHLP.


For the IHLP-4040ED-5A series, the polarity mark also indicates the "start" or "inside" lead of the winding.

Observing the polarity orientation when mounting the inductor will ensure the most consistent EMI reduction performance.

Drawing is for illustrative purposes only. The flux leakage from the inductor is minimal.









PART MARKING / POCKET TAPE ORIENTATION

Part marking and tape orientation for IHLP with polarity marking











PERFORMANCE GRAPHS













PERFORMANCE GRAPHS











PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY





PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.