


ASSEMBLY CONNECTIVITY	
LC CONN.	LC CONN.
YELLOW (A)	WHITE (B)
WHITE (B)	YELLOW (A)

STANDARD LENGTHS ACCORDING TO CUSTOMER DRAWING 1206850	
PART NUMBER	"L" (meter)
X-2061529-Y	XY.0

- NOTES:
- 1 ATTENUATION ≤ 0.3 dB, MEASURED AT 850 nm
ACCORDING TO I.E.C. 61300-3-4 INSERTION METHOD B
 - 2 RETURN LOSS ≥ 20 dB, IN MATED CONDITION
AGAINST REFERENCE CONNECTOR AT 850 nm
 - 3 FILLED OUT TEST RESULT SHEET SUPPLIED WITH EACH INDIVIDUALLY PACKED ASSEMBLY
 - 4 CABLE INFORMATION:
 - CORE DIAMETER: 50/125 μm (2x)
 - OUTER JACKET DIAMETER: 1.8 x 3.6 mm
 - OUTER JACKET COLOUR: ORANGE
 - OUTER JACKET MATERIAL: LSZH
- 5 BLANK LABEL
- ONLY ONE LABEL IN THE MIDDLE OF THE CABLE IS USED FOR LENGTHS < 0.6 METER

2	BLANK LABEL				3
2	LC DUPLEX CONNECTOR, ULTRA SHORT, MULTI MODE, BEIGE				2
L	FOCAB 1.8MZ 50/125, ORANGE, LSZH				1
Qty	Description				Item
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. COOLEN 13APR2011	TE Connectivity		
		CHK R. GROENEVELD 01JUN2011			
		APVD A. HENGELMOLEN 01JUN2011			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
		0 PLC ± 1.0		FIBER OPTIC LEAD 1.8MZ LC/DPX - LC/DPX ULTRA SHORT MULTI MODE 50/125	
		1 PLC ± 0.5			
		2 PLC ± -			
		3 PLC ± -			
4 PLC ± -		PRODUCT SPEC			
		APPLICATION SPEC			
MATERIAL		FINISH		SIZE	RESTRICTED TO
-		-		A2 00779	-
		WEIGHT -		DRAWING NO	
				C-2061529	
		CUSTOMER DRAWING		SCALE	SHEET
				NTS	1 of 1
				REV B	