

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION ,19 .

© COPYRIGHT 19

BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC

G

DIST

14

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	REV PER 063A-0541-00	25SEP00	JR	TM

1

WIRE INSULATION DIA IS 3.18-3.50
[.125-.138]

RING "A"
COLOR: NONE

RING "B"
COLOR: NONE

SLEEVE

2.67
[.105]

7.21
[.284]

3.56
[.140]
REF 2 PLC

13.34
[.525] MAX

TEFLON	ASTM D-1710	SLEEVE
COPPER PER ASTM B152 / NICKEL PL PER QQ-N-290		RING "B"
COPPER PER ASTM B152 / NICKEL PL PER QQ-N-290		RING "A"
MATERIAL / FINISH		DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
MM [INCHES]

MATERIAL
SEE TABLE

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±-

2 PLC ±0.40 [.015]

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH
SEE TABLE

DWN
JR RUTH
31MAY00

CHK
R HERSEY
31MAY00

APVD
T MICHIELUTTI
31MAY00

AMP

AMP Incorporated
Harrisburg, PA 17105-3608

NAME

PRE-INSULATED SPARE WIRE CAP

SIZE
A3

CAGE CODE
00779

DRAWING NO
C- 328861

RESTRICTED TO
-

CUSTOMER DRAWING

SCALE
10:1

SHEET
1 OF 1

REV
E

AMP 1470-19 REV 11JUN97

25-SEP-00 13:56:29 amp13469 /home/amp13469/ednmod