





REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	C	REVISED PER ECO-18-018129	04OCT2019	AP	DS



- △ REFERENCE APPLICATION SPEC 114-13059 FOR RECOMMENDED PLATED THRU HOLE DIAMETER AND PLATING THICKNESSES.
- △ MATERIAL:
CONTACT AND SHIELD - PHOSPHOR BRONZE
HOUSING - GLASS FILLED POLYESTER, UL 94V-0.
- △ FINISH: SIGNAL AND GROUND CONTACTS:
MATING AREA: MEETS THE PERFORMANCE REQUIREMENTS OF PRODUCT SPECIFICATION 108-2055; BASED ON TELCORDIA GR-1217-CORE, APPLICATIONS IN UNCONTROLLED ENVIRONMENTS
COMPLIANT PIN AREA: 0.5 μm MIN MATTE TIN OVER BASE PLATING
- △ CONNECTOR MARKED WITH PART NUMBER AND DATE CODE.
- △ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- △ THE FOUR GROUNDS IN EACH COLUMN ARE COMMONED.
7. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE: GR-1217-CORE, ISSUE 1, NOVEMBER 1995.
- △ REFER TO "CONTACT LAYOUT" CHART FOR SEQUENCING.
- △ DIMENSION APPLIES TO FIRST AND LAST CIRCUITS.
- △ TE OR TE CONNECTIVITY LOGO IS LOCATED.

CONTACT LAYOUT										
A = 3.80mm (DIM M) B = 5.30mm (DIM M) G = GROUND										
ROWS	COLUMNS									
	10	9	8	7	6	5	4	3	2	1
	A	B	B	B	B	B	B	B	B	B
	B	B	B	B	B	B	B	B	B	B
	BG	G	G	G	G	G	G	G	G	G
	C	A	B	B	B	B	B	B	B	B
	D	A	B	B	B	B	B	B	B	B
	DG	G	G	G	G	G	G	G	G	G
	E	B	B	B	B	B	B	B	B	B
	F	B	B	B	B	B	B	B	B	B
	FG	G	G	G	G	G	G	G	G	G
	G	B	B	B	B	B	B	B	B	B
	H	B	B	B	B	B	B	B	B	B
	HG	G	G	G	G	G	G	G	G	G

⊕ Ø0.05Ⓢ X Y
ALL PLATED THRU HOLES

RECOMMENDED PC BOARD LAYOUT, BACKPLANE, COMPONENT SIDE SHOWN
SCALE 4:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S.J.MAGARO 25JUL2004 CHK R.A.PATTERSON 25JUL2004 APVD R.PATTERSON 16AUG2007	NAME HEADER ASSEMBLY, 4 PAIR, SELECTIVELY LOADED, 2.5mm TAIL, 25mm HMZd	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ± FINISH	PRODUCT SPEC APPLICATION SPEC	SIZE CAGE CODE DRAWING NO A100779C=6469292	RESTRICTED TO
MATERIAL	WEIGHT	CUSTOMER DRAWING	SCALE 8:1	SHEET 1 OF 1 REV C