

S8XXXB

Base Station Omni Antennas 800 MHz/900 MHz

Omnidirectional antennas are the right choice for situations where you need to be in contact with sources that are in two directions or if you do not know what direction the signals are coming from. Standard data transmission omnis are fully decoupled antennas built on a copper laminate and housed in 0.100-inch wall fiberglass housings. They may be mounted right side up or tipped upside down depending upon the desired pattern. They also feature a very versatile clamp mounting system that fits most every situation you may encounter.

FEATURES AND BENEFITS

- Fiberglass enclosures
- Broadband performance
- Plated copper laminated radiator
- DC grounded
- Weatherproof designs with
- Omnidirectional UltraLink pigtail
- RoHS-compliant


APPLICATIONS

- M2M/IoT
- Two-way dispatch
- LoRa


MODEL	FREQUENCY	VSWR (NOMINAL)	GAIN (dBi)	BANDWIDTH	-3DB BEAM WIDTHE-PLANE	TYPE (FEMALE)	HEIGHT cm (in)	WEIGHT kg (lb)	W/SUR AREA	W/SURVIVAL	PIGTAIL
S8964B	896-960	1.5:1	6	64	25°	N	107 (42	0.70 (1.56)	0.02 (0.22)	200 (125)	23
S8963B	896-960	1.5:1	5	64	45°	N	78 (30¾)	0.53 (1.19)	0.016 (0.176)	200 (125)	23
S8960B	896-960	1.5:1	2	64	75°	N	44.5 (17½)	0.25 (0.56)	0.009 (0.083)	200 (125)	17
S8060B	806-868	1.5:1	2	62	75°	N	44.5 (17½)	0.25 (0.56)	0.009 (0.083)	200 (125)	17

COMMON SPECIFICATIONS	
Power Handling (Watts)	5
Element Material	Plated copper laminate
Enclosure Material	Fiberglass
Mounting Style	Tube end
Maximum Mast Diameter – cm (in.)	5.1 (2.0)


RADIATION PATTERNS



S8060B



S8063B



S8064B

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies.
Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, complete, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information. Antenna performance may vary. TE is a component manufacturer, and customer and/or end-user is responsible for all end-use compliance and regulatory requirements.

©2025 TE Connectivity. All Rights Reserved.

05/25 Original