


LOC	DIST	REVISIONS				
AD	00	P	LTR	DESCRIPTION	DATE	APVD
			B1	REVISED PER ECO-11-004587	11MAR11	RK HMR



1 . LOOSE PIECE TERMINAL MUST MEET ALL APPLICABLE STRIP SPECIFICATIONS IN ADDITION TO THOSE SHOWN.

2 .000030 MIN. GOLD OVER .000050-.000100 NICKEL.


3 GOLD FLASH OVER .000050-.000100 NICKEL
.000030 GOLD ON CONTACT AREA.

4 PREPLATING: .000078-.000158 BRIGHT TIN (HALT)
PER 112-20-6


5 .000050 GOLD OVER .000050-.000100 NICKEL.

6 GOLD FLASH OVER .000050-.000100 NICKEL
.000015 GOLD ON CONTACT AREA.

7 GOLD FLASH ON AREA "L"
.000050 GOLD ON CONTACT AREA.
ALL OVER .000050-.000100 NICKEL ENTIRE CONTACT.



OBSOLETE	7	1-87666-6	87667-6
	6	87666-5	87667-5
	5	87666-4	87667-4
	4	87666-3	87667-3
	3	87666-2	87667-2
	2	87666-1	87667-1
FINISH	MAKE FROM STRIP PART NO.		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER	27JUN06	 TE Connectivity					
		CHK D.ROHDE	27JUN06						
DIMENSIONS: INCHES		APVD D.ROHDE	27JUN06	NAME CONTACT,FEMALE,MOD IV, CRIMP SNAP-IN (LOOSE PIECE)					
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± .02 3 PLC ± .005 4 PLC ± .0005 ANGLES ± 0°30'	PRODUCT SPEC —							
		APPLICATION SPEC —							
MATERIAL SEE TABLE		FINISH SEE TABLE		WEIGHT —	SIZE A3	CAGE CODE 00779	DRAWING NO C-87667	RESTRICTED TO —	
CUSTOMER DRAWING					SCALE 8:1	SHEET 1 OF 1	REV B1		