REVISIONS					
REV.	ECR#	ZONE	DESCRIPTION	CHANGED BY/DATE	APPROVED BY/DATE
AA			INITIAL RELEASE	TB 03-30-09	TB 03-30-09
AB	CRN ECR#850		ADDED TO TABLE, TORQUE, 50 CYCLES, OPER & STORAGE TEMP., AND CONNECTOR BODY WITH ITS CENTER CONTACT. 4-2-13 CONNECTOR BODY from Nickleplate to black chrome.	MCL 3/27/2013	K.S. 3/27/2013



PARAMETER	PERFORMANCE
Model Number	RD2458-5-RSMA
Antenna Type	Dipole
Frequency	2.40-2.50GHz/4.9-5.85GHz
Input Impedance	50 Ohms
VSWR	2.0:1
RF Connector	RSMA
Radome	Black, TPEE
Fastening Torque	0.5 ~ 0.8N*m
Product Cycles	50 (MIN)
Operational Temperature (C)	-30° to +70°
Storage Temperature (C)	-40° to +85°
Connector Body	Black Chrome
Connector Center Contact	Gold Plating

MATERIAL: N/A		
FINISH: N/A		
APPROVALS		DATE
DRAWN BY	T.BOWSER	03-30-09
PROJ. ENG.	T. PETROPOULOS	12/15/09
APPL. MECH.	R. CHICOINE	12/15/09
MFG.	I. CHICKLIS	12/15/09

THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING

INTERPRET DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5M-1994

TOLERANCES UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN MILLIMETERS

ANGLE:	±30'
0 PLACE DECIMAL:	±0.5
1 PLACE DECIMAL:	±0.25
2 PLACE DECIMAL:	±0.13

SURFACE ROUGHNESS 1.6

TE connectivity

RD2458-5-RSMA

SIZE	DWG. NO.	REV
A3	RD2458-5-RSMAMO	AB

SCALE: 1:1 | PREVIOUS# | SHEET 1 OF 1

THIS DRAWING IS UNPUBLISHED. | RELEASED FOR PUBLICATION – , – .

© Copyright 2022 TE Connectivity Ltd. ALL RIGHTS RESERVED.