

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
G	50		C	ECR-13-000998	11FEB2013	PK	HS

CRIMP LOCATION MARKS

SIGHT HOLE 3

33.5
[1.32]
MAX DIA

38.4
[1.51]
MIN TYP

500HD
1323/24

- 1 CIRCULAR MIL RANGE: 450-550 MCM
- 2 USE CRIMP DIES 46756-2 (600 MCM)

3 .045 MAX BURR ALLOWED INSIDE THE WIRE BARREL ID IN AREA OF SIGHT HOLE.


15° TYP

3 26.2
[1.03]
MIN DIA

3.43±0.08
[.135 ±.003]


84.1
[3.31]
MAX

WIRE STOPS



696058-1

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN JR RUTH 28DEC98	 TE Connectivity				
		CHK M BRENNEMAN 28DEC98					
		APVD JL MECKLEY 28DEC98					
		NAME					
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-30200-3	SPLICE, BUTT, HEAVY DUTY, AMPOWER, WIRE SIZE: 500 MCM				
	0 PLC ± -	APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
	1 PLC ± -	—	A3	HS	C=696058	—	
MATERIAL COPPER	FINISH TIN PLATE	WEIGHT 242 grams	CUSTOMER DRAWING		SCALE 1:1	SHEET 1 OF 1	REV C