Circular Connectors Conforming to JIS C 5432

JR Series



■Features

1. These round connectors conform to JIS C 5432 "Circular connectors for electric appliances."

■Product Specifications

		Shell size	Number of contacts	Rated current
Ratings	Rated current	13	3	10A
			5	5A
		16	7	10A
			10, 14	5A
		21	10	10A
			16	5A (Crimp type : 3A)
			26	5A (Contact numbers A and B only : 10A)
		25	4	30A
			5, 16	10A
			24	5A (Crimp type : 3A)

		Shell size	Number of contacts	Rated voltage
Ratings	Rated voltage	13	3, 5	AC250, DC350V
		16	7, 10, 14	
		21	10, 16, 26	
		25	4, 5 16, 24	AC1000V, DC1400V AC250, DC350V

Ratings	Operating temperature range	-25 to +85℃
	Storage temperature range	-10 to +60℃

Items	Specifications	Conditions
1. Contac resistance	5mΩ max. JR 21-16 contact crimping type : 10mΩ max. JR 25-24 contact crimping type : 10mΩ max.	Measured at DC 1A
2. Insulation resistance	1,000MΩ min. JR 25-4 and 5 contacts : 10,000MΩ min.	Measured at DC 500V
3. Withstanding voltage	No flashover or dielectric breakdown.	AC 1,000V for 1 minute JR 25-4, 5 contacts : AC 3,000V for 1 minute
4. Vibration resistance	No electrical discontinuity for 10μs or greater	10 to 55Hz/cycle, amplitude : 0.75mm, 3 directions, 2 hours each
5. Shock resistance	No electrical discontinuity for 10μs or greater	Acceleration : 490m/s^2, duration : 11ms, 6 axis directions, 3 cycles each
6. Mating cycles	Contact resistance : 10mΩ max.	500 times
7. Temperature cycle	Insulation resistance : 1,000MΩ min. JR 25-4 and 5 contacts : Insulation resistance : 10,000MΩ min.	-40℃ : 30 minutes → Normal temperature : 10 to 15 minutes → 100℃ : 30 minutes → Normal temperature : 10 to 15 minutes, left for 5 cycles
8. Moisture resistance	Insulation resistance (when dry) 100MΩ min. 5,000MΩ min. : JR 25-4 , 5 contacts	Temperature : 40℃, relative humidity: 90 to 95%, left for 96 hours

■Materials / Finish

Part	Material	Finish	Remarks
Shell	Aluminum alloy	Nickel plating	————
Insulator	Phenol resin PPS resin	————	UL94V-0
Contact	Copper alloy	Silver plating	————

Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

■Product Number Structure

Refer to the chart below when determining the product specifications from the product number.
Please select from the product numbers listed in this catalog when placing orders.

JR 16 P A - 10 S C (**)
❶ ❷ ❸ ❹ ❺ ❻ ❼ ❽


❶Model name : JR Series	❺Number of contacts
❷Shell size : The shell size is the outer shell diameter of the mating end of the plug.	❻Contact form P : Male contact S : Female contact
❸Shell type P : Threaded lock plug　J : Threaded lock jack R : Threaded lock receptacle　BP : Bayonet-lock plug RC : Threaded lock receptacle cap　BR : Bayonet-lock receptacle	❼Contact termination method: None : Solder termination C : Crimp termination
❹Shell variation : Letters such as A, B, C, etc. indicate variations in the shell.	❽Other specifications : A two-digit number is added to indicate other specifications.

■Solder Type

●Threaded lock plug



JR25PH-4S




Part No.	HRS No.	No. of contacts	ϕA	B	ϕC	ϕD	E	JIS No.
JR13PK-3P(71)	114-0501-7 71	3	12.7	M18×1	21.8	8.5	45.5	CNR01SPM013003
JR13PK-5P(71)	114-0502-0 71	5						CNR01SPM013005
JR16PK-7P(71)	114-0503-2 71	7	16.3	M22×1	25.8	11.5	49.5	CNR01SPM016007
JR16PK-10P(71)	114-0504-5 71	10						CNR01SPM016010
JR21PK-10P(71)	114-0505-8 71		20.5	M26×1	29.8	15	53.5	CNR01SPM021010
JR21PK-16P(71)	114-0506-0 71	16						CNR01SPM021016
JR25PK-16P(71)	114-0507-3 71		24.7	M30×1	33.8	18	56.5	CNR01SPM025016
JR25PK-24P(71)	114-0508-6 71	24						CNR01SPM025024
JR25PH-4P	114-0626-2	4						————
JR25PH-5P	114-0624-7	5						————
JR13PK-3S(71)	114-0509-9 71	3	12.7	M18×1	21.8	8.5	45.5	CNR01SPF013003
JR13PK-5S(71)	114-0510-8 71	5						CNR01SPF013005
JR16PK-7S(71)	114-0511-0 71	7	16.3	M22×1	25.8	11.5	49.5	CNR01SPF016007
JR16PK-10S(71)	114-0512-3 71	10						CNR01SPF016010
JR21PK-10S(71)	114-0513-6 71		20.5	M26×1	29.8	15	53.5	CNR01SPF021010
JR21PK-16S(71)	114-0514-9 71	16						CNR01SPF021016
JR25PK-16S(71)	114-0515-1 71		24.7	M30×1	33.8	18	56.5	CNR01SPF025016
JR25PK-24S(71)	114-0516-4 71	24						CNR01SPF025024
JR25PH-4S	114-0627-5	4						————

Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

●Threaded lock receptacle



JR25RH-4P




Part No.	HRS No.	No. of contacts	ϕA	B	C	D	E	JIS No.
JR13RK-3P	114-0517-7	3	15.9	M18×1	26.6	26	20	CNR01SRM013003
JR13RK-5P	114-0518-0	5			26.1			CNR01SRM013005
JR16RK-7P	114-0519-2	7	19.9	M22×1	26.6	29	23	CNR01SRM016007
JR16RK-10P	114-0520-1	10			26.1			CNR01SRM016010
JR21RK-10P	114-0521-4		23.9	M26×1	26.6	32	26	CNR01SRM021010
JR21RK-16P	114-0522-7	16			26.1			CNR01SRM021016
JR25RK-16P	114-0523-0		27.9	M30×1	26.6	35	29	CNR01SRM025016
JR25RK-24P	114-0524-2	24			26.1			CNR01SRM025024
JR25RH-4P	114-0628-8	4			28			————
JR13RK-3S	114-0525-5	3	15.9	M18×1		26	20	CNR01SRF013003
JR13RK-5S	114-0526-8	5			27			CNR01SRF013005
JR16RK-7S	114-0527-0	7	19.9	M22×1	28	29	23	CNR01SRF016007
JR16RK-10S	114-0528-3	10			27			CNR01SRF016010
JR21RK-10S	114-0529-6		23.9	M26×1	28	32	26	CNR01SRF021010
JR21RK-16S	114-0530-5	16			27			CNR01SRF021016
JR25RK-16S	114-0531-8		27.9	M30×1	28	35	29	CNR01SRF025016
JR25RK-24S	114-0532-0	24			27			CNR01SRF025024
JR25RH-4S	114-0629-0	4			28			————
JR25RH-5S	114-0625-0	5			27.8			————

●Threaded lock jack



JR25JK-24P



Part No.	HRS No.	No. of contacts	ϕA	B	C	ϕD
JR13JK-3P	114-0533-3	3	19	M18×1	44.5	8.5
JR13JK-5P	114-0534-6	5				
JR16JK-7P	114-0535-9	7	23	M22×1	48.5	11.5
JR16JK-10P	114-0536-1	10				
JR21JK-10P	114-0537-4		27	M26×1	52.5	15
JR21JK-16P	114-0538-7	16				
JR25JK-16P	114-0539-0		31	M30×1	55.5	18
JR25JK-24P	114-0540-9	24				
JR13JK-3S	114-0541-1	3	19	M18×1	44.5	8.5
JR13JK-5S	114-0542-4	5				
JR16JK-7S	114-0543-7	7	23	M22×1	48.5	11.5
JR16JK-10S	114-0544-0	10				
JR21JK-10S	114-0545-2		27	M26×1	52.5	15
JR21JK-16S	114-0546-5	16				
JR25JK-24S	114-0548-0	24	31	M30×1	55.5	18


Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

■Crimp Type

●Threaded lock plug



JR21PK-10PC(71)




Part No.	HRS No.	No. of contacts	φA	B	φC	φD	E	Remarks
JR21PK-10PC(71)	114-0570-0 71	10	20.5	M26×1	29.8	15	53.5	Contact φ1.6
JR21PK-10SC(71)	114-0571-2 71							
JR21PK-16PC(71)	114-0572-5 71	16						Contact φ1
JR21PK-16SC(71)	114-0573-8 71							
JR25PK-24PC(71)	114-0574-0 71	24	24.7	M30×1	33.8	18	56.5	
JR25PK-24SC(71)	114-0575-3 71							

●Threaded lock receptacle



JR21RK-10SC




Part No.	HRS No.	No. of contacts	φA	B	C	D	E	Remarks
JR21RK-10SC	114-0577-9	10	23.9	M26×1	27.6	32	26	Contact φ1.6
JR21RK-16PC	114-0578-1	16			25.4			Contact φ1
JR21RK-16SC	114-0579-4				23			
JR25RK-24SC	114-0581-6	24	27.9	M30×1		35	29	

●Threaded lock receptacle cap



JRC25RC(71)



Part No.	HRS No.	A	φB	C	JIS No.
JRC13RC(71)	114-0053-8 71	M18×1	21	10	CNR01RC013
JRC16RC(71)	114-0054-0 71	M22×1	25		CNR01RC016
JRC21RC(71)	114-0055-3 71	M26×1	29		CNR01RC021
JRC25RC(71)	114-0056-6 71	M30×1	33		CNR01RC025


Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

■Solder Type

●Bayonet - lock plug



JRC16BP-14P(71)




Part No.	HRS No.	No. of contacts	φA	φB	C	φD	Remarks
JRC16BP-14P(71)	114-0251-1 71	14	16.3	27	91	11.2	
JRC21BPA-26P(31)	114-0268-4 31	26	20.5	31	98	12.2	
JRC16BP-14S(71)	114-0254-0 71	14	16.3	27	91	11.2	
JRC21BP-26S(31)	114-0267-1 31	26	20.5	31	98	12.2	

●Bayonet - lock receptacle



JRC16BR-14S(71)




Part No.	HRS No.	No. of contacts	φA	φB	C	D	E	Remarks
JRC16BR-14P(71)	114-0257-8 71	14	20.5	19.9	26.6	29	23	
JRC21BR-26P(71)	114-0269-7 71	26	25.8	23.9	26.8	32	26	
JRC16BR-14S(71)	114-0260-2 71	14	20.5	19.9	25.8	29	23	
JRC21BRA-26S	114-0270-6	26	25.8	23.9	28	32	26	

Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

Crimp Contacts


Contact diameter ϕ1.0mm

Male contact



Type	Part No.	HRS No.	B	C	Applicable wire
Loose contact	JRC-PC2-112	114-0243-3	1.6	2.0	20 to 24 AWG
	JRC-PC2-122	114-0244-6	1.45	1.5	24 to 28 AWG
Reel contact	JRC-PC2-212	114-0245-9	1.6	2.0	20 to 24 AWG
	JRC-PC2-222	114-0246-1	1.45	1.5	24 to 28 AWG

Female contact




Type	Part No.	HRS No.	B	C	Applicable wire
Loose contact	JRC-SC2-112	114-0247-4	1.6	2.0	20 to 24 AWG
	JRC-SC2-122	114-0248-7	1.45	1.5	24 to 28 AWG
Reel contact	JRC-SC2-212	114-0249-0	1.6	2.0	20 to 24 AWG
	JRC-SC2-222	114-0250-9	1.45	1.5	24 to 28 AWG

Note : Loose contact in pack of 100 pcs. Reel contact contains 8,000 pcs.


Contact diameter ϕ1.6mm

Male contact



Type	Part No.	HRS No.	B	C	Applicable wire
Loose contact	JRC-PC-112	114-0239-6	2.3	2.9	16 to 20 AWG
Reel contact	JRC-PC-212	114-0240-5			

Female contact



Type	Part No.	HRS No.	B	C	Applicable wire
Loose contact	JRC-SC-112	114-0241-8	2.3	2.9	16 to 20 AWG
Reel contact	JRC-SC-212	114-0242-0			

Note : Loose contact in pack of 100 pcs. Reel contact contains 5,000 pcs.

Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

Applicable Tools

Contact dia.	Type	Item	Part No.	HRS No.	Applicable terminal	Applicable wire
φ1	Manual	Manual crimping tool	HT802/RM-11	150-0401-6	JRC-PC2-112 JRC-SC2-112	20 to 24 AWG
			HT802/RM-12	150-0402-9	JRC-PC2-122 JRC-SC2-122	24 to 28 AWG
	Automatic	Automatic crimping press	CM-105C	901-0001-0	————	————
		Applicator	AP105-JRC2-1	901-2037-1	JRC-PC2-212 JRC-SC2-212	20 to 24 AWG
			AP105-JRC2-2	901-2038-4	JRC-PC2-222 JRC-SC2-222	24 to 28 AWG
	Extraction tool		RM-TP	150-0008-7	————	————
φ1.6	Manual	Manual crimping tool	JRC-TC-11	150-0033-4	JRC-PC-112 JRC-SC-112	16 AWG
			JRC-TC-12	150-0034-7	JRC-PC-112 JRC-SC-112	18 to 20 AWG
	Automatic	Automatic crimping press	CM-105C	901-0001-0	————	————
		Applicator	AP105-JRC-1	901-2039-7	JRC-PC-212 JRC-SC-212	16 to 20 AWG
	Extraction tool		JRC-TP	150-0035-0	————	————

Hand Tool Crimp



(For Contact Diameter φ1.0mm)



(For Contact Diameter φ1.6mm)

Extraction Tool



(For Contact Diameter φ1.0mm)



(For Contact Diameter φ1.6mm)



Automatic Crimping Machine CM-105C

Precautions

1. This product series uses silver plated contacts. Silver reacts easily to exposure to sulfur gas so the below conditions may cause tarnishing.
   - Dusty environments
   - Area with a high concentration area of gases such as sulfur dioxide gas, hydrogen sulfide gas, nitrogen dioxide gas and so on.
     Example; In close proximity to factory exhaust, automotive emissions, etc.
   - Close to heaters, or in other areas marked by extreme temperature differences or high humidity.
   - Close to rubber products includes rubber adhesives.

   The Electrical connection is not affected by tarnishing on a silver surface due to the wiping effect of the contact pins.

2. Storage
   Packing state; Packed in original packing or equivalent container
   Temperature -10 to +60℃
   Humidity 85% Max
   (It is recommended that the product be stored in an area of normal level of temperature and humidity, and free of any temperature fluctuation)




   Please use this products within 6 months of delivery.
   (After 6 month, please check the solderbility before use)
   "Storage" means long-term storage of the unused products in sealed packaging, prior to assembly to PCB.




3. Ask a Hirose sales personnel to provide Cable Assembly Procedure (ETAD-C0473-00)





Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

Contact Position Arrangement

Shell size				
13				
No. of contacts	3	5		
Withstanding voltage	AC1000V a minute			
Current rating	10A	5A		
Insulation resistance	1000MΩ MIN.			
Contact resistance	5mΩ MAX.			
Solderpot inner diameter	1.7mm dia.	1.1mm dia.		

Shell size			
16			
No. of contacts	7	10	14
Withstanding voltage	AC1000V a minute		
Current rating	10A	5A	
Insulation resistance	1000MΩ MIN.		
Contact resistance	5mΩ MAX.		
Solderpot inner diameter	1.7mm dia.		1.1mm dia.

Shell size				
21				
No. of contacts	10	16	26	
Withstanding voltage	AC1000V a minute			
Current rating	10A	5A (crimp type 3A)	5A	10A (only A, B)
Insulation resistance	1000MΩ MIN.			
Contact resistance	5mΩ MAX.	5mΩ MAX. (crimp type 10mΩ)	5mΩ MAX.	
Solderpot inner diameter	1.7mm dia.	1.1mm dia.		1.7mm dia. (only A, B)

Shell size				
25				
No. of contacts	4	5	16	24
Withstanding voltage	AC3000V a minute		AC1000V a minute	
Current rating	30A	10A		5A (crimp type 3A)
Insulation resistance	10,000MΩ MIN.		1000MΩ MIN.	
Contact resistance	5mΩ MAX.			5mΩ MAX. (crimp type 10mΩ)
Solderpot inner diameter	3.4mm dia.	1.7mm dia.		1.1mm dia.

Remarks : 1. Viewed from mating face.
2. The withstand voltage is the test value.

Feb.1.2025 Copyright2025 HIROSE ELECTRIC CO., LTD. All rights Reserved.

HIROSE ELECTRIC CO.,LTD.
2-6-3,Nakagawa Chuoh,Tsuzuki-Ku,Yokohama-Shi 224-8540,JAPAN
https://www.hirose.com/

The characteristics and the specifications contained herein are for reference purpose. Please refer to the latest customer drawings prior to use.
The contents of this catalog are current as of date of 10/2021. Contents are subject to change without notice for the purpose of improvements.