

HomeWIZ750SR-485



WIZ750SR-485

Qty: 1

ADD TO CART

✓ Add to Wishlist

✓ Add to Compare

Quick Overview

compact size Ethernet to RS-422/-485 converter based on W7500p. Fully compatible with WIZ107SR/WIZ108SR.

MY CART

You have no items in your shopping cart.

More Views



Details

Product Description

The WIZ750SR is the compact sized serial to Ethernet module using the WIZnet chip W7500P, based on a Cortex M0. The WIZ750SR is the protocol converter that transmits the data sent by serial equipment as TCP/IP data type and converts back the TCP/IP data received through the network into serial data. The WIZ750SR is the successor of the widely used WIZ107SR/WIZ108SR and incorporates the experience of several years of module development. It complies with industrial temperature standard and supports all relevant serial interface systems (TTL / RS-232 / RS-422/485). WIZ750SR contains an 4-pin GPIO expansion port that can be controlled freely by the user. (analog input or digital in/out)

This module is the RS-422/RS-485 version.

Features

- › Hardwired TCP/IP Ethernet functionality
- › Serial to Ethernet module based on the W7500p chip
- › RJ45 mounted on the PCB already, pin header type module
- › RS-422/485 signals: TXD+, TXD-, RXD+, RXD-
- › configurable by AT command set and configuration tool
- › module settings can be secured with a password
- › 10/100 Mbps Ethernet speed, 230 kbps max serial connection speed
- › 8 Independent hardware socket
- › Internal 32 kBytes memory for TCP/IP packet processing

Related Links

[WIZ750SR product page in the wizwiki.net wiki](#)

[W7500 product page in the wizwiki.net wiki](#)

[More references for WIZ750SR in the WIZnetMuseum](#)



Additional Information

Dimension	48 x 30 x 18 mm
Ethernet I/F	PHY
Operating Temperature	0 °C to +70 °C
Operating Voltage	3.3 V

Functions	4-in-1, MCU+TCP/IP+MAC+PHY
Auto Negotiation	Yes
Package	stand alone PCB
pin count	2 x 6, 1 x 2, 1 x 12 and 1 x 5
auto MDIX	Yes
Wake on Lan	Yes
Power Down Mode	Yes
typ. Power Consumption	110 mA
MCU core	ARM Cortex-M0
MCU I/F	I2C, SPI, UART
PHY chip	internal
Related Chip/Module	W7500P
Connector Type	header pins
Serial I/F	RS422 / RS485
serial connector count	1
Ethernet connector	RJ45
pin pitch	2.54 mm and 1.27 mm
voltage regulator (LDO)	No
MAC address inside	Yes
PoE possible	No
Ethernet Speed	10/100
UART (max speed)	230k
Manufacturer	WIZnet

Product Tags

Add Your Tags:

ADD TAGS

Use spaces to separate tags. Use single quotes (') for phrases.

Company Information/Informationen

Impressum/Imprint
AGB
Widerrufsbelehrung/-formular
Datenschutzerklärung/Privacy Policy

Customer Service

Kontaktformular/Contact Us
Sitemap
Useful Tips and Information
WIZwiki.net - WIZnet Wiki
WIZnet Github

Zahlung & Versand / Payment & Shipping













