
1N4938UR-1

FEATURES

- **1N4938UR-1 AVAILABLE IN JAN, JANTX, AND JANTXV PER MIL-PRF-19500/169**
- **SWITCHING DIODE**
- **METALLURGICALLY BONDED**
- **HERMETICALLY SEALED**
- **DOUBLE PLUG CONSTRUCTION**
- **ALSO AVAILABLE AS LL4938. & MLL4938**



MAXIMUM RATINGS AT 25 °C

Operating Temperature:	-65°C to +175°C
Storage Temperature:	-65°C to +175°C
Surge Current A, sine, 1uS:	2.0A
Surge Current B, sine, 1S:	0.5A
Total Power Dissipation:	500mW
Operating Current:	100mA, T_A= +25°C
Derating Factor:	0.667mA/°C above T_A= +25°C
D.C. Reverse Voltage (VRWM):	175V

DC ELECTRICAL CHARACTERISTICS

V_F				I_R				V_{BR}			
Ambient (°C)	I_F mA	Min V	Max V	Ambient (°C)	V (dc)	Min µA	Max µA	Ambient (°C)	I_R µA	Min V	Max V
25	100	-	1.0	25	175	-	0.1	25	100	200	-
-55	100	-	1.2	150	175	-	100				

DESIGN DATA

Case: Hermetically sealed glass package per MIL-PRF-19500/169 DO-213AA outline

Lead Material: Copper clad steel

Lead Finish: Tin/Lead

Thermal Resistance ($R_{\theta JEC}$): 50°C/W maximum

Thermal Impedance ($Z_{\theta JX}$): 70°C/W maximum

Polarity: Cathode end is banded.

AC ELECTRICAL CHARACTERISTICS AT 25°C

	Symbol	Min	Max
Capacitance @ 0V	**pF**	-	5
T_{RR} @ I_F=I_R=30mA, I_{Rec} = 3mA.	**nsec**	-	50

WWW.MICROSEMI.COM

IRELAND - GORT ROAD, ENNIS, CO. CLARE
PHONE: **+353 65 6840044**
TOLL FREE: **+186 62 702434**
FAX: **+353 65 6822298**

U.S.A. DOMESTIC SALES CONTACT
PHONE: **(617) 926 0404**
TOLL FREE: **1 800 666 2999**