TABLE 1	
DASH NO	DESCRIPTION
-1	NO CHAIN
-2	2.5 BRASS CHAIN
-3	2.5 NYLON CHAIN
-4	3.0 BRASS CHAIN
-5	3.0 NYLON CHAIN
-6	6.0 BRASS CHAIN
-7	6.0 NYLON CHAIN
-8	4.0 BRASS CHAIN
-9	4.0 NYLON CHAIN
-10	10.0 BRASS CHAIN
-11	10.0 NYLON CHAIN
-12	2.5 SST ROPE
-13	3.0 SST ROPE
-14	6.0 SST ROPE
-15	4.0 SST ROPE
-16	7.0 SST ROPE
-17	4.5 SST ROPE
-18	12.0 SST ROPE
-19	18.0 SST ROPE


TABLE 2				
DASH NO	ØA	ØB	C DIM	D DIM
-D2	.630	.750	1.066	.450
-D3	.505	.625	.941	.388
-D4	.439	.562	.878	.355
-D5	.380	.500	.816	.325
-D6	.317	.437	.753	.295
-D7	.281	.406	.722	.278
-D8	.610	.750	1.066	.450
-D9	.567	.687	1.003	.419
-D10	.192	.312	.628	.231
-DD8	.330	.450	.766	.300


DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND SHALL NOT BE DISCLOSED, COPIED OR USED FOR PROCUMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION.

REVISIONS			
REV	DESCRIPTIONS	DATE	APPROVED
U	REVISED PER ECO # 16769	10/14/08	[illegible]

TABLE 3				
KEYING LETTER	E DEGREES	F DEGREES	G DEGREES	COLOR BAND
NONE	120°	120°	120°	NONE
T	100°	150°	110°	RED
U	120°	130°	110°	ORANGE
V	115°	130°	115°	YELLOW
W	125°	110°	125°	GREEN
X	130°	100°	130°	BLUE
Y	110°	140°	110°	VIOLET
Z	100°	160°	100°	GRAY
S	135°	135°	90°	WHITE


TABLE 4	
MODEL NUMBER	
RF175	3-LUG
RF175FL	4-LUG






-1 SHOWN

NO CHAIN/ROPE OR MOUNTING LUG




-2 THRU -11 SHOWN

STANDARD CHAIN AND MOUNTING LUG




-12 THRU -19 SHOWN

STAINLESS STEEL ROPE AND MOUNTING LUG



-2-D2 THRU -11-DD8 SHOWN

STANDARD CHAIN AND BULKHEAD JACK MOUNTING LUG



-12-D2 THRU -19-DD8 SHOWN

STAINLESS STEEL ROPE AND BULKHEAD JACK MOUNTING LUG

3. EXAMPLE OF COMPLETE MODEL NUMBER:

RF175 T -3 -D3

- RF175: MODEL NO (SEE TABLE 4)
- T: POLORIZATION LETTER NOT REQ'D FOR STD POLORIZATION (SEE TABLE 3)
- -3: CHAIN/ROPE MAT'L AND LENGTH (SEE TABLE 1)
- -D3: BULKHEAD JACK MOUNTING LUG (OPTIONAL) ONLY AVAILABLE WITH BRASS OR NYLON CHAIN (SEE TABLE 2)

2. FINISH: TFS-1A (NICKEL)

1. 3 AND 4 LUG BNC/TRB DUST CAP WITH CHAIN/ROPE OR MOUNTING LUG OPTIONS

NOTES: UNLESS OTHERWISE SPECIFIED.

4 NOTE THAT LENGTH FOR SST ROPE WITH MOUNTING LUG OPTION IS NOT MEASURED TO CENTER OF BULKHEAD MOUNTING LUG

UNCONTROLLED COPY

RED INDICATES ORIGINAL

INTERPRET DRAWING PER MIL-STD-100. DIMENSIONS ARE IN INCHES AND INCLUDE FINISH THICKNESS UNLESS OTHERWISE SPECIFIED.

TOL: UNLESS SPECIFIED. .XX ± .02 .XXX ± .010 ANGLE ± 1°

DRN J.CARPENTER 09-12-08
CHK M.T 10-17-08
QUALITY
MANUF
APPROVED DR 10-13-08
PROVE FILE NO. 305-0001
NEXT ASSY
MATERIAL:
FINISH:
DO NOT SCALE DWG

TROMPETER RF connectivity a cinch connectivity solutions brand

TITLE: RF175/RF175FL T/U/V/W/X/Y/Z/S

SIZE	CAGE CODE	DRAWING NO.	REV.
A	14949	305-0001	U

SCALE	DATE	SHEET
2/1	10-4-67	1C

Please read our datasheet & drawing disclaimer here.