

2018.07.25 16:28:41 +08'00'

APPROVED: _____


DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
-		RELEASED	4/13/05	
A		REDRAWN	07/17/13	
B		UPDATED DRAWING	7/25/18	HR/MY





RECOMMENDED PCB LAYOUT





DXXX	NO. OF CONTACTS	DIMENSIONS				
		A	B	C	D	E
DE09	9	1.213 [30.81]	.984 [24.99]	.666 [16.92]	.436 [11.08]	.756 [19.20]
DA15	15	1.543 [39.20]	1.311 [33.30]	.994 [25.25]	.763 [19.39]	1.091 [27.70]
DB25	25	2.088 [53.04]	1.852 [47.04]	1.534 [38.96]	1.309 [33.24]	1.618 [41.10]
DC37	37	2.732 [69.40]	2.500 [63.50]	2.182 [55.42]	1.963 [49.86]	2.256 [57.30]

SPECIFICATIONS:
Material:
Insulator: PBT, Thermoplastic, glass filled, rated UL 94V–0
Insulator color: Black
Contacts: Copper alloy
Shell: Steel, Tin plated
Boardlock: Brass, Tin plated
Plating:
Gold flash over Nickel underplate on contact area.
Electrical:
Voltage rating: 250 VAC/rms
Current rating: 3 Amp
Contact resistance: 20 mohms
Insulation resistance: 1,000 Mohms @ 500 VDC
Dielectric withstanding voltage: 1,000 VAC for 1 minute
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	4/13/05
CHECKED		
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: D-SUB PLUG, STANDARD PROFILE
RIVETED #4-40 STANDOFFS W/BOARDLOCKS

SIZE	PART NO.	REV.
X	DXXX-PT-1-BL	B

REF: S00087T | SCALE: NTS | SHEET 1 OF 1