

Automotive-grade N-channel 60 V, 32 mΩ typ., 30 A STripFET II Power MOSFET in a D²PAK and TO-220 packages





Features

Order codes	V_{DS}	$R_{DS(on)}$ max.	I_D
STB36NF06LT4	60 V	40 mΩ	30 A
STP36NF06L	60 V	40 mΩ	30 A

- AEC-Q101 qualified
- Exceptional dv/dt capability
- 100% avalanche tested
- Low gate charge

Applications

- Switching applications

Description

This Power MOSFET has been developed using STMicroelectronics' unique STripFET process, which is specifically designed to minimize input capacitance and gate charge. This renders the device suitable for use as primary switch in advanced high-efficiency isolated DC-DC converters for telecom and computer applications, and applications with low gate charge driving requirements.

Product status links
STB36NF06L
STP36NF06L

Product summary	
Order code	**STB36NF06LT4**
Marking	B36NF06
Package	D²PAK
Packing	Tape and reel
Order code	**STP36NF06L**
Marking	P36NF06L
Package	TO-220
Packing	Tube

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage (V_{GS} = 0 V)	60	V
V_{DGR}	Drain-gate voltage (R_{GS} = 20 kΩ)	60	V
V_{GS}	Gate-source voltage	±18	V
I_D	Drain current (continuous) at T_C = 25 °C	30	A
	Drain current (continuous) at T_C = 100 °C	21	
I_{DM}(1)	Drain current (pulsed)	120	A
P_{TOT}	Total power dissipation at T_C = 25 °C	70	W
	Derating factor	0.47	W/°C
dv/dt(2)	Peak diode recovery voltage slope	10	V/ns
E_{AS}(3)	Single-pulse avalanche energy	225	mJ
T_{stg}	Storage temperature range	-55 to 175	°C
T_J	Operating junction temperature range		°C

1. *Pulse width limited by safe operating area.*
2. *I_{SD} ≤ 30 A, di/dt ≤ 400 A/µs, V_{DD} ≤ $V_{(BR)DSS}$, T_J ≤ T_J max.*
3. *Starting T_J = 25 °C, I_D = 15 A, V_{DD} = 30 V.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	2.14	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	62.5	°C/W
T_l	Maximum lead temperature for soldering purpose	300	°C

2 Electrical characteristics

T_C = 25 °C unless otherwise specified.

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 250 µA	60			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 60 V			1	µA
		V_{GS} = 0 V, V_{DS} = 60 V, T_C = 125 °C			10	
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = ±18 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	1.0		2.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 15 A		32	40	mΩ
		V_{GS} = 5 V, I_D = 15 A		45	50	

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
g_{fs}	Forward transconductance	V_{DS} = 15 V, I_D = 15 A	-	15		S
C_{iss}	Input capacitance	V_{DS} = 25 V, f = 1 MHz, V_{GS} = 0 V	-	660		pF
C_{oss}	Output capacitance		-	170		pF
C_{rss}	Reverse transfer capacitance		-	70		pF
Q_g	Total gate charge	V_{DD} = 30 V, I_D = 30 A, V_{GS} = 5 V (see Figure 13. Test circuit for gate charge behavior)	-	13	17	nC
Q_{gs}	Gate-source charge		-	4.2		nC
Q_{gd}	Gate-drain charge		-	7.8		nC

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 30 V, I_D = 15 A, R_G = 4.7 Ω, V_{GS} = 5 V (see Figure 12. Test circuit for resistive load switching times and Figure 17. Switching time waveform)	-	10	-	ns
t_r	Rise time		-	80	-	ns
$t_{d(off)}$	Turn-off delay time		-	19	-	ns
t_f	Fall time		-	13	-	ns

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		30	A
I_{SDM}(1)	Source-drain current (pulsed)		-		120	A
V_{SD}(2)	Forward on voltage	I_{SD} = 24 A, V_{GS} = 0 V	-		1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 20 A, di/dt = 100 A/µs,	-	55		ns
Q_{rr}	Reverse recovery charge	V_{DD} = 20 V, T_J = 150 °C	-	107		nC
I_{RRM}	Reverse recovery current	(see Figure 14. Test circuit for inductive load switching and diode recovery times)	-	3.9		A

1. *Pulse width limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characteristics




Figure 4. Transfer characteristics




Figure 5. Trasconductance




Figure 6. Static drain-source on-resistance




Figure 7. Gate charge vs gate-source voltage




Figure 8. Capacitance variations




Figure 9. Normalized gate threshold voltage vs temperature




Figure 10. Normalized on-resistance vs temperature






Figure 11. Normalized $V_{(BR)DSS}$ vs temperature




3 Test circuits

Figure 12. Test circuit for resistive load switching times




AM01468v1

Figure 13. Test circuit for gate charge behavior




AM01469v1

Figure 14. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 15. Unclamped inductive load test circuit




AM01471v1

Figure 16. Unclamped inductive waveform



AM01472v1

Figure 17. Switching time waveform




AM01473v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 TO-220 type A package information

Figure 18. **TO-220 type A package outline**



0015988_typeA_Rev_23

Table 7. **TO-220 type A package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10

4.2 D²PAK (TO-263) type A package information

Figure 19. D²PAK (TO-263) type A package outline





Table 8. D²PAK (TO-263) type A package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
A1	0.03		0.23
b	0.70		0.93
b2	1.14		1.70
c	0.45		0.60
c2	1.23		1.36
D	8.95		9.35
D1	7.50	7.75	8.00
D2	1.10	1.30	1.50
E	10.00		10.40
E1	8.30	8.50	8.70
E2	6.85	7.05	7.25
e		2.54	
e1	4.88		5.28
H	15.00		15.85
J1	2.49		2.69
L	2.29		2.79
L1	1.27		1.40
L2	1.30		1.75
R		0.40	
V2	0°		8°

Figure 20. **D²PAK (TO-263) recommended footprint (dimensions are in mm)**



0079457_Rev26_footprint

4.3 D²PAK packing information

Figure 21. D²PAK tape outline





Figure 22. **D²PAK reel outline**



AM06038v1

Table 9. **D²PAK tape and reel mechanical data**

Tape			Reel		
Dim.	mm		Dim.	mm	
	Min.	Max.		Min.	Max.
A0	10.5	10.7	A		330
B0	15.7	15.9	B	1.5	
D	1.5	1.6	C	12.8	13.2
D1	1.59	1.61	D	20.2	
E	1.65	1.85	G	24.4	26.4
F	11.4	11.6	N	100	
K0	4.8	5.0	T		30.4
P0	3.9	4.1			
P1	11.9	12.1	Base quantity		1000
P2	1.9	2.1	Bulk quantity		1000
R	50				
T	0.25	0.35			
W	23.7	24.3			

Revision history

Table 10. **Document revision history**

Date	Version	Changes
14-Jun-2003	1	First release.
13-Mar-2006	2	Complete version.
26-Jun-2006	3	New template, no content change.
07-Oct-2022	4	Updated title, Internal schematic, Device summary, Features and Description on cover page. Updated Section 4 Package information. Minor text changes.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 5

3 **Test circuits** 7

4 **Package information** 8

4.1 TO-220 type A package information 8

4.2 D²PAK (TO-263) type A package information 10

4.3 D²PAK packing information 13

Revision history 15

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved