


Thyristor surge suppressor (TSS)



Product status link

[SMP100MC](#)

Features

- Bidirectional crowbar protection
- Voltage: range from 140 V to 400 V
- Low V_{BO} / V_R ratio
- Micro capacitance from 15 pF to 30 pF at 50 V
- Low leakage current: $I_R = 2 \mu A$ max
- Holding current: $I_H = 150$ mA min.
- Repetitive peak pulse current:
 - $I_{PP} = 100$ A (10/1000 μs)
- **Benefits:**
 - TSS (Thyristor surge suppressor) are not subject to ageing and provide a fail safe mode in short circuit for better protection
 - Helps equipment meet main standards such as UL60950, IEC 950 / CSA C22.2 and UL1459
 - Epoxy meets UL94, V0
 - Package is JEDEC registered (DO-214AA)
- **Complies with the following standards:**
 - IEC 61000-4-5
 - IEC 61000-4-2 level 4
 - GR-1089 Core
 - ITU-T-K20/K21
 - TIA/EIA IS-968
 - UL497B recognized, UL file E136224

Applications

These devices protect sensitive equipment from lightning strikes and AC power faults. They are designed for industrial and telecom applications because they comply with the most stringent standards. Their low capacitance makes them suitable for data line protection.

- Terminals (phone, fax, modem...) and central office equipment
- ADSL2+ and low end VDSL

Description

The SMP100MC series consists of micro-capacitance transient surge arresters designed to protect high data rate communication equipment. The micro-capacitance prevents signal distortion and is compatible with digital transmission line cards, such as ADSL, VDSL, and Ethernet.

1 Characteristics

Table 1. In compliance with the following standards

Standard	Peak surge voltage (V)	Waveform voltage	Required peak current (A)	Current waveform	Minimum serial resistor to meet standard (Ω)
GR-1089 Core First level	2500	2/10 μs	500	2/10 μs	0
	1000	10/1000 μs	100	10/1000 μs	0
GR-1089 Core Second level	5000	2/10 μs	500	2/10 μs	0
GR-1089 Core Intra-building	1500	2/10 μs	100	2/10 μs	0
ITU-T-K20/K21	6000	10/700 μs	150	5/310 μs	0
	1500		37.5		0
ITU-T-K20 (IEC61000-4-2)	8000	1/60 ns	ESD contact discharge		0
	15000		ESD air discharge		0
IEC61000-4-5	4000	10/700 μs	100	5/310 μs	0
	4000	1.2/50 μs	100	8/20 μs	0
TIA/EIA IS-968, lightning surge type A	1500	10/160 μs	200	10/160 μs	0
	800	10/560 μs	100	10/560 μs	0
TIA/EIA IS-968, lightning surge type B	1000	9/720 μs	25	5/320 μs	0

Table 2. Absolute ratings ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameter	Value	Unit
I_{PP}	Repetitive peak pulse current	10/1000 μs	100
		8/20 μs	300
		10/560 μs	140
		5/310 μs	150
		10/160 μs	200
		1/20 μs	300
		2/10 μs	500
I_{FS}	Fail-safe mode: maximum current ⁽¹⁾	8/20 μs	5
I_{FS}	Non repetitive surge peak on-state current (sinusoidal)	$t = 0.2\text{ s}$	18
		$t = 1\text{ s}$	9
		$t = 2\text{ s}$	7
		$t = 15\text{ mn}$	4
I^2t	I^2t value for fusing	$t = 16.6\text{ ms}$	20
		$t = 20\text{ ms}$	21
T_{stg}	Storage temperature range	-55 to +150	$^{\circ}\text{C}$
T_j	Operating junction temperature range	-40 to +150	$^{\circ}\text{C}$
T_L	Maximum lead temperature for soldering during 10 s	260	$^{\circ}\text{C}$

1. In fail safe mode the device acts as a short circuit.

Table 3. Thermal resistance parameter

Symbol	Parameter	Typ. value	Unit
$R_{th(j-a)}$	Junction to ambient (with recommended footprint)	100	$^{\circ}\text{C/W}$
$R_{th(j-l)}$	Junction to leads	20	



Figure 1. Electrical characteristics - parameter definitions


Figure 2. Pulse definition for electrical characteristics

Table 4. Electrical characteristics - parameter values ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Type	I_{RM} max at V_{RM}		I_R at V_R		Dynamic $V_{BO}^{(1)}$	Static V_{BO} at $I_{BO}^{(2)}$		$I_H^{(3)}$	$C^{(4)}$	$C^{(5)}$
	Max.		Max.		Max.	Max.	Max.	Min.	Typ.	Typ
	μA	V	μA	V	V	V	mA	mA	pF	pF
SMP100MC-140	2	126	5	140	180	175	800	150	30	60
SMP100MC-160		144		160	205	200			25	50
SMP100MC-200		180		200	255	250			20	45
SMP100MC-270		243		270	345	335			20	40
SMP100MC-400		360		400	540	530			15	30

1. See Figure 10.

2. See Figure 11.

3. See Figure 12.

 4. $V_R = 50\text{ V bias}$, $V_{RMS} = 1\text{ V}$, $F = 1\text{ MHz}$.

 5. $V_R = 2\text{ V bias}$, $V = 1\text{ V}$, $F = 1\text{ MHz}$.

1.1 Characteristics (curves)

Figure 3. Non repetitive surge peak on-state current versus overload duration




Figure 4. On-state voltage versus on-state current (typical values)




Figure 5. Relative variation of holding current versus junction temperature




Figure 6. Relative variation of breakover voltage versus junction temperature




Figure 7. Relative variation of leakage current versus reverse voltage applied (typical values)




Figure 8. Variation of thermal impedance junction to ambient versus pulse duration





Figure 9. Relative variation of junction capacitance versus reverse voltage applied (typical values)



2 Measurement setups

Figure 10. Test circuit 1 for Dynamic I_{BO} and V_{BO} parameters





Figure 11. Test circuit 2 for I_{BO} and V_{BO} parameters



TEST PROCEDURE


Pulse test duration ($t_p = 20$ ms):

- for Bidirectional devices = Switch K is closed
- for Unidirectional devices = Switch K is open

V_{OUT} selection:

- Device with $V_{BO} < 200$ V $\rightarrow V_{OUT} = 250$ V_{RMS}, $R1 = 140$ Ω
- Device with $V_{BO} \geq 200$ V $\rightarrow V_{OUT} = 480$ V_{RMS}, $R2 = 240$ Ω

Figure 12. Test circuit 3 for dynamic I_H parameter



This is a GO-NOGO test which allows to confirm the holding current (I_H) level in a functional test circuit.

TEST PROCEDURE

- 1/ Adjust the current level at the I_H value by short circuiting the AK of the D.U.T.
- 2/ Fire the D.U.T. with a surge current $\rightarrow I_{PP} = 10\text{ A}, 10/1000\text{ }\mu\text{s}$.
- 3/ The D.U.T. will come back off-state within 50 ms maximum.


3 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

3.1 SMB package information

- Epoxy meets UL94, V0
- Lead free plating + halogen-free molding resin

Figure 13. SMB package outline





0087334_1_18

Table 5. SMB package mechanical data

Ref.	Dimensions					
	Millimeters			Inches ⁽¹⁾		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A1	1.90		2.45	0.075		0.096
A2	0.05		0.20	0.002		0.008
b	1.95		2.20	0.077		0.087
c	0.15		0.40	0.006		0.016
D	3.30		3.95	0.130		0.156
E	5.10		5.60	0.201		0.220
E1	4.05		4.60	0.159		0.181
L	0.75		1.50	0.030		0.059

1. Inches only for reference

Figure 14. SMB footprint

Figure 15. Marking layout


Note: Marking layout can vary according to assembly location.

4 Ordering information

Figure 16. Ordering information scheme




Table 6. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
SMP100MC-140	ML14	SMB	98 mg	2500	Tape and reel
SMP100MC-160	ML16				
SMP100MC-200	ML20				
SMP100MC-270	ML27				
SMP100MC-400	ML40				

Revision history

Table 7. Document revision history

Date	Version	Changes
September-2003	0B	First issue.
14-Dec-2004	1	Absolute ratings values, <i>table 3</i> on page 2, updated.
11-May-2005	2	New types introduction.
20-Jun-2005	3	Telecom Circuit Protector added
05-Jan-2006	4	SMP100MC-320 / 360 / 400 in full production ("in development" mention removed)
09-Feb-2012	5	Added UL statement in Complies with the following standards.
11-Mar-2026	6	Updated Table 4 , Section 3.1: SMB package information , and Table 6 . Minor texte changes.

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2026 STMicroelectronics – All rights reserved