

N-channel 900 V, 4.7 Ω typ., 2.1 A SuperMESH Power MOSFET in a DPAK package



DPAK



AM01476v1_tab

Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STD2NK90ZT4	900 V	6.5 Ω	2.1 A

- 100% avalanche tested
- Gate charge minimized
- Very low intrinsic capacitance
- Zener-protected

Applications

- Switching applications

Description

This high-voltage device is a Zener-protected N-channel Power MOSFET developed using the SuperMESH technology by STMicroelectronics, an optimization of the well-established PowerMESH. In addition to a significant reduction in on-resistance, this device is designed to ensure a high level of dv/dt capability for the most demanding applications.

Product status link
STD2NK90ZT4

Product summary	
Order code	STD2NK90ZT4
Marking	D2NK90Z
Package	DPAK
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	900	V
V_{GS}	Gate-source voltage	±30	V
I_D	Drain current (continuous) at T_C = 25 °C	2.1	A
	Drain current (continuous) at T_C = 100 °C	1.3	
I_{DM}(1)	Drain current (pulsed)	8.4	A
P_{TOT}	Total power dissipation at T_C = 25 °C	70	W
ESD	Gate-source, human body model (R = 1.5 kΩ, C = 100 pF)	2	kV
dv/dt(2)	Peak diode recovery voltage slope	4.5	V/ns
T_{stg}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range		°C

1. *Pulse width limited by safe operating area.*
2. *I_{SD} ≤ 2.1 A, di/dt ≤ 200 A/µs, V_{DD} = 80%$V_{(BR)DSS}$.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	1.78	°C/W
R_{thJA}(1)	Thermal resistance, junction-to-ambient	50	°C/W

1. *When mounted on an 1-inch² FR-4, 2 Oz copper board.*

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not repetitive (pulse width is limited by T_J max.)	2.1	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	150	mJ

2 Electrical characteristics

T_C = 25 °C unless otherwise specified.

Table 4. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 1 mA	900			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 900 V			1	µA
		V_{GS} = 0 V, V_{DS} = 900 V, T_C = 125 °C (1)			50	
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = ±20 V			±10	µA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 50 µA	3	3.75	4.5	V
$R_{DS(on)}$	Static drain-source on resistance	V_{GS} = 10 V, I_D = 1.05 A		4.7	6.5	Ω

1. *Specified by design, not tested in production.*

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 25 V, f = 1 MHz, V_{GS} = 0 V	-	485		pF
C_{oss}	Output capacitance		-	50		pF
C_{rss}	Reverse transfer capacitance		-	10		pF
$C_{oss\ eq.}$ (1)	Equivalent output capacitance	V_{GS} = 0 V, V_{DS} = 0 V to 720 V	-	24		pF
Q_g	Total gate charge	V_{DD} = 720 V, I_D = 2 A, V_{GS} = 0 to 10 V (see Figure 14. Test circuit for gate charge behavior)	-	19.5	27	nC
Q_{gs}	Gate-source charge		-	3.4		nC
Q_{gd}	Gate-drain charge		-	10.8		nC

1. *$C_{oss\ eq.}$ is defined as a constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS}increases from 0 to 80% V_{DSS}.*

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 450 V, I_D = 1 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 13. Test circuit for resistive load switching times and Figure 18. Switching time waveform)	-	21	-	ns
t_r	Rise time		-	11	-	ns
$t_{d(off)}$	Turn-off delay time		-	43	-	ns
t_f	Fall time		-	40	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		2.1	A
I_{SDM} (1)	Source-drain current (pulsed)		-		8.4	A
V_{SD} (2)	Forward on voltage	I_{SD} = 2.1 A, V_{GS} = 0 V	-		1.6	V
t_{rr}	Reverse recovery time	I_{SD} = 2 A, di/dt = 100 A/µs, V_{DD} = 50 V (see Figure 15. Test circuit for inductive load switching and diode recovery times)	-	415		ns
Q_{rr}	Reverse recovery charge		-	1.5		µC
I_{RRM}	Reverse recovery current		-	7.2		A
t_{rr}	Reverse recovery time	I_{SD} = 2 A, di/dt = 100 A/µs V_{DD} = 50 V, T_J = 150 °C (see Figure 15. Test circuit for inductive load switching and diode recovery times)	-	515		ns
Q_{rr}	Reverse recovery charge		-	1.9		µC
I_{RRM}	Reverse recovery current		-	7.5		A

1. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*
2. *Pulse width is limited by safe operating area.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characterisics




Figure 4. Transfer characteristics




Figure 5. Static drain-source on resistance




Figure 6. Gate charge vs gate-source voltage




Figure 7. Capacitance variations




Figure 8. Normalized gate threshold voltage vs temperature




Figure 9. Normalized on resistance vs temperature




Figure 10. Source-drain diode forward characteristics




Figure 11. Normalized $V_{(BR)DSS}$ vs temperature






Figure 12. Maximum avalanche energy vs temperature




3 Test circuits

Figure 13. Test circuit for resistive load switching times




AM01468v1

Figure 14. Test circuit for gate charge behavior




AM01469v1

Figure 15. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 16. Unclamped inductive load test circuit




AM01471v1

Figure 17. Unclamped inductive waveform



AM01472v1

Figure 18. Switching time waveform




AM01473v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 DPAK (TO-252) type C3 package information

Figure 19. DPAK (TO-252) type C3 package outline




0068772_type-C3_rev34

Table 8. **DPAK (TO-252) type C3 mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	2.20	2.30	2.38
A1	0.00		0.10
A2	0.90	1.01	1.10
b	0.72		0.85
b2	0.72		1.10
b3	5.13	5.33	5.46
c	0.47		0.60
c2	0.47		0.60
D	6.00	6.10	6.20
D1	5.20	5.45	5.70
E	6.50	6.60	6.70
E1	5.00	5.20	5.40
e	2.186	2.286	2.386
H	9.80	10.10	10.40
L	1.40	1.50	1.70
L1	2.90 REF		
L2	0.51 BSC		
L3	0.90		1.25
L4	0.60	0.80	1.00
L5	0.15		0.75
L6	1.80 REF		
θ	0°		8°
θ1	5°	7°	9°
θ2	5°	7°	9°

4.2 DPAK (TO-252) type E package information

Figure 20. **DPAK (TO-252) type E package outline**




0068772_typeE_rev.34

Table 9. **DPAK (TO-252) type E mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	2.18		2.39
A2			0.13
b	0.65		0.884
b4	4.95		5.46
c	0.46		0.61
c2	0.46		0.60
D	5.97		6.22
D1	5.21		
E	6.35		6.73
E1	4.32		
e		2.286	
e1		4.572	
H	9.94		10.34
L	1.50		1.78
L1		2.74	
L2	0.89		1.27
L4			1.02

Figure 21. DPAK (TO-252) recommended footprint (dimensions are in mm)



Notes:

1) This footprint is able to ensure insulation up to 630 Vrms (according to CEI IEC 664−1)

2) The device must be positioned within ⌖ 0.05 A B

FP_0068772_34

4.3 DPAK (TO-252) packing information

Figure 22. **DPAK (TO-252) tape outline**





Figure 23. **DPAK (TO-252) reel outline**



AM06038v1

Table 10. **DPAK (TO-252) tape and reel mechanical data**

Tape			Reel		
Dim.	mm		Dim.	mm	
	Min.	Max.		Min.	Max.
A0	6.8	7	A		330
B0	10.4	10.6	B	1.5	
B1		12.1	C	12.8	13.2
D	1.5	1.6	D	20.2	
D1	1.5		G	16.4	18.4
E	1.65	1.85	N	50	
F	7.4	7.6	T		22.4
K0	2.55	2.75			
P0	3.9	4.1	Base qty.		2500
P1	7.9	8.1	Bulk qty.		2500
P2	1.9	2.1			
R	40				
T	0.25	0.35			
W	15.7	16.3			

Revision history

Table 11. **Document revision history**

Date	Revision	Changes
06-Oct-2004	1	First version
08-Sep-2005	2	Complete version
05-Mar-2006	3	Inserted Ecopack indication
27-Jul-2006	4	New template, no content change
28-Jun-2018	5	Removed maturity status indication from cover page. The document status is production data. Updated title in cover page, *Section 1 Electrical ratings*, *Section 2 Electrical characteristics* and *Section 4 Package information*. Minor text changes.
02-Oct-2023	6	The part numbers STD2NK90Z-1 and STP2NK90Z have been moved to a separate datasheet and the document has been updated accordingly. Updated title on cover page. Removed "*Table 8. Gate-source Zener diode*". Removed "*Section 4.2 DPAK (TO-252) type A2 package information*", replaced "*Section 4.3 DPAK (TO-252) type A2 package information*" with Section 4.1 DPAK (TO-252) type C3 package information and updated Section 4.2 DPAK (TO-252) type E package information. Minor text changes.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 7
4 **Package information** 8
4.1 DPAK (TO-252) type C3 package information 8
4.2 DPAK (TO-252) type E package information 10
4.3 DPAK (TO-252) packing information 13
Revision history 15

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2023 STMicroelectronics – All rights reserved